

Table of Contents

1. Unmatched queries using outer join.....	1
2. Queries using the AltgeldMart tables	2
3. Unmatched queries using subqueries.....	3
4. What can go wrong?	4

Inner joins are great for finding Customers with Orders and for finding Products that have been ordered. But we often want to find customers who have no orders or products that no one has ordered. These are sometimes called unmatched queries since we are looking for customers in the customer table who have no matching rows in the order headers table. We will see several ways to do this. For now we will look at two approaches: (1) using the outer join and (2) using subqueries.

1. Unmatched queries using outer join

In the previous document we used the outer join to find employees **with and without** an assigned department. A variation on the outer join is a query to display only those employees who have no assigned department. Be careful to select the proper column for testing against null. With these tests you do not want to use the join with the Using (col) syntax because you have to specify the exact column you are looking for. Compare the following two queries. We want departments with no employees.

Demo 01: Unmatched rows. Departments which do not have any employees

```
select z_em_Emp.D_ID as "EM_Emp.D_ID"
, z_em_Dept.D_ID as "EM_Dept.D_ID"
, D_Name
from z_em_Dept
LEFT JOIN z_em_Emp ON z_em_Dept.d_id = z_em_Emp.D_ID
where z_em_Emp.D_ID IS NULL;
```

EM_Emp.D_ID	EM_Dept.D_ID	D_NAME
-----	-----	-----
	200	MARKETING

Demo 02: Unmatched rows. This syntax will not work since the USING clause means that we cannot qualify D_ID to specify the table name. Note that this does not present as an error; we simply get no rows returned.

```
select D_ID as "EM_Emp.D_ID"
, D_ID as "EM_Dept.D_ID"
, D_Name
from z_em_Dept
LEFT JOIN z_em_Emp Using (D_ID)
where D_ID IS NULL;
```

no rows selected

Demo 03: Unmatched rows. Take care which attribute you test. Since we are retrieving all data from the department table, we will not have nulls in the department table id attribute.

```
select z_em_Emp.D_ID as "EM_Emp.D_ID"
, z_em_Dept.D_ID as "EM_Dept.D_ID"
, D_Name
from z_em_Dept
LEFT JOIN z_em_Emp ON z_em_Dept.d_id = z_em_Emp.D_ID
where z_em_Dept.D_ID IS NULL
;
```

no rows selected

Demo 04: If you have troubles with setting up this type of query, run the query without the null filter first and examine the columns for the rows you want to return. Here we can see that we want to test the `z_em_Emp.d_id` column for nulls.

```
select z_em_Emp.D_ID as "EM_Emp.D_ID"
, z_em_Dept.D_ID as "EM_Dept.D_ID"
, D_Name
from z_em_Dept
LEFT JOIN z_em_Emp ON z_em_Dept.d_id = z_em_Emp.D_ID
;
```

EM_Emp.D_ID	EM_Dept.D_ID	D_NAME
150	150	Accounting
150	150	Accounting
250	250	Research
100	100	Manufacturing
	200	Marketing

2. Queries using the AltgeldMart tables

Demo 05: Customers without orders. We have an outer join from customers left join order headers to get customers with and without orders and then we filter for just rows where the order id in the order headers table is null.

```
select CS.customer_id
, CS.customer_name_last
, OH.order_id
from cust_customers CS
left join oe_orderHeaders OH on CS.customer_id = OH.customer_id
where OH.order_id IS NULL
order by CS.customer_id;
```

CUSTOMER_ID	CUSTOMER_NAME_LAST	ORDER_ID
400801	Washington	
402110	Coltrane	
402120	McCoy	
402500	Jones	
403500	Stevenson	
403750	O'Leary	
403760	O'Leary	
404150	Dancer	
404180	Shay	
. . . rows omitted		

Demo 06: If we try to find orders with no customers, we have no rows returned. Our database is set up to reject any order that is not associated with a customer. This would be a good query to run on poorly designed databases to locate orphaned rows.

```
select
  CS.customer_id
, CS.customer_name_last
, OH.order_id
from oe_orderHeaders OH
Left Join cust_customers CS On CS.customer_id = OH.customer_id
where OH.customer_id Is Null;
```

no rows selected

Demo 07: What is the product name and list price for the products that are not selling? These would be products in the products table that do not appear on any order.

```
select
  catg_id
, prod_id
, prod_desc As product
, prod_list_price
from prd_products
Left Join oe_orderDetails Using (prod_id)
where order_id Is Null
order by catg_id, prod_id;
```

CATG_ID	PROD_ID	PRODUCT	PROD_LIST_PRICE
APL	1126	Low Energy Washer Dryer combo	850
APL	4569	Sized for the apartment	349.95
GFD	5000	Cello bag of mixed fingerling potatoes	12.5
GFD	5001	Dundee Ginger Preserve 12 oz jar	5
HW	1160	Stand Mixer with attachments	149.99
HW	4575	GE model 34PG98	49.95
MUS	2234	Charles Mingus - Pithecanthropus Erectus	15.88
MUS	2337	John Coltrane - Blue Train	15.87
MUS	2487	Stanley Turrentine - Don't Mess With Mr. T	9.45
MUS	2933	David Newman - I Remember Brother Ray	12.45
MUS	2987	Stanley Turrentine - Ballads	15.87
PET	1142	Bird seed mix with sunflowers	2.5
PET	1143	Bird seed mix with more sunflower seeds	2.5
PET	4567	Our highest end cat tree- you gotta see this	549.99
PET	4568	Satin four-poster cat bed	549.99

3. Unmatched queries using subqueries

The unmatched pattern we have used gets customer with and without orders and then filters away the customers with orders.

Some people find the subquery syntax easier to understand. The subquery approach says to find rows where we have a value in one table and we do not have that value in another table. For example, customers in the customer table but that customer is not in the order-headers table.

Demo 08: These are customers without orders query done using a subquery.

The subquery gets the cust_id for customers with orders and then the main query filters those out using the NOT IN test. That gives us the customers with no orders.

```
select
  customer_id
, customer_name_last
from cust_customers
where customer_id Not In (
  select customer_id
  from oe_orderHeaders
);
```

CUSTOMER_ID	CUSTOMER_NAME_LAST
400801	Washington
402110	Coltrane
402120	McCoy
402500	Jones

```

403500 Stevenson
403750 O'Leary
403760 O'Leary
404150 Dancer
404180 Shay
. . . rows omitted

```

Notice that we are comparing the `customer_id` in the `customers` table with a list of `customer_id` values from the `order_headers` table. We compare `customer_id` to `customer_id`. This is similar to the join logic.

Demo 09: What is the product name and list price for the products that are not selling? These would be products in the `products` table that do not appear on any order.

This query does not need table aliases for `prod_id` since each part of the query is referencing a single table.

```

select catg_id
, prod_id
, prod_desc as product
, prod_list_price
from prd_products
where prod_id NOT IN (
    select prod_id
    from oe_order_details)
order by catg_id, prod_id ;

```

CATG_ID	PROD_ID	PRODUCT	PROD_LIST_PRICE
APL	1126	Low Energy washer Dryer combo	850
APL	4569	Sized for the apartment	349.95
GFD	5000	Cello bag of mixed fingerling potatoes	12.5
GFD	5001	Dundee Ginger Preserve 12 oz jar	5
HW	1160	Stand Mixer with attachments	149.99
HW	4575	GE model 34PG98	49.95
MUS	2234	Charles Mingus - Pithecanthropus Erectus	15.88
MUS	2337	John Coltrane - Blue Train	15.87
MUS	2487	Stanley Turrentine - Don't Mess With Mr. T	9.45
MUS	2933	David Newman - I Remember Brother Ray	12.45
MUS	2987	Stanley Turrentine - Ballads	15.87
PET	1142	Bird seed mix with sunflowers	2.5
PET	1143	Bird seed mix with more sunflower seeds	2.5
PET	4567	Our highest end cat tree- you gotta see this	549.99
PET	4568	Satin four-poster cat bed	549.99

4. What can go wrong?

Suppose we want to find employees who are not associated with any orders. Remember that in the `order_headers` table, the employee who took the order is referred to as the `sales_rep`. First do a left join to see what the data looks like.

Demo 10: Left join Employees to Orders

```

select
    emp_id
, name_last
, order_id
from emp_employees
Left Join oe_orderHeaders On emp_id = sales_rep_id
;

```

EMP_ID	NAME_LAST	ORDER_ID
100	King	
101	Koch	
102	D'Haa	
103	Hunol	
104	Ernst	
108	Green	
109	Fiet	
110	Chen	
145	Russ	112
145	Russ	540
145	Russ	2505
145	Russ	405
145	Russ	130
145	Russ	312
. . . rows omitted		

Some employees have served as a sales rep and some have taken more than one order. We could add a filter to find the rows where the Order_id is null.

Demo 11: Left join Employees to Orders with null order id. These are employees who are not associated with any order.

```
select emp_id, name_last
from emp_employees
Left Join oe_orderHeaders On emp_id = sales_rep_id
where order_id Is Null;
```

EMP_ID	NAME_LAST
100	King
101	Koch
102	D'Haa
103	Hunol
104	Ernst
108	Green
109	Fiet
110	Chen
146	Partne
. . . rows omitted	
18 rows selected.	

What if we try this with a subquery?

Demo 12: Subquery version 1 We filter for employee id values that are not in the appropriate column (sales_rep_id) in the order headers table. This returns no rows at all! Before you read on to the next demo. try to figure out why this might happen. (What is the usual villain when a query goes bad?)

```
select emp_id, name_last
from emp_employees
where emp_id Not In (
  select sales_rep_id
  from oe_orderHeaders
);
```

no rows selected

Remember that a Not In () predicate returns no rows if there is a null in the list.

Demo 13: Subquery version 2-Eliminate the nulls from the subquery.

```
select
  emp_id
, name_last
from emp_employees
where emp_id Not In (
  select sales_rep_id
  from oe_orderHeaders
  where sales_rep_id Is Not Null
);
Same result set as with the outer join
```

So now the question is: why did the other subqueries work? We were filtering on an attribute that was a not null attribute.