

## Table of Contents

1. Column Alias..... 1
2. Table Alias/Correlation Name/ Tuple Variable/Range Variable ..... 1

There are two places in a Select statement where you might create something referred to as an alias. One is a column alias that you could use in the Select clause. The other is a table alias.

## 1. Column Alias

One use for column aliases is to make the output easier to understand.

This query does not use any column aliases; With Oracle if you have an expression that does not have a column alias, then the expression is used instead.

```
select order_id, prod_id, quoted_price, quantity_ordered
, quoted_price * quantity_ordered
from oe orderDetails;
```

ORD_ID	PROD_ID	QUOTED_PRICE	QUANTITY_ORDERED	QUOTED_PRICE*QUANTITY_ORDERED
400	5002	23	5	115
400	5004	15	5	75

Now we have an alias for several of the columns; the column alias is used as the column header; it can be used in the Order By clause- but not in the Where clause.

```
select order_id, prod_id
, quoted_price AS PRICE
, quantity_ordered AS QUANTITY
, quoted_price * quantity_ordered AS ExtCost
from oe orderDetails;
```

ORD_ID	PROD_ID	PRICE	QUANTITY	EXTCOST
400	5002	23	5	115
400	5004	15	5	75

Note that Oracle will let you use the same column alias for more than one column in the result. That is generally not advisable since the column alias should identify the column.

## 2. Table Alias/Correlation Name/ Tuple Variable/Range Variable

We can also designate an alternate name for a table. This is most commonly called a table alias; Oracle often uses the term correlation names; you may also see this called a tuple variable or a range variable. I'll generally use the term table alias since it is the most commonly used.

The table alias is defined in the From clause of the SQL statement and is limited in scope to that statement. The table alias is not saved on the server. Once you establish a table alias in a query, you need to use that alias, not the table name, in the other clauses of that query. You are not allowed to use the same table alias for two different tables in the query.

The use of table aliases is very common in SQL and you need to be aware of its use. However, poorly defined table aliases can make a query harder to read and understand.

The table alias is commonly a single letter but a single letter alias is often difficult to understand and remember. You should not have to keep referring to the From clause to interpret the Select clause. Table aliases can be longer than one character to make them more meaningful.

Some types of queries require the use of table aliases since the same table is included in the query more than once. In other queries, it is optional.

Each of the following queries will run. Each of these queries uses a single table and does not require the use of qualification of the columns in the Select or Where clause.

```
select order_id
, prod_id
, quoted_price
from oe_orderDetails
where quoted_price = 150.00;
```

This query qualifies each column name and uses the full table name; this is rather long and harder to read.

```
select oe_orderDetails.order_id
, oe_orderDetails.prod_id
, oe_orderDetails.quoted_price
from oe_orderDetails
where oe_orderDetails.quoted_price = 150.00;
```

This query qualifies each column name and uses a table alias; this is easier to read.

```
select od.order_id
, od.prod_id
, od.quoted_price
from oe_orderDetails od
where od.quoted_price = 150.00;
```

In this statement we use the token "od" for two different purposes. In the From clause, it identifies the table and stands for the set of rows that make up that table at the present time. In the Select and the Where clauses, "od" refers to a row at a time.

When we say

```
where od.quoted_price = 150.00
```

we are not testing that the entire table set of rows has a value for quoted\_price of 150.00, or that at least one of the rows has that value; we are testing for each row- one row at a time- if that row has the value 150.00 for the quoted\_price column in that row.

Likewise in the Select clause, the expression od.ord\_id stands for the ord\_id column of each row- one row at a time.

(This understanding of the token 'od' is the basis for calling this a tuple variable or a range variable.)