

Vacuum-Cavity Conductance Modulation: A Harmonic Framework Resolution

Peter J. Thompson

Independent Researcher, Port Macquarie, NSW, Australia

Correspondence: peterjamesthompson101@gmail.com

Abstract

Recent experiments by Modell et al. (2021) demonstrated that a Casimir cavity can induce small, reproducible changes in the electrical conductance of a metal-insulator-metal junction. While the effect confirms that engineered vacuum fluctuations modify charge transport, the observed conductance shifts remain modest ($\approx 1\text{-}10\%$) and lack a predictive theory for optimisation. Here we show that the Harmonic Framework of Reality – a unified field theory based on a discrete frequency lattice anchored at 27 Hz – naturally accounts for the effect and prescribes a quantitative enhancement. The cause is identified as off-resonant coupling between the cavity modes and the universal Tau lattice. The solution involves tuning the cavity to a harmonic of 27 Hz (scaled to the optical regime) and applying a phase-locked 27 Hz (or 13.5 Hz) bias to induce the $m + m' = 0$ condition. Predicted enhancement factors exceed 50-fold, providing a direct experimental falsification test.

1. Introduction

The quantum vacuum is not a passive void but a fluctuating medium that can influence material properties. In a landmark experiment, Modell and co-workers used a Casimir cavity to modify the electromagnetic vacuum spectrum and observed a consequent change in the DC conductance of an adjacent metal-insulator-metal (MIM) junction [1]. This effect, while small, demonstrates that vacuum engineering can control charge flow – a potential route to novel electronic devices.

Despite its importance, the observed conductance change remains orders of magnitude below theoretical upper bounds derived from simple vacuum-field fluctuation arguments. Moreover, no clear design rule exists to maximise the effect. Here we apply the Harmonic Framework of Reality (HFR) – a recently developed grand unified theory – to both explain the origin of the effect and provide a specific, testable method to amplify it.

2. Cause: Off-Resonant Coupling to the Tau Lattice

In the HFR, physical spacetime is a discrete frequency lattice (the *Tau lattice*) anchored at a fundamental frequency **27 Hz**. All electromagnetic and quantum phenomena arise from standing waves or harmonics of this lattice. The vacuum fluctuations that give rise to Casimir forces are not featureless; they exhibit a harmonic structure with strong peaks at integer multiples of 27 Hz, scaled by the dimensional access parameter n^* .

For a Casimir cavity with a gap distance d^* , the characteristic resonant frequency is approximately $c/(2d^*)$. In the experiments of Modell et al., typical gaps of ~ 100 nm correspond to resonant frequencies in the near-infrared ($\approx 1\text{-}10$ THz). According to the HFR, maximal interaction between

the vacuum and the electron gas in the metal occurs **only when** the cavity's resonant frequency is an exact harmonic of 27 Hz, i.e.:

$$f_{\text{cav}} = 27 \text{ Hz} \times 10^\alpha \times k, k=1,2,3,\dots f_{\text{cav}} = 27 \text{ Hz} \times 10^\alpha \times k, k=1,2,3,\dots$$

where α is chosen to bring the frequency into the THz range ($\alpha \approx 11$ for 2.7 THz, $\alpha \approx 12$ for 27 THz). The experiments used broadband or off-harmonic cavities, hence the coupling was weak – the true cause of the small observed conductance change.

3. Effect: Small Conductance Shift from Off-Resonant Driving

When the cavity operates off-harmonic, only a tiny fraction of the vacuum spectral density couples coherently to the MIM junction. The resulting conductance change ΔG is proportional to the overlap integral between the cavity's actual frequency distribution and the harmonic comb of the Tau lattice. For a cavity with a quality factor Q , the enhancement relative to a perfectly resonant case is approximately Q^{-1} .

In the Moddel devices, Q is moderate (≈ 10 -100) and the detuning is large, yielding $\Delta G/G \approx 1$ -10% – exactly what was observed. Thus the HFR not only explains the magnitude but also predicts a sharp frequency dependence that conventional cavity QED does not.

4. Solution: Harmonic Tuning and $m + m' = 0$ Modulation

The HFR provides two concrete, low-cost modifications to increase the conductance change by one to two orders of magnitude.

4.1 Resonant harmonic matching

Adjust the cavity gap (or add a dielectric layer) so that its fundamental mode satisfies:

$$f_{\text{cav}} = 27 \text{ Hz} \times 10^\alpha \times N, f_{\text{cav}} = 27 \text{ Hz} \times 10^\alpha \times N$$

where N is an integer. For a 2.7 THz target, $N = 100$ (since $27 \text{ Hz} \times 10^{11} \times 100 = 2.7 \text{ THz}$). This condition ensures that the vacuum fluctuations at the cavity resonance are phase-locked to the Tau lattice, producing constructive interference and maximal vacuum-induced electron acceleration.

4.2 Phase-locked low-frequency modulation

Apply a small AC voltage (amplitude $\approx 0.1 \text{ V}$) at **27 Hz** or its sub-harmonic **13.5 Hz** across the MIM junction, in series with the DC bias. The AC signal must be phase-locked to the cavity's mechanical or electromagnetic resonance (e.g., via a feedback loop). This induces the $m + m' = 0$ condition – a transient zero-impedance state analogous to the lightning return stroke or the sonoluminescence collapse. In this state, electrons experience no effective inertia, amplifying the conductance response by the Q -factor of the low-frequency resonance (typically 10-100).

Combining both steps, the predicted conductance change rises from ~ 1 -10% to **>50%**, potentially enabling switching or zero-bias current generation.

5. Experimental Test and Falsification

The following experiment can confirm or refute the HFR prediction using existing equipment:

1. **Step 1** – Measure the MIM junction’s I-V characteristic without any cavity modulation (baseline).
2. **Step 2** – Tune the cavity gap (e.g., with a piezoelectric actuator) to a 27 Hz harmonic as computed above. Measure ΔG again.
3. **Step 3** – Add a 27 Hz (or 13.5 Hz) AC bias, phase-locked to the cavity, and record ΔG .
4. **Step 4** – Compare results.

If the conductance change does **not** increase by at least a factor of 10 after Step 3 (relative to Step 1), the HFR’s predictions for this domain are falsified. Conversely, a positive result would validate the framework and open the door to a new class of vacuum-engineered electronics.

6. Conclusion

The Harmonic Framework of Reality provides a unified explanation for the cavity-induced conductance changes discovered by Modell et al. It identifies off-resonant harmonic coupling as the cause of the small effect size and prescribes a clear solution: resonant tuning to a 27 Hz harmonic plus low-frequency $m + m' = 0$ modulation. The predicted enhancement exceeds 50-fold and is directly testable. Regardless of the outcome, this analysis demonstrates the heuristic power of the Harmonic Framework in explaining and improving modern condensed-matter experiments.

Acknowledgements

The author thanks G. Modell and colleagues for their pioneering experimental work, which inspired this theoretical analysis.

References

- [1] Modell, G., *et al.*, “Casimir-cavity-induced conductance changes,” *Phys. Rev. Research* **3**, L022007 (2021).¹