



root@localhost:~



File Edit View Search Terminal Help

```
[oracle@localhost ~]$ su -
```

```
Password:
```

```
[root@localhost ~]# mkdir -p /u01/app/oracle/product/19.0.0/dbhome_1
```

```
[root@localhost ~]# usermod -g oinstall oracle
```

```
[root@localhost ~]# usermod -aG dba oracle
```

```
[root@localhost ~]# id
```

```
uid=0(root) gid=0(root) groups=0(root) context=unconfined_u:unconfined_r:unconfi  
ned_t:s0-s0:c0.c1023
```

```
[root@localhost ~]# █
```



root@localhost:~



File Edit View Search Terminal Help

Password:

```
[root@localhost ~]# mkdir -p /u01/app/oracle/product/19.0.0/dbhome_1
```

```
[root@localhost ~]# groupadd oinstall
```

```
[root@localhost ~]# groupadd dba
```

```
[root@localhost ~]# groupadd oper
```

```
[root@localhost ~]# usermod -g oinstall oracle
[root@localhost ~]# usermod -aG dba oracle
[root@localhost ~]# id
uid=0(root) gid=0(root) groups=0(root) context=unconfined_u:unconfined_r:unconfi
ned_t:s0-s0:c0.c1023
[root@localhost ~]# exit
logout
[oracle@localhost ~]$ id
uid=1000(oracle) gid=1000(oracle) groups=1000(oracle),10(wheel) context=unconfin
ed_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
[oracle@localhost ~]$ id oracle
uid=1000(oracle) gid=1001(oinstall) groups=1001(oinstall),10(wheel),1002(dba)
[oracle@localhost ~]$
```

```
root@localhost:~  
File Edit View Search Terminal Help  
[oracle@localhost ~]$ su -  
Password:  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/oracle  
[root@localhost ~]# chown -R oracle:oinstall /u01/app  
[root@localhost ~]# chown -R oracle:oinstall /u01  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/oracle/product  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/oracle/product/19.0.0  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/oracle/product/19.0.0/dbhome_1  
[root@localhost ~]# mkdir -p /u01/app/orainventory  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/orainventory  
[root@localhost ~]# mkdir -p /u01/app/oracle/oradata  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/oracle/oradata  
[root@localhost ~]# mkdir -p /u01/app/oracle/fast_recovery_area  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/oracle/fast_recovery_area  
[root@localhost ~]#
```

```
root@localhost:~  
File Edit View Search Terminal Help  
[oracle@localhost ~]$ su -  
Password:  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/oracle  
[root@localhost ~]# chown -R oracle:oinstall /u01/app  
[root@localhost ~]# chown -R oracle:oinstall /u01  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/oracle/product  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/oracle/product/19.0.0  
[root@localhost ~]# chown -R oracle:oinstall /u01/app/oracle/product/19.0.0/dbhome_1  
[root@localhost ~]#
```

```
[oracle@localhost ~]$ export ORACLE_HOME=/u01/app/oracle/product/19.0.0/dbhome_1
[oracle@localhost ~]$ export ORACLE_BASE=/u01/app/oracle
[oracle@localhost ~]$ export ORACLE_SID=orcl
[oracle@localhost ~]$ export PATH=$ORACLE_HOME/bin:$PATH
[oracle@localhost ~]$ cat >> ~/.bash_profile <<'EOF'
> export ORACLE_SID=orcl
> export ORACLE_BASE=/u01/app/oracle
> export ORACLE_HOME=/u01/app/oracle/product/19.0.0/dbhome_1
> export PATH=$ORACLE_HOME/bin:$PATH
> EOF
[oracle@localhost ~]$ source ~/.bash_profile
[oracle@localhost ~]$ cat > /etc/oraInst.loc <<'EOF'
> inventory_loc=/u01/app/oraInventory
> inst_group=oinstall
> EOF
bash: /etc/oraInst.loc: Permission denied
[oracle@localhost ~]$ su -
Password:
su: Authentication failure
[oracle@localhost ~]$ Oracle@123
bash: Oracle@123: command not found...

\[oracle@localhost ~]$
[oracle@localhost ~]$ su -
Password:
[root@localhost ~]# cat > /etc/oraInst.loc <<'EOF'
> inventory_loc=/u01/app/oraInventory
> inst_group=oinstall
> EOF
[root@localhost ~]# cat > /etc/oraInst.loc <<'EOF'
> inventory_loc=/u01/app/oraInventory
> inst_group=oinstall
>
>
>
>
>
>
>
>
>
> ^C
[root@localhost ~]# cat /etc/oraInst.loc
inventory_loc=/u01/app/oraInventory
inst_group=oinstall
[root@localhost ~]#
```

```
root@localhost:~
File Edit View Search Terminal Help
[root@localhost ~]# dnf install -y gcc
Oracle Linux 8 BaseOS Latest (x86_64) 3.8 MB/s | 166 MB 00:43
Oracle Linux 8 Application Stream (x86_64) 3.1 MB/s | 86 MB 00:27
Latest Unbreakable Enterprise Kernel Release 7 for Oracle Linux 8 (x86_64) 3.5 MB/s | 120 MB 00:34
Last metadata expiration check: 0:00:47 ago on Sun 20 Sep 2026 07:09:35 AM EDT.
Dependencies resolved.
=====
Package Architecture Version Repository Size
=====
Installing:
gcc x86_64 8.5.0-28.0.1.el8_10 ol8_appstream 24 M
Upgrading:
libgcc x86_64 8.5.0-28.0.1.el8_10 ol8_baseos_latest 94 k
libgomp x86_64 8.5.0-28.0.1.el8_10 ol8_baseos_latest 219 k
Installing dependencies:
cpp x86_64 8.5.0-28.0.1.el8_10 ol8_appstream 10 M
glibc-devel x86_64 2.28-251.0.2.el8 ol8_baseos_latest 89 k
isl x86_64 0.16.1-6.el8 ol8_appstream 841 k
libxcrypt-devel x86_64 4.1.1-6.el8 ol8_baseos_latest 25 k
Transaction Summary
=====
Install 5 Packages
Upgrade 2 Packages

Total download size: 35 M
Downloading Packages:
(1/7): libxcrypt-devel-4.1.1-6.el8.x86_64.rpm 58 kB/s | 25 kB 00:00
(2/7): glibc-devel-2.28-251.0.2.el8.x86_64.rpm 166 kB/s | 89 kB 00:00
(3/7): isl-0.16.1-6.el8.x86_64.rpm 986 kB/s | 841 kB 00:00
(4/7): libgcc-8.5.0-28.0.1.el8_10.x86_64.rpm 98 kB/s | 94 kB 00:00
(5/7): libgomp-8.5.0-28.0.1.el8_10.x86_64.rpm 391 kB/s | 219 kB 00:00
(6/7): cpp-8.5.0-28.0.1.el8_10.x86_64.rpm 1.6 MB/s | 10 MB 00:06
(7/7): gcc-8.5.0-28.0.1.el8_10.x86_64.rpm 2.3 MB/s | 24 MB 00:10
-----
Total 3.3 MB/s | 35 MB 00:10
Oracle Linux 8 BaseOS Latest (x86_64) 3.0 MB/s | 3.1 kB 00:00
Importing GPG key 0xAD986DA3:
  Userid : "Oracle OSS group (Open Source Software group) <build@oss.oracle.com>"
  Fingerprint: 76FD 3DB1 3AB6 7410 B89D B10E 8256 2EA9 AD98 6DA3
  From : /etc/pki/rpm-gpg/RPM-GPG-KEY-oracle
Key imported successfully
Running transaction check
Transaction check succeeded.
Running transaction test
```

```
root@localhost:~
File Edit View Search Terminal Help
[root@localhost ~]# dnf install -y gcc-c++
Last metadata expiration check: 0:12:41 ago on Sun 20 Sep 2026 07:09:35 AM EDT.
Dependencies resolved.
=====
Package                                Architecture      Version           Repository        Size
=====
Installing:
gcc-c++                                x86_64            8.5.0-28.0.1.el8_10  ol8_appstream    12 M
Upgrading:
libstdc++                              x86_64            8.5.0-28.0.1.el8_10  ol8_baseos_latest 484 k
Installing dependencies:
libstdc++-devel                        x86_64            8.5.0-28.0.1.el8_10  ol8_appstream    2.1 M
=====
Transaction Summary
=====
Install 2 Packages
Upgrade 1 Package

Total download size: 15 M
Downloading Packages:
(1/3): libstdc++-8.5.0-28.0.1.el8_10.x86_64.rpm 540 kB/s | 484 kB 00:00
(2/3): libstdc++-devel-8.5.0-28.0.1.el8_10.x86_64.rpm 1.2 MB/s | 2.1 MB 00:01
(3/3): gcc-c++-8.5.0-28.0.1.el8_10.x86_64.rpm 2.8 MB/s | 12 MB 00:04
-----
Total                                          3.4 MB/s | 15 MB 00:04
Running transaction check
Transaction check succeeded.
Running transaction test
Transaction test succeeded.
Running transaction
  Preparing      : 1/1
  Upgrading      : libstdc++-8.5.0-28.0.1.el8_10.x86_64 1/4
  Running scriptlet: libstdc++-8.5.0-28.0.1.el8_10.x86_64 1/4
  Installing     : libstdc++-devel-8.5.0-28.0.1.el8_10.x86_64 2/4
  Installing     : gcc-c++-8.5.0-28.0.1.el8_10.x86_64 3/4
  Cleanup        : libstdc++-8.5.0-21.0.1.el8.x86_64 4/4
  Running scriptlet: libstdc++-8.5.0-21.0.1.el8.x86_64 4/4
  Verifying      : gcc-c++-8.5.0-28.0.1.el8_10.x86_64 1/4
  Verifying      : libstdc++-devel-8.5.0-28.0.1.el8_10.x86_64 2/4
  Verifying      : libstdc++-8.5.0-28.0.1.el8_10.x86_64 3/4
  Verifying      : libstdc++-8.5.0-21.0.1.el8.x86_64 4/4

Upgraded:
libstdc++-8.5.0-28.0.1.el8_10.x86_64
Installed:
```



root@localhost:~



File Edit View Search Terminal Help

```
[root@localhost ~]# dnf install -y libaio-devel
```

```
Last metadata expiration check: 0:15:17 ago on Sun 20 Sep 2026 07:09:35 AM EDT.
```

```
Dependencies resolved.
```

```
=====
Package                                Architecture      Version           Repository
Size
=====
Installing:
libaio-devel                          x86_64            0.3.112-1.el8    ol8_baseos_latest
19 k
=====
```

```
Transaction Summary
```

```
=====
Install 1 Package
```

```
Total download size: 19 k
```

```
Installed size: 8.7 k
```

```
Downloading Packages:
```

```
libaio-devel-0.3.112-1.el8.x86_64.rpm                                47 kB/s
| 19 kB    00:00
```

```
-----
Total                                                                47 kB/s
| 19 kB    00:00
```

```
Running transaction check
```

```
Transaction check succeeded.
```

```
Running transaction test
```

```
Transaction test succeeded.
```

```
Running transaction
```

```
Preparing :
1/1
```

```
Installing : libaio-devel-0.3.112-1.el8.x86_64
```

root@localhost:~

File Edit View Search Terminal Help

comp...
[root@localhost ~]# dnf install -y oracle-database-preinstall-19c
Last metadata expiration check: 0:17:31 ago on Sun 20 Sep 2026 07:09:35 AM EDT.
Dependencies resolved.

Package	Architecture	Version	Repository	Size
Installing:				
oracle-database-preinstall-19c	x86_64	1.0-4.el8	ol8_appstream	30 k
Installing dependencies:				
ksh	x86_64	20120801-272.0.1.el8_10	ol8_appstream	924 k
libnsl	x86_64	2.28-251.0.2.el8	ol8_baseos_latest	111 k
lm_sensors-libs	x86_64	3.4.0-23.20180522git70f7e08.el8	ol8_baseos_latest	59 k
make	x86_64	1:4.2.1-11.el8	ol8_baseos_latest	498 k
sysstat	x86_64	11.7.3-13.0.3.el8_10	ol8_appstream	427 k

Transaction Summary

Install 6 Packages

Total download size: 2.0 M
Installed size: 6.3 M
Downloading Packages:

(1/6): lm_sensors-libs-3.4.0-23.20180522git70f7e08.el8.x86_64.rpm	143 kB/s	59 kB	00:00
(2/6): libnsl-2.28-251.0.2.el8.x86_64.rpm	243 kB/s	111 kB	00:00
(3/6): oracle-database-preinstall-19c-1.0-4.el8.x86_64.rpm	379 kB/s	30 kB	00:00
(4/6): make-4.2.1-11.el8.x86_64.rpm	749 kB/s	498 kB	00:00
(5/6): sysstat-11.7.3-13.0.3.el8_10.x86_64.rpm	1.3 MB/s	427 kB	00:00
(6/6): ksh-20120801-272.0.1.el8_10.x86_64.rpm	1.8 MB/s	924 kB	00:00
Total	2.1 MB/s	2.0 MB	00:00

Running transaction check
Transaction check succeeded.
Running transaction test
Transaction test succeeded.
Running transaction

Preparing	:	1/1
Installing	: ksh-20120801-272.0.1.el8_10.x86_64	1/6
Running scriptlet:	ksh-20120801-272.0.1.el8_10.x86_64	1/6
Installing	: make-1:4.2.1-11.el8.x86_64	2/6
Running scriptlet:	make-1:4.2.1-11.el8.x86_64	2/6
Installing	: lm_sensors-libs-3.4.0-23.20180522git70f7e08.el8.x86_64	3/6
Running scriptlet:	lm_sensors-libs-3.4.0-23.20180522git70f7e08.el8.x86_64	3/6
Installing	: sysstat-11.7.3-13.0.3.el8_10.x86_64	4/6
Running scriptlet:	sysstat-11.7.3-13.0.3.el8_10.x86_64	4/6

```
[root@localhost ~]# dnf install -y xorg -x11 -utils
usage: dnf install [-c [config file]] [-q] [-v] [--version]
                  [--installroot [path]] [--nodocs] [--noplugins]
                  [--enableplugin [plugin]] [--disableplugin [plugin]]
                  [--releasever RELEASEVER] [--setopt SETOPTS]
                  [--skip-broken] [-h] [--allowerasing] [-b | --nobest] [-C]
                  [-R [minutes]] [-d [debug level]] [--debugsolver]
                  [--showduplicates] [-e ERRORLEVEL] [--obsoletes]
                  [--rpmverbosity [debug level name]] [-y] [--assumeno]
                  [--enablerepo [repo]] [--disablerepo [repo] | --repo
[repo]] [--enable | --disable] [-x [package]]
                  [--disableexcludes [repo]] [--repofrompath [repo,path]]
                  [--noautoremove] [--nogpgcheck] [--color COLOR] [--refresh]
                  [-4] [-6] [--destdir DESTDIR] [--downloadonly]
                  [--comment COMMENT] [--bugfix] [--enhancement]
                  [--newpackage] [--security] [--advisory ADVISORY]
                  [--bz BUGZILLA] [--cve CVES]
                  [--sec-severity {Critical,Important,Moderate,Low}]
                  [--forcearch ARCH]
                  PACKAGE [PACKAGE ...]
```

```
dnf install: error: unrecognized arguments: -utils
```

```
[root@localhost ~]# dnf install -y xorg-x11-utils
```

```
Last metadata expiration check: 0:01:35 ago on Sun 20 Sep 2026 07:27:44 AM EDT.
```

```
Package xorg-x11-utils-7.5-28.el8.x86_64 is already installed.
```

```
Dependencies resolved.
```

```
Nothing to do.
```

```
Complete!
```

```
[root@localhost ~]#
```

```
[root@localhost ~]# ls -lh /mnt/hgfs/
```

```
total 0
```

```
drwxrwxrwx. 1 root root 0 Sep 19 06:42 VM-Oracle
```

```
[root@localhost ~]# ls -lh /mnt/hgfs/VM-Oracle/
```

```
total 2.9G
```

```
-rwxrwxrwx. 1 root root 2.9G Sep 12 07:10 LINUX.X64_193000_db_home.zip
```

```
drwxrwxrwx. 1 root root 4.0K Sep 19 06:45 OEM 13.5
```

```
[root@localhost ~]# df -h /u01
```

Filesystem	Size	Used	Avail	Use%	Mounted on
------------	------	------	-------	------	------------

/dev/mapper/ol-root	70G	9.0G	61G	13%	/
---------------------	-----	------	-----	-----	---

```
[root@localhost ~]# ls -ld /u01/app/oracle/product/19.0.0/dbhome_1
```

```
drwxr-xr-x. 2 oracle oinstall 6 Sep 20 06:44 /u01/app/oracle/product/19.0.0/dbhome_1
```

```
[root@localhost ~]#
```

```
[root@localhost ~]# ls -lh /mnt/hgfs/
total 0
drwxrwxrwx. 1 root root 0 Sep 19 06:42 VM-Oracle
[root@localhost ~]# ls -lh /mnt/hgfs/VM-Oracle/
total 2.9G
-rwxrwxrwx. 1 root root 2.9G Sep 12 07:10 LINUX.X64_193000_db_home.zip
drwxrwxrwx. 1 root root 4.0K Sep 19 06:45 OEM 13.5
[root@localhost ~]# df -h /u01
Filesystem      Size  Used Avail Use% Mounted on
/dev/mapper/ol-root  70G   9.0G   61G  13% /
[root@localhost ~]# ls -ld /u01/app/oracle/product/19.0.0/dbhome_1
drwxr-xr-x. 2 oracle oinstall 6 Sep 20 06:44 /u01/app/oracle/product/19.0.0/dbhome_1
[root@localhost ~]# exit
logout
[oracle@localhost ~]$ cd /mnt/hgfs/
[oracle@localhost hgfs]$ ls
VM-Oracle
[oracle@localhost hgfs]$ cd VM-Oracle
[oracle@localhost VM-Oracle]$ ls
LINUX.X64_193000_db_home.zip OEM 13.5
[oracle@localhost VM-Oracle]$ export display = :0
bash: export: `=': not a valid identifier
bash: export: `:0': not a valid identifier
[oracle@localhost VM-Oracle]$ export DISPLAY=:0
[oracle@localhost VM-Oracle]$
```

```
[oracle@localhost VM-Oracle]$ unzip /mnt/hgfs/VM-Oracle/LINUX.X64_193000_db_home.zip \
> -d /u01/app/oracle/product/19.0.0/dbhome_1
Archive:  /mnt/hgfs/VM-Oracle/LINUX.X64_193000_db_home.zip
  creating: /u01/app/oracle/product/19.0.0/dbhome_1/drdaas/
  creating: /u01/app/oracle/product/19.0.0/dbhome_1/drdaas/admin/
 inflating: /u01/app/oracle/product/19.0.0/dbhome_1/drdaas/admin/drdsqtt_translator_setup.sql
 inflating: /u01/app/oracle/product/19.0.0/dbhome_1/drdaas/admin/drdapkg_db2.sql
 inflating: /u01/app/oracle/product/19.0.0/dbhome_1/drdaas/admin/drdaas.ora
 inflating: /u01/app/oracle/product/19.0.0/dbhome_1/drdaas/admin/drdsqt_set_profile_dd.sql
  creating: /u01/app/oracle/product/19.0.0/dbhome_1/drdaas/lib/
 inflating: /u01/app/oracle/product/19.0.0/dbhome_1/drdaas/lib/s0dpspmain.o
 inflating: /u01/app/oracle/product/19.0.0/dbhome_1/drdaas/lib/s0dpsscmain.o
 inflating: /u01/app/oracle/product/19.0.0/dbhome_1/drdaas/lib/s0dpssmain.o
  creating: /u01/app/oracle/product/19.0.0/dbhome_1/instantclient/
 inflating: /u01/app/oracle/product/19.0.0/dbhome_1/instantclient/libsqlplusic.so
 inflating: /u01/app/oracle/product/19.0.0/dbhome_1/schagent.conf
  creating: /u01/app/oracle/product/19.0.0/dbhome_1/opmn/
```

```
oracle@localhost:/u01/app/oracle/product/19.0.0/dbhome_1
File Edit View Search Terminal Help
[oracle@localhost ~]$ cd /u01/app/oracle/product/19.0.0/dbhome_1
[oracle@localhost dbhome_1]$ ls
addnode      deinstall    javavm      OPatch      R            sqlj
apex         demo         jdbc        opmn        racg         sqlpatch
assistants  diagnostics  jdk         oracore     rdbms        sqlplus
bin          dmdu         jlib        ord         relnotes     srvrm
clone       drdaas       ldap        ords        root.sh      suptools
crs          dv           lib         oss         root.sh.old  ucp
css          env.ora      md          oui         root.sh.old.1 usm
ctx          has          mgw         owm         runInstaller utl
cv           hs           network     perl        schagent.conf wwg
data         install      nls         plssql      sdk          xdk
dbjava       instantclient odbc        precomp     slax
dbs          inventory    olap        OPatch      sqldeveloper

[oracle@localhost dbhome_1]$ echo $DISPLAY
:0
[oracle@localhost dbhome_1]$ ./runInstaller
```

oracle@localhost:/u01/app/oracle/product/19.0.0/dbhome_1

File Edit View Search Terminal Help

```
[root@localhost dbhome_1]# export PATH=$ORACLE_HOME/bin:$PATH
```

```
[root@localhost dbhome_1]# export DISPLAY=:0
```

```
[root@localhost dbhome_1]# echo $CV_ASSUME_DISTID
```

```
DL7
```

```
[root@localhost dbhome_1]# cd $ORACLE_HOME
```

```
[root@localhost dbhome_1]# su - oracle
```

```
[oracle@localhost ~]$ cd /u01/app/oracle/product/1
```

```
[oracle@localhost dbhome_1]$ echo $ORACLE_HOME
```

```
/u01/app/oracle/product/19.0.0/dbhome_1
```

```
[oracle@localhost dbhome_1]$ echo $CV_ASSUME_DISTID
```

```
[oracle@localhost dbhome_1]$ export CV_ASSUME_DISTID
```

```
[oracle@localhost dbhome_1]$ export DISPLAY=:0
```

```
[oracle@localhost dbhome_1]$ export PATH=$ORACLE_H
```

```
[oracle@localhost dbhome_1]$ export ORACLE_SID=orc
```

```
[oracle@localhost dbhome_1]$ export ORACLE_BASE=/u
```

```
[oracle@localhost dbhome_1]$ export ORACLE_HOME=/u
```

```
dbhome_1
```

```
[oracle@localhost dbhome_1]$ whoami
```

```
oracle
```

```
[oracle@localhost dbhome_1]$ ./runInstaller
```

```
Launching Oracle Database Setup Wizard...
```

```
[oracle@localhost dbhome_1]$
```

Oracle Database 19c Installer - Step 1 of 9

Select Configuration Option

19^c ORACLE[®]
Database

- Configuration Option
- Database Installation Options
- Install Type
 - Typical Installation
 - Root script execution
 - Prerequisite Checks
 - Summary
 - Install Product
 - Finish

Select any of the following install options.

- ☒ Create and configure a single instance database.
This option creates a starter database.
- ☐ Set Up Software Only

Note 1: For RAC install, do 'Set Up Software Only' and then execute DBCA (Database Configuration Assistant) from the oracle home.

Note 2: To upgrade an Oracle Database, do 'Set Up Software Only' and then execute DBUA (Database Upgrade Assistant) from the oracle home.

Help

< Back

Next >

Install

Cancel

oracle@localhost:/u01/app/oracle/product/19.0.0/dbhome_1

File Edit View Search Terminal Help

```
[root@localhost dbhome_1]# export PATH=$ORACLE_HOME/bin:$PATH
```

```
[root@localhost dbhome_1]# export DISPLAY=:0
```

```
[root@localhost dbhome_1]# echo $CV_ASSUME_DISTID
```

```
OL7
```

```
[root@localhost dbhome_1]# cd $ORACLE_HOME
```

```
[root@localhost dbhome_1]# su - oracle
```

```
[oracle@localhost ~]$ cd /u01/app/oracle/product/1
```

```
[oracle@localhost dbhome_1]$ echo $ORACLE_HOME
```

```
/u01/app/oracle/product/19.0.0/dbhome_1
```

```
[oracle@localhost dbhome_1]$ echo $CV_ASSUME_DISTID
```

```
[oracle@localhost dbhome_1]$ export CV_ASSUME_DISTID=OL7
```

```
[oracle@localhost dbhome_1]$ export DISPLAY=:0
```

```
[oracle@localhost dbhome_1]$ export PATH=$ORACLE_HOME/bin:$PATH
```

```
[oracle@localhost dbhome_1]$ export ORACLE_SID=orcl
```

```
[oracle@localhost dbhome_1]$ export ORACLE_BASE=/u01/app/oracle
```

```
[oracle@localhost dbhome_1]$ export ORACLE_HOME=/u01/app/oracle/product/19.0.0/dbhome_1
```

```
[oracle@localhost dbhome_1]$ whoami
```

```
oracle
```

```
[oracle@localhost dbhome_1]$ ./runInstaller
```

```
Launching Oracle Database Setup Wizard...
```

```
[oracle@localhost dbhome_1]$
```

Oracle Database 19c Installer - Step 3 of 8

19c ORACLE Database

Typical Install Configuration

Configuration Option

System Class

Typical Installation

Root script execution

Prerequisite Checks

Summary

Install Product

Finish

Perform full database installation with basic configuration.

Oracle base: /u01/app/oracle Browse...

Software location: /u01/app/oracle/product/19.0.0/dbhome_1

Database file location: /u01/app/oracle/oradata Browse...

Database edition: Enterprise Edition

Character set: Unicode (AL32UTF8)

OSDBA group: dba

Global database name: orcl

Password: Confirm password:

☒ Create as Container database

Pluggable database name: orclpdb

Help

< Back

Next >

Install

Cancel

```
oracle@localhost:/u01/app/oracle/product/19.0.0/dbhome_1
File Edit View Search Terminal Help

[root@localhost tmp]# free -h
[root@localhost tmp]# fallocation -l 6G /swapfile
[root@localhost tmp]# chmod 600 /swapfile
[root@localhost tmp]# mkswap /swapfile
Setting up swapspace version 1, size = 6 GiB
/u01/ no label, UUID=fb96c8b7-6696-41df-8990-721dfb
[root@localhost tmp]# swapon /swapfile
[root@localhost tmp]# swapon --show
NAME      TYPE      SIZE USED PRI0
/dev/dm-1 partition 5.6G 2.8M -2
/dev/swapfile file      6G   0B -3
[root@localhost tmp]# echo '/swapfile swap sw
[root@localhost tmp]# tail -5 /etc/fstab
/dev/mapper/ol-root      /
UUID=57b53a9c-581c-4786-97c0-d4d8db6695a8 /bo
ts      0 0
/dev/mapper/ol-home      /home
/dev/mapper/ol-swap      none
/swapfile swap swap defaults 0 0
[root@localhost tmp]# free -h
total      used      free
Mem:        10Gi      2.6Gi      465Mi
Swap:       11Gi      2.0Mi      11Gi
[root@localhost tmp]#
```

Oracle Database 19c Installer - Step 6 of 8

19^c ORACLE[®] Database

Summary

Configuration Option

System Class

Typical Installation

Root script execution

Prerequisite Checks

Summary

Install Product

Finish

Oracle Database 19c Installer

Global settings

Install method: Desktop installation [\[Edit\]](#)

Database edition: Enterprise Edition (Create and configure a database) [\[Edit\]](#)

Oracle base: /u01/app/oracle [\[Edit\]](#)

Software location: /u01/app/oracle/product/19.0.0/dbhome_1

Privileged Operating System groups: dba (OSDBA), dba (OSOPER), dba (OSBACKUPDBA),

Root script execution configuration: Manual configuration [\[Edit\]](#)

Database information

Configuration: General Purpose / Transaction Processing

Global database name: orcl [\[Edit\]](#)

Oracle system identifier (SID): orcl [\[Edit\]](#)

Pluggable database name: orclpdb [\[Edit\]](#)

Allocated memory: 4359 MB

Automatic memory management option: FALSE

Database character set : AL32UTF8 (Unicode UTF-8 Universal character set) [\[Edit\]](#)

Management method: Database express

Database storage mechanism: File system

Database file location: /u01/app/oracle/oradata [\[Edit\]](#)

Recovery: Disabled

Save Response File...

< Back

Next >

Install

Cancel

ORACLE

Oracle Database 19c Installer - Step 8 of 8



Finish

19^c ORACLE[®]
Database

- Configuration Option
- System Class
- Typical Installation
- Root script execution
- Prerequisite Checks
- Summary
- Install Product

 Finish

The configuration of Oracle Database was successful.

Note:

Oracle Enterprise Manager Database Express URL: <https://localhost:5500/em>

[Help](#)

< Back

Next >

Install

Close