

Package ‘ROOT’

December 4, 2025

Title Identifying Underrepresented Subpopulations With Interpretable Trees

Version 0.0.0.9000

Description ROOT (Rashomon set of Optimal Trees) is a general framework for globally optimizing user-specified functionals over interpretable binary weight functions represented as sparse decision trees. It searches over many candidate trees to construct a Rashomon set of near-optimal solutions and derives a characteristic summary tree that highlights stable patterns in the optimized weights. The current implementation focuses on generalizability and trans-
portability problems. Given trial and target data, ROOT learns weighting rules that optimize target treatment effect estimators and helps identify subpopulations that are underrepresented or contribute disproportionately to the variance of the target treatment effect estimate.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Suggests mlbench,
testthat (>= 3.0.0),
knitr,
rmarkdown,
ragg

Config/testthat/edition 3

Imports MASS,
rpart,
gbm,
stats,
withr,
rpart.plot

VignetteBuilder knitr

Depends R (>= 3.5)

LazyData true

Contents

characterize_tree	2
characterizing_underrep	3
choose_feature	5
diabetes_data	6

estimate	6
estimate_dml	7
estimate_dml_single	8
estimate_single	8
gen_S	9
gen_T	9
gen_XY	10
get_data	11
loss_from_objective	11
midpoint	12
objective_default	12
objective_if	13
plot.characterizing_underrep	13
plot.ROOT	14
print.characterizing_underrep	15
print.ROOT	16
reduce_weight	17
ROOT	18
split_node	20
stratified_kfold	21
summary.characterizing_underrep	22
summary.ROOT	23
train	24
train_single	25

Index	26
--------------	-----------

characterize_tree	<i>Fit a shallow decision tree to characterize learned weights w</i>
-------------------	--

Description

Trains a classification tree on the covariates X to predict the binary membership w . This provides an interpretable summary of how the weighted subgroup can be distinguished by X .

Usage

```
characterize_tree(X, w, max_depth = 3)
```

Arguments

X	A data.frame of covariates.
w	A vector of length $nrow(X)$ that is binary. Accepts 0 and 1 or a factor with two levels.
max_depth	An integer(1) giving the maximum tree depth. Default is 3.

Details

The tree uses the Gini index for classification and no pruning with complexity parameter $cp = 0$. Depth control is through `max_depth`. If w is not a factor it is converted internally. The resulting rules indicate which covariates and splits separate the two classes defined by w .

Value

An rpart object that represents the fitted classification tree.

```
characterizing_underrep
  Characterize under-represented subgroups (wraps ROOT)
```

Description

Combines an RCT ($S = 1$) and a target dataset ($S = 0$), then calls `ROOT()` to learn a weighted tree that identifies subgroups with different representation in the target population compared to the trial.

Usage

```
characterizing_underrep(
  DataRCT,
  covariateColName_RCT,
  trtColName_RCT,
  outcomeColName_RCT,
  DataTarget,
  covariateColName_TargetData,
  leaf_proba = 0.25,
  seed = 123,
  num_trees = 10,
  vote_threshold = 2/3,
  explore_proba = 0.05,
  feature_est = "Ridge",
  feature_est_args = list(),
  top_k_trees = FALSE,
  k = 10,
  cutoff = "baseline",
  verbose = FALSE,
  global_objective_fn = objective_default,
  keep_threshold = 0.5,
  lX_threshold = NULL
)
```

Arguments

<code>DataRCT</code>	A data.frame containing the randomized clinical trial data. Must include treatment, outcome, and covariate columns.
<code>covariateColName_RCT</code>	A character vector of covariate column names in <code>DataRCT</code> .
<code>trtColName_RCT</code>	A character(1) naming the treatment column in <code>DataRCT</code> with values 0 or 1.
<code>outcomeColName_RCT</code>	A character(1) naming the outcome column in <code>DataRCT</code> .
<code>DataTarget</code>	A data.frame containing the target population covariates only.
<code>covariateColName_TargetData</code>	A character vector of covariate column names in <code>DataTarget</code> .

leaf_proba	A numeric(1) giving the probability for the "leaf" option in ROOT tree growth. Default 0.25.
seed	An integer(1) seed for reproducibility. Default 123.
num_trees	An integer(1) number of trees to grow. Default 10.
vote_threshold	A numeric(1) in (0.5, 1] for the majority vote threshold. Default 2/3.
explore_proba	A numeric(1) exploration probability. Default 0.05.
feature_est	Either a character(1) in c("Ridge", "GBM") or a function(X, y, ...) that returns a named nonnegative numeric vector of importances.
feature_est_args	A named list of extra arguments passed to the user supplied feature_est function.
top_k_trees	A logical(1). If TRUE, selects top k trees by objective; otherwise uses cutoff. Default FALSE.
k	An integer(1) number of trees used when top_k_trees = TRUE. Default 10.
cutoff	A numeric(1) or the value "baseline" used as the Rashomon set cutoff when top_k_trees = FALSE.
verbose	A logical(1). If TRUE, prints progress and estimand summaries. Default FALSE.
global_objective_fn	A function with signature function(D) -> numeric to minimize. Default objective_default.
keep_threshold	Unused; kept for backward compatibility. A numeric(1) if provided.
lx_threshold	Unused; kept for backward compatibility. A numeric(1) if provided.

Value

A characterizing_underrep S3 object (a list) with components:

root	The resulting ROOT object returned by ROOT().
combined	A data.frame with the stacked RCT and target data used for analysis.
leaf_summary	A data.frame of terminal node summaries with rules, counts, percentages, and labels when a summary tree exists; otherwise NULL.

Abbreviations

RCT means randomized clinical trial. ATE means Average Treatment Effect. WTATE means Weighted Transported ATE. SE means Standard Error.

References

Parikh, H., Ross, R. K., Stuart, E., and Rudolph, K. E. (2025). Who Are We Missing?: A Principled Approach to Characterizing the Underrepresented Population. *Journal of the American Statistical Association*, 1–32.

Examples

```
## Not run:
# Load example data
data(diabetes_data)

# Split into Trial (S=1) and Target (S=0)
trial <- subset(diabetes_data, S == 1)
target <- subset(diabetes_data, S == 0)

# Run characterization
res <- characterizing_underrep(
  DataRCT = trial,
  covariateColName_RCT = c("Race_Black", "Sex_Male", "DietYes", "Age45"),
  trtColName_RCT = "Tr",
  outcomeColName_RCT = "Y",
  DataTarget = target,
  covariateColName_TargetData = c("Race_Black", "Sex_Male", "DietYes", "Age45"),
  seed = 123
)

## End(Not run)
```

choose_feature

*Randomly choose a split feature based on provided probabilities***Description**

Selects one feature name at random according to a probability vector that may include a special "leaf" entry.

Usage

```
choose_feature(split_feature, depth)
```

Arguments

split_feature	A named numeric vector of feature selection probabilities. Names correspond to feature identifiers and may include "leaf".
depth	An integer(1) giving the current tree depth. Present for parity with the Python version and does not change probabilities here.

Value

A character(1) which is the chosen feature name or "leaf".

Note

The factor $2^{(0-\text{depth}/4)}$ present in the code equals 1 and does not change the first element weight. All probabilities are normalized to sum to 1 before sampling.

diabetes_data	<i>Simulated Diabetes Dataset for Examples</i>
---------------	--

Description

A toy dataset for illustrating ROOT examples and tests.

Usage

```
data(diabetes_data)
```

Format

A `data.frame` with one row per individual and the columns:

Age45 Indicator in 0/1: age \geq 45.

DietYes Indicator in 0/1: on a diet program.

Race_Black Indicator in 0/1: race is Black.

S Sample indicator in 0/1: 1 means RCT or source, 0 means target.

Sex_Male Indicator in 0/1: male.

Tr Treatment assignment in 0/1.

Y Observed outcome (numeric or 0/1).

Abbreviations

RCT means randomized clinical trial. ATE means Average Treatment Effect.

estimate	<i>Compute pseudo outcome components a and b and their product v</i>
----------	--

Description

Uses nuisance model outputs to compute inverse probability weighted quantities for ATE in the trial sample.

Usage

```
estimate(testing_data, outcome, treatment, sample, pi, pi_m, e_m)
```

Arguments

testing_data	A <code>data.frame</code> that contains at least outcome, treatment, and sample indicator columns.
outcome	A <code>character(1)</code> name of the outcome column in <code>testing_data</code> .
treatment	A <code>character(1)</code> name of the treatment column in <code>testing_data</code> with values 0 or 1.
sample	A <code>character(1)</code> name of the sample indicator column in <code>testing_data</code> with values 0 or 1.

pi	A numeric(1) giving the estimated prevalence $P(S = 1)$ from the training data.
pi_m	A fitted glm model for $P(S = 1 X)$.
e_m	A fitted glm model for $P(Tr = 1 X, S = 1)$.

Details

Predictions from pi_m and e_m are clamped to $[1e-8, 1 - 1e-8]$ for stability.

Value

A list with numeric vectors of length `nrow(testing_data)`:

v	Pseudo outcome values.
a	IPW adjusted outcome contrast.
b	Overlap weight factors.

estimate_dml	<i>Cross fitted estimation of pseudo outcomes for two sample Double ML</i>
--------------	--

Description

Trains nuisance models on each training fold and computes pseudo outcomes on the corresponding test fold, then aggregates results. Returns the pseudo outcome table and aligned evaluation data.

Usage

```
estimate_dml(data, outcome, treatment, sample, crossfit = 5)
```

Arguments

data	A data.frame containing at least the outcome, treatment, and sample indicator columns.
outcome	A character(1) name of the outcome column.
treatment	A character(1) name of the treatment column with values 0 or 1.
sample	A character(1) name of the sample indicator column with values 0 or 1.
crossfit	An integer(1) number of folds for cross fitting where the value is at least 2. Default 5.

Value

A list with:

df_v	data.frame with one row per kept observation indexed by primary_index. Contains te, a, b, te_sq, a_sq. Only $S == 1$ rows with finite values are kept.
data2	data.frame subset of the original data corresponding to <code>df_v\$primary_index</code> .

Note

Rows with infinite or undefined weights are removed. Squared deviation columns are centered in the $S == 1$ group.

estimate_dml_single	<i>Cross fitted Double ML for single sample mode</i>
---------------------	--

Description

Runs K fold cross fitting to produce pseudo outcomes for ATE estimation when no sample membership indicator is available or has no variation.

Usage

```
estimate_dml_single(data, outcome, treatment, crossfit = 5)
```

Arguments

data	A data.frame containing outcome, treatment, and covariates.
outcome	A character(1) name of the outcome column.
treatment	A character(1) name of the binary treatment indicator column with values 0 or 1.
crossfit	An integer(1) number of folds for cross fitting where the value is at least 2. Default 5.

Value

A list with:

df_v	data.frame with one row per kept observation that contains te, a, b, te_sq, a_sq, and primary_index.
data2	data.frame subset of data that corresponds to df_v\$primary_index.

estimate_single	<i>Compute single sample pseudo outcomes</i>
-----------------	--

Description

Computes single sample pseudo outcome components for ATE style estimation: $a_i = T_i Y_i / e_i - (1 - T_i) Y_i / (1 - e_i)$ with $v_i = a_i$ and $b_i \equiv 1$.

Usage

```
estimate_single(testing_data, outcome, treatment, e_m)
```

Arguments

testing_data	A data.frame containing at least outcome, treatment, and covariates.
outcome	A character(1) name of the outcome column.
treatment	A character(1) name of the binary treatment indicator column with values 0 or 1.
e_m	A fitted glm model for $P(T = 1 X)$ such as the result of train_single .

Value

A list with numeric vectors of length `nrow(testing_data)`:

<code>v</code>	Pseudo outcome values which equal <code>a</code> in single sample mode.
<code>a</code>	IPW adjusted outcome contrast.
<code>b</code>	Vector of ones because there is no sample overlap weighting in single sample mode.

<code>gen_S</code>	<i>Generate sample indicator S drawn from a Bernoulli distribution</i>
--------------------	---

Description

Generates a binary sample inclusion indicator S for each observation using a logistic model influenced by a rectangular region in X_0 and X_1 .

Usage

```
gen_S(X, seed = NULL)
```

Arguments

<code>X</code>	A <code>data.frame</code> of covariates that contains at least X_0 and X_1 .
<code>seed</code>	Optional <code>numeric(1)</code> seed. If <code>NULL</code> no seed is set.

Details

The inclusion probability is $p = \text{plogis}(a)$ where $a = 0.25 - 2 \cdot I\{X_0 \in (0.5, 1) \wedge X_1 \in (0.5, 1)\}$.

Value

A `data.frame` with one column S of values in $\{0, 1\}$.

<code>gen_T</code>	<i>Generate treatment indicator T_r drawn from a Bernoulli distribution</i>
--------------------	--

Description

Assigns treatment indicators combining a randomized design for $S == 1$ and an observational assignment driven by X_0 for $S == 0$.

Usage

```
gen_T(X, S, seed = NULL)
```

Arguments

<code>X</code>	A <code>data.frame</code> of covariates.
<code>S</code>	A <code>data.frame</code> with column S in $\{0, 1\}$.
<code>seed</code>	Optional <code>numeric(1)</code> seed. If <code>NULL</code> no seed is set.

Details

For $S == 1$ the treatment probability is 0.5. For $S == 0$ the treatment probability is $\text{plogis}(X_0)$. The combined probability is $\pi_i = S_i \cdot 0.5 + (1 - S_i) \cdot \text{plogis}(X_{0_i})$.

Value

A list with:

Tr	data.frame with one column Tr in 0 or 1.
pi	numeric vector of assignment probabilities per observation.

gen_XY	<i>Generate covariates X and potential outcomes (Y0, Y1)</i>
--------	--

Description

Simulates a regression problem based on Friedman number one and defines a treatment effect. Uses `mlbench.friedman1` to generate feature matrix X and a baseline outcome Y0. The treatment potential outcome Y1 is defined as $Y1 = Y0 + \log(Y0 + 1)$ which introduces heterogeneous treatment effect.

Usage

```
gen_XY(n = 1000, seed = NULL)
```

Arguments

n	A numeric(1) or integer(1) giving the number of observations to simulate. Must be positive.
seed	Optional numeric(1) for the random number generator seed. If NULL no seed is set.

Details

The `mlbench.friedman1` generator creates ten continuous features and a baseline outcome Y0 with additive noise. The potential outcome Y1 adds a nonlinear term $\log(Y0 + 1)$ to Y0.

Value

A list with two components:

X	data.frame of simulated covariates with columns X0, X1, ... up to X(p-1).
Y	data.frame with columns Y0 and Y1.

get_data	<i>Convenience wrapper to generate a full simulated dataset</i>
----------	---

Description

Generates covariates, sample inclusion, treatment assignments, and observed outcomes for a given sample size by calling `gen_XY()`, `gen_S()`, and `gen_T()`.

Usage

```
get_data(n = 1000, seed = NULL)
```

Arguments

<code>n</code>	A <code>numeric(1)</code> or <code>integer(1)</code> sample size.
<code>seed</code>	Optional <code>numeric(1)</code> base seed. If provided, internal generators use simple offsets.

Value

A list with:

<code>data</code>	<code>data.frame</code> of length <code>n</code> with covariates X_0, \dots , sample indicator S , treatment indicator Tr , and observed outcome Y_{obs} .
<code>Y</code>	<code>data.frame</code> of length <code>n</code> with potential outcomes Y_0 and Y_1 .

Examples

```
sim <- get_data(n = 100, seed = 599)
dim(sim$data)
head(sim$data$Yobs)
head(sim$Y)
```

loss_from_objective	<i>Backward and fast path micro evaluator adaptor</i>
---------------------	---

Description

Wraps a global objective `global_objective_fn(D)` into a splitter compatible loss function `loss_fn(val, indices, D)` by calling `objective_if` on a temporary copy of `D`.

Usage

```
loss_from_objective(global_objective_fn)
```

Arguments

<code>global_objective_fn</code>	A function with signature <code>function(D) -> numeric</code> that returns a scalar to be minimized. For example <code>objective_default</code> .
----------------------------------	--

Value

A function `loss_fn(val, indices, D)` suitable for use in `ROOT` and `split_node`. It sets `w = val` on indices without mutation of the original `D` and then returns `global_objective_fn(D)`.

midpoint

Compute the midpoint of a numeric vector

Description

Calculates the midpoint defined as $(\max(X) + \min(X))/2$ while ignoring any NA values in `X`.

Usage

`midpoint(X)`

Arguments

`X` A numeric vector.

Value

A `numeric(1)` giving the midpoint of the finite values in `X`. Returns `NA_real_` when `X` is empty or has no finite values.

objective_default

Generic objective interface

Description

Default objective that serves as a proxy for Standard Error in Weighted Transported Average Treatment Effect and Population Average Treatment Effect.

Usage

`objective_default(D)`

Arguments

`D` A `data.frame` with at least numeric columns `vsq` and `w`.

Details

Computes $\sqrt{\sum_i \text{vsq}_i \cdot w_i} / (\sum_i w_i)^2$. Requires columns `vsq` and `w` in `D`. The goal is to minimize the value. Supply your own `function(D) -> numeric` to use a different objective.

Value

A `numeric(1)` objective value. Returns `Inf` when undefined.

Abbreviations

ATE means Average Treatment Effect. SE means Standard Error. TATE means Transported ATE. WTATE means Weighted TATE. WATE means Weighted ATE. PATE means Population ATE.

objective_if	<i>Helper to evaluate the objective after a hypothetical local change</i>
--------------	---

Description

Evaluates `global_objective_fn` on a temporary copy of `D` after setting `w = val` for the rows selected by `indices`.

Usage

```
objective_if(val, indices, D, global_objective_fn)
```

Arguments

<code>val</code>	A <code>numeric(1)</code> that must be either 0 or 1.
<code>indices</code>	An integer vector of row indices or a character vector of row names that receive <code>val</code> .
<code>D</code>	A <code>data.frame</code> used by <code>global_objective_fn</code> . Must contain columns <code>w</code> and <code>vsq</code> .
<code>global_objective_fn</code>	A function with signature <code>function(D) -> numeric</code> .

Value

A `numeric(1)` objective value after the hypothetical change.

<code>plot.characterizing_underrep</code>	<i>Plot Under represented Population Characterization</i>
---	---

Description

Visualizes the decision tree derived from the R00T analysis. Highlights which subgroups are represented where `w = 1` versus underrepresented where `w = 0`.

Usage

```
## S3 method for class 'characterizing_underrep'
plot(x, ...)
```

Arguments

<code>x</code>	A <code>characterizing_underrep</code> S3 object with <code>x\$root\$f</code> present as an <code>rpart</code> object for the summary or characterization tree. The <code>rpart</code> model should have classification levels that allow identification of the represented class.
<code>...</code>	Additional arguments passed to <code>rpart.plot::prp()</code> .

Value

NULL. The plot is drawn to the active graphics device.

Abbreviations

ATE means Average Treatment Effect. RCT means Randomized Controlled Trial. SE means Standard Error. TATE means Transported ATE. WTATE means Weighted TATE. WATE means Weighted ATE. PATE means Population ATE.

Examples

```
## Not run:
# Load example data
data(diabetes_data)

# Split into Trial (S=1) and Target (S=0)
trial <- subset(diabetes_data, S == 1)
target <- subset(diabetes_data, S == 0)

# Run characterization
res <- characterizing_underrep(
  DataRCT = trial,
  covariateColName_RCT = c("Race_Black", "Sex_Male", "DietYes", "Age45"),
  trtColName_RCT = "Tr",
  outcomeColName_RCT = "Y",
  DataTarget = target,
  covariateColName_TargetData = c("Race_Black", "Sex_Male", "DietYes", "Age45"),
  seed = 123
)

# Plot the annotated tree
plot(res)

## End(Not run)
```

plot.ROOT

Plot the ROOT summary tree

Description

Visualizes the decision tree that characterizes the weighted subgroup identified by ROOT using `rpart.plot::prp()`.

Usage

```
## S3 method for class 'ROOT'
plot(x, ...)
```

Arguments

x	A ROOT S3 object returned by <code>ROOT()</code> with <code>x\$f</code> an <code>rpart</code> object which is the summary or characterization tree.
...	Additional arguments passed to <code>rpart.plot::prp()</code> .

Value

No return value; the plot is drawn to the active graphics device.

Examples

```
## Not run:
# Load example data
data(diabetes_data)

# Run ROOT
res <- ROOT(data = diabetes_data, outcome = "Y", treatment = "Tr", sample = "S")

# Plot characterization tree
plot(res)

## End(Not run)
```

```
print.characterizing_underrep
      Print a characterizing_underrep fit
```

Description

Prints the ROOT summary which includes unweighted and weighted estimates with standard errors. The weighted SE is omitted when a custom `global_objective_fn` was used in `ROOT()`. Provides a shorter overview of results.

Usage

```
## S3 method for class 'characterizing_underrep'
print(x, ...)
```

Arguments

<code>x</code>	A <code>characterizing_underrep</code> S3 object. Expected components include <code>root</code> which is a ROOT object. The ROOT object may contain <code>D_forest</code> which is data frame like, <code>D_rash</code> which may include <code>w_opt</code> , and <code>rashomon_set</code> which is an integer vector of selected tree indices.
<code>...</code>	Currently unused. Included for S3 compatibility.

Details

Delegates core statistics, number of trees grown and Rashomon size, and the percentage of observations with ensemble vote `w_opt == 1` to `print(x$root)`.

Value

`x` returned invisibly. Printed output is a human readable summary.

Abbreviations

ATE means Average Treatment Effect. RCT means Randomized Controlled Trial. SE means Standard Error. TATE means Transported ATE. WTATE means Weighted TATE. WATE means Weighted ATE. PATE means Population ATE.

Examples

```
## Not run:
# Load example data
data(diabetes_data)

# Split into Trial (S=1) and Target (S=0)
trial <- subset(diabetes_data, S == 1)
target <- subset(diabetes_data, S == 0)

# Run characterization
res <- characterizing_underrep(
  DataRCT = trial,
  covariateColName_RCT = c("Race_Black", "Sex_Male", "DietYes", "Age45"),
  trtColName_RCT = "Tr",
  outcomeColName_RCT = "Y",
  DataTarget = target,
  covariateColName_TargetData = c("Race_Black", "Sex_Male", "DietYes", "Age45"),
  seed = 123
)

# Print core results
print(res)

## End(Not run)
```

print.ROOT

Print a ROOT fit

Description

Prints a ROOT object by reporting the primary estimands and core diagnostics. The first lines report:

1. the unweighted estimate which is ATE in an RCT for single sample or TATE for two sample and its SE
2. the weighted estimate which is WATE in RCT or WTATE using w_{opt} and its SE whenever w_{opt} is effectively binary which means subset mean SE. If w_{opt} is nonbinary, the SE is omitted with a note.

Subsequent lines include number of trees grown, Rashomon size, and the percentage of observations with ensemble vote $w_{\text{opt}} == 1$.

Usage

```
## S3 method for class 'ROOT'
print(x, ...)
```


Arguments

`x` A ROOT S3 object returned by `ROOT()`.
`...` Currently unused and included for S3 compatibility.

Details

When `x$estimate` is absent, calculations mirror those described in [summary.ROOT](#).

Value

`x` returned invisibly. Printed output is a human readable summary.

Abbreviations

ATE means Average Treatment Effect. RCT means Randomized Controlled Trial. SE means Standard Error. TATE means Transported ATE. WTATE means Weighted TATE. WATE means Weighted ATE. PATE means Population ATE.

Examples

```
## Not run:
# Load example data
data(diabetes_data)

# Run ROOT
res <- ROOT(data = diabetes_data, outcome = "Y", treatment = "Tr", sample = "S")

# Print core results
print(res)

## End(Not run)
```

reduce_weight

Reduce a feature selection weight by one half and renormalize

Description

Lowers the probability weight of a given feature by one half and then renormalizes the full vector to sum to one.

Usage

```
reduce_weight(fj, split_feature)
```

Arguments

`fj` A character(1) feature name that must be present in `names(split_feature)`.
`split_feature` A named numeric vector of probabilities for features as used in splitting.

Details

This is used when a feature split was rejected. The feature probability is halved to reduce the chance of immediate reselection which encourages exploration of other features. If `fj` equals "leaf" its weight is also halved.

Value

A numeric vector of the same length as `split_feature` that sums to 1.

ROOT	<i>Ensemble of weighted trees (loss/objective agnostic) and Rashomon selection</i>
------	--

Description

Builds multiple weighted trees, then identifies a "Rashomon set" of top performing trees and aggregates their weight assignments by majority vote.

Usage

```
ROOT(
  data,
  outcome,
  treatment,
  sample,
  leaf_proba = 0.25,
  seed = NULL,
  num_trees = 10,
  vote_threshold = 2/3,
  explore_proba = 0.05,
  feature_est = "Ridge",
  feature_est_args = list(),
  top_k_trees = FALSE,
  k = 10,
  cutoff = "baseline",
  verbose = FALSE,
  global_objective_fn = objective_default
)
```

Arguments

<code>data</code>	A <code>data.frame</code> containing the dataset. Must include outcome, treatment, and sample indicator columns.
<code>outcome</code>	A <code>character(1)</code> specifying the name of the outcome column in data.
<code>treatment</code>	A <code>character(1)</code> specifying the name of the treatment indicator column in data. Values should be 0 or 1.
<code>sample</code>	A <code>character(1)</code> specifying the name of the sample indicator column in data with values 0 or 1. Use <code>NULL</code> for single sample SATE mode.
<code>leaf_proba</code>	A <code>numeric(1)</code> giving the probability mass for the "leaf" option in each tree. Default 0.25.

seed	An optional numeric(1) seed for reproducibility. Default NULL.
num_trees	An integer(1) giving the number of trees to grow in the forest. Default 10.
vote_threshold	A numeric(1) in (0.5, 1] giving the majority vote threshold for final weight = 1. Default 2/3.
explore_proba	A numeric(1) giving the probability of exploration at leaves in each tree. Default 0.05.
feature_est	Either a character(1) in c("Ridge", "GBM") or a function(X, y, ...) returning a named nonnegative numeric vector of importances where names match columns of X.
feature_est_args	A list of extra arguments passed to a user supplied feature_est function.
top_k_trees	A logical(1). If TRUE, select top k trees by objective; otherwise use cutoff. Default FALSE.
k	An integer(1) giving the number of top trees used when top_k_trees = TRUE. Default 10.
cutoff	A numeric(1) or the character(1) value "baseline". Used as the Rashomon set cutoff when top_k_trees = FALSE.
verbose	A logical(1). If TRUE, prints two lines with unweighted and weighted estimates and their SE. Default FALSE.
global_objective_fn	A function with signature function(D) -> numeric that scores the entire state and is minimized. Default objective_default.

Value

An S3 object of class "ROOT" which is a list with elements including:

D_rash	data.frame that contains the Rashomon set votes and w_opt.
D_forest	data.frame with forest level working columns including v, vsq, S, and the w_tree_* columns.
w_forest	list of per tree results returned by split_node().
rashomon_set	integer vector of selected tree indices.
global_objective_fn	The function used for the global objective.
f	An rpart object for the summary tree or NULL when no covariates exist.
testing_data	data.frame aligned to the rows used to compute scores.
estimate	list with elements estimand_unweighted, value_unweighted, se_unweighted, estimand_weighted, value_weighted, se_weighted, se_weighted_note, n_analysis, sum_w, n_A.

Abbreviations

ATE means Average Treatment Effect. SATE means Sample Average Treatment Effect. WTATE means Weighted Transported ATE. WATE means Weighted ATE. PATE means Population ATE. SE means Standard Error.

References

Parikh, H., Ross, R. K., Stuart, E., and Rudolph, K. E. (2025). Who Are We Missing?: A Principled Approach to Characterizing the Underrepresented Population. *Journal of the American Statistical Association*, 1–32.

Examples

```
## Not run:
# Load example data
data(diabetes_data)

# Run ROOT
res <- ROOT(data = diabetes_data, outcome = "Y", treatment = "Tr", sample = "S")

## End(Not run)
```

split_node

Recursive split builder for weighted tree

Description

Recursively builds a weighted decision tree to optimize a global objective, using an exploration versus exploitation choice at leaves. Internal and used by `ROOT()`.

Usage

```
split_node(
  split_feature,
  X,
  D,
  parent_loss,
  depth,
  explore_proba = 0.05,
  choose_feature_fn = choose_feature,
  reduce_weight_fn = reduce_weight,
  global_objective_fn = objective_default,
  max_depth = 8,
  min_leaf_n = 5,
  log_fn = function(...) {
  },
  max_rejects_per_node = 1000
)
```

Arguments

split_feature	A named numeric vector of feature selection probabilities. Must include the name "leaf".
X	A <code>data.frame</code> of current observations. Includes candidate split feature columns and may include a working copy of weights <code>w</code> .
D	A <code>data.frame</code> representing the global state. Must include columns <code>w</code> and <code>vsq</code> . Row names must align to <code>X</code> .
parent_loss	A <code>numeric(1)</code> giving the loss of the parent node. Used to decide if a split improves the objective.
depth	An <code>integer(1)</code> giving the current tree depth.
explore_proba	A <code>numeric(1)</code> between 0 and 1 for the probability of flipping the exploit choice at a leaf.

choose_feature_fn	A function to choose the next feature. Default is choose_feature.
reduce_weight_fn	A function to penalize the last tried feature on a rejected split. Default is reduce_weight.
global_objective_fn	A function with signature function(D) -> numeric that scores the entire state.
max_depth	An integer(1) giving the maximum depth. A node becomes a leaf at this depth.
min_leaf_n	An integer(1) giving the minimum number of rows to attempt a split. Otherwise make a leaf.
log_fn	A function for logging. Default is a function that performs no operation.
max_rejects_per_node	An integer(1) giving the safety budget of rejected splits before forcing a leaf.

Value

A list representing the subtree. Includes updated D and a field named "local objective".

stratified_kfold	<i>Stratified K fold index generator</i>
------------------	--

Description

Splits indices into K folds while preserving the class distribution of a binary factor. This mimics the behavior of stratified K fold allocation to keep the ratio of classes in each fold.

Usage

```
stratified_kfold(S, K = 5)
```

Arguments

S	A vector or factor indicating class membership for stratification. Typical values are 0 or 1.
K	An integer(1) number of folds. If K exceeds the number of observations it is reduced to that number.

Value

A list of length K where each element is an integer vector of row indices assigned to that fold. The union of all folds equals seq_along(S) and folds are close in size.

summary.characterizing_underrep

Summarize a characterizing_underrep fit

Description

Summarizes the ROOT summary which includes unweighted and weighted estimates with standard errors. The weighted SE is omitted when a custom `global_objective_fn` was used in `ROOT()`. Provides a brief overview of terminal rules from the annotated summary tree when available.

Usage

```
## S3 method for class 'characterizing_underrep'
summary(object, ...)
```

Arguments

<code>object</code>	A <code>characterizing_underrep</code> S3 object. Expected components include <code>root</code> which is a ROOT object and may contain <code>f</code> which is an <code>rpart</code> object for the summary tree, and <code>leaf_summary</code> which is a <code>data.frame</code> with one row per terminal node and may include a <code>rule</code> column of type <code>character</code> .
<code>...</code>	Currently unused. Included for S3 compatibility.

Details

Delegates core statistics to `summary(object$root)`. Previews up to ten terminal rules when a summary tree exists and reports plot availability.

Value

`object` returned invisibly. Printed output is a human readable summary.

Abbreviations

ATE means Average Treatment Effect. RCT means Randomized Controlled Trial. SE means Standard Error. TATE means Transported ATE. WTATE means Weighted TATE. WATE means Weighted ATE. PATE means Population ATE.

Examples

```
## Not run:
# Load example data
data(diabetes_data)

# Split into Trial (S=1) and Target (S=0)
trial <- subset(diabetes_data, S == 1)
target <- subset(diabetes_data, S == 0)

# Run characterization
res <- characterizing_underrep(
  DataRCT = trial,
  covariateColName_RCT = c("Race_Black", "Sex_Male", "DietYes", "Age45"),
```

```

    trtColName_RCT = "Tr",
    outcomeColName_RCT = "Y",
    DataTarget = target,
    covariateColName_TargetData = c("Race_Black", "Sex_Male", "DietYes", "Age45"),
    seed = 123
  )

# View Summary
summary(res)

## End(Not run)

```

summary.ROOT

Summarize a ROOT fit

Description

Summarizes a ROOT object by reporting the primary estimands and key model diagnostics. The first lines report:

1. the unweighted estimate which is ATE in an RCT for single sample or TATE for two sample and its standard error *SE*
2. the weighted estimate which is WATE in RCT or WTATE using *w_opt* and its SE whenever *w_opt* is effectively binary which means subset mean SE. If *w_opt* is nonbinary, the SE is omitted with a note.

Subsequent lines describe the estimand type, number of trees, size of the Rashomon set, presence of a summary tree, covariate count, observation count, baseline loss, selected tree losses, and the proportion kept by *w_opt*.

Usage

```

## S3 method for class 'ROOT'
summary(object, ...)

```

Arguments

object	A ROOT S3 object returned by <code>ROOT()</code> . Expected components include <code>D_forest</code> which is data frame like with columns <code>v</code> , <code>vsq</code> , <code>S</code> , <code>lX</code> , and <code>w_tree*</code> , <code>D_rash</code> which may contain <code>w_opt</code> , <code>rashomon_set</code> which is <code>integer()</code> , optional <code>estimate</code> which is a list with fields <code>estimand_unweighted</code> , <code>value_unweighted</code> , <code>se_unweighted</code> , <code>estimand_weighted</code> , <code>value_weighted</code> , <code>se_weighted</code> , <code>se_weighted_note</code> , and optional <code>f</code> which is an <code>rpart</code> object.
...	Currently unused and included for S3 compatibility.

Details

This method prefers precomputed estimates in `object$estimate`. If unavailable, it recomputes:

- Unweighted effect as \bar{v} over the analysis set where the analysis set is all rows in single sample and `S == 1` in two sample

- Unweighted SE as $\sqrt{\frac{1}{n(n-1)} \sum (v_i - \bar{v})^2}$ which is `sqrt(sum((v - vbar)^2) / (n * (n - 1)))`
- Weighted effect when `w_opt` is binary with $A = \{i : w_i = 1\}$ which is `A <- which(w == 1)`, that is $\bar{v}_A = \frac{1}{n_A} \sum_{i \in A} v_i$ which is `mean(v[w == 1])`
- Weighted SE which is WTATE or WATE for binary `w_opt` as $\sqrt{\frac{1}{n_A(n_A-1)} \sum_{i \in A} (v_i - \bar{v}_A)^2}$ which is `sqrt(sum((v[w == 1] - vbarA)^2) / (nA * (nA - 1)))`

Value

object returned invisibly. Printed output is a human readable summary.

Abbreviations

ATE means Average Treatment Effect. RCT means Randomized Controlled Trial. SE means Standard Error. TATE means Transported ATE. WTATE means Weighted TATE. WATE means Weighted ATE. PATE means Population ATE.

Examples

```
## Not run:
# Load example data
data(diabetes_data)

# Run ROOT
res <- ROOT(data = diabetes_data, outcome = "Y", treatment = "Tr", sample = "S")

# Summary of results
summary(res)

## End(Not run)
```

train	<i>Train nuisance models for weighting</i>
-------	--

Description

Fits models to estimate sampling and treatment propensities on training data by logistic regression.

Usage

```
train(training_data, outcome, treatment, sample)
```

Arguments

training_data	A <code>data.frame</code> that contains the training dataset.
outcome	A <code>character(1)</code> name of the outcome column. Typically this is the observed outcome such as "Yobs".
treatment	A <code>character(1)</code> name of the treatment indicator column such as "Tr".
sample	A <code>character(1)</code> name of the sample inclusion indicator column such as "S".

Value

A list with:

pi	numeric(1) prevalence of $S = 1$ in the training data.
pi_m	glm model with binomial family for $P(S = 1 X)$.
e_m	glm model with binomial family for $P(Tr = 1 X, S = 1)$.

train_single	<i>Train treatment propensity model for single sample mode</i>
--------------	--

Description

Fits a logistic regression model for $P(T = 1 | X)$ on the provided training data. Used by the single sample Double ML path where no sample selection model is required.

Usage

```
train_single(training_data, outcome, treatment)
```

Arguments

training_data	A data.frame containing the outcome, treatment, and covariates. Only treatment and covariates are used for fitting.
outcome	A character(1) name of the outcome column. Present for a consistent signature and not used here.
treatment	A character(1) name of the binary treatment indicator column with values 0 or 1.

Value

A list with:

e_m	A glm model with binomial family for the treatment propensity.
-----	--

Index

* datasets

diabetes_data, [6](#)

characterize_tree, [2](#)

characterizing_underrep, [3](#)

choose_feature, [5](#)

diabetes_data, [6](#)

estimate, [6](#)

estimate_dml, [7](#)

estimate_dml_single, [8](#)

estimate_single, [8](#)

gen_S, [9](#)

gen_T, [9](#)

gen_XY, [10](#)

get_data, [11](#)

loss_from_objective, [11](#)

midpoint, [12](#)

objective_default, [11](#), [12](#)

objective_if, [11](#), [13](#)

plot.characterizing_underrep, [13](#)

plot.ROOT, [14](#)

print.characterizing_underrep, [15](#)

print.ROOT, [16](#)

reduce_weight, [17](#)

ROOT, [12](#), [18](#)

split_node, [12](#), [20](#)

stratified_kfold, [21](#)

summary.characterizing_underrep, [22](#)

summary.ROOT, [17](#), [23](#)

train, [24](#)

train_single, [8](#), [25](#)