

# ΔFIX Preprocessor Cheat Sheet

[ΔFIX Cheat Sheet.md]

Cat.	Item	Example
Cont.	Continuation line symbol... or .. (dots / diaereses are ignored)	<pre>a←1 + 2 + ...   3 4 5 s←'one two three ..   four five' [See also Continuing DQ Strings]</pre>
Cont.	Continuing Parenthetical Expressions Across lines	<pre>a←~1+(2*   31 32 33)÷(   1+~3)</pre>
Cont.	Continuing SQ Strings Across Lines	<pre>'This is line 1 and line 2.' 'This is line 1 and line 2.'</pre>
Cont.	Continuing DQ Strings Across Lines	<pre>"This is line1 and line 2." ('This is line1',(⊞UCS 10),'and line 2.')</pre>
Cont.	Quotes with continuation line symbol ... or ..	<pre>This is a cat.. alog. This is a cat ..alog.' 'This is a catalog. This is a cat alog.'</pre>
Where	Semicolon at end or beginning of line (outside parens, brackets, braces) represents → "where".  For semicolons within parens, see Lists. Parens inside brackets follow APL standards.)	<pre>S← (A×x*2)+(B×x)+C     ; A←10     ; B←~5     ; C←o1     ; x←~100  S←(A×x*2)+(B×x)+C→A←10→B←~5→C←o1→x←~10 S 3.141592654 8.141592654 33.14159265 78.14159265 143.1415927 228.1415927 333.1415927 458.1415927 603.1415927 768.1415927</pre>
Unicode	Decimal ⊞Unnn	⊞U123≡⊞UCS 123 ♦ ⊞U123≡{'
Unicode	Hexadecimal ⊞Unhhx	⊞U7BX≡⊞U123
Nums	Hexadecimal Integers dhhhx	1122X≡123X+0FFFX
Nums	Long number separator _	<pre>123_245_343_122.35 3.14159_26534</pre>
Atoms	Atoms consist of APL names, numbers, and APL strings.	<pre>:FOR a :IN `fred 'jack 123'...           3.14159 55</pre>
Atoms	Atoms as names `atom1 atom2	<pre>colors←`red orange yellow reds← `red orange 1≡^/redsecolors</pre>
Atoms	Atoms as numbers	local←`CA 14850
Atoms	Atoms as strings `name1 'string2'	Last←`Smith 'Van Buren' Jones

# ΔFIX Preprocessor Cheat Sheet

[ΔFIX Cheat Sheet.md]

Cat.	Item	Example
Parms (Parameters)	Parameters	atom1 atom2→ arbitrary code [See Lists for examples]
Lists	Lists (code1 ; code2;)	Create mappings from names/numbers/ strings to arbitrary code expressions
Lists	Ordinary code (code1; code2; )	test←(i3 ; i4)
Lists	Function parameters	graph←(XY type 3→(i20)(10i20); legend x→'Voltage'; legend y→'Amplitude' )
Lists	With atoms	graph(type→`XY 3; smooth → `true; line color→`green; line height→`2.5 in)
Lists	Omitted parameters (code1;;code3)	address(2525; 'Cozy'; 'Lane'; ; ; 90212; USA) A city/state opal with zip
Lists	Null list ()	Always true: () ≡ 0
Name Suffixes	Is name defined? name..DEF	:IF print..DEF
Name Suffixes	Is name undefined? name..UNDEF	:IF print..UNDEF
Name Suffixes	Put name in quotes: name..Q (possibly after macro or other processing)	□NPARTS fileName..Q
Name Suffixes	Get value of environment variable 'name'	PATH←PATH..ENV{×≠α: ω <> α}'...'
Direc- tive	If clause ::IF code	::IF 0≠DEBUG..ENV
Direc- tive	Test that name is defined	::IFDEF DEBUG_FLAG
Direc- tive	Test that name is not defined	::IFNDEF DEBUG_FLAG
Direc- tive	Undefine name	::UNDEF DEBUG_FLAG
Direc- tive	Else-if clause ::ELSEIF/ELIF code	::ELSEIF DEBUG_FLAG≥3
Direc- tive	Terminate ::IF, ::IFD EF or ::IFNDEF sequence	::END, ::ENDIF, ::ENDIFDEF, ::ENDIFNDEF
Direc- tive	Conditional with single variable name	::COND DEBUG □←CUR_RESULT
Direc- tive	Conditional with arbitrary parenthetical expression	::COND (DEBUG≥3) □←CUR_RESULT

## ΔFIX Preprocessor Cheat Sheet

[ΔFIX Cheat Sheet.md]

Cat.	Item	Example
Directive	Preprocessor messages ::MESSAGE/MSG text	::MSG DEBUGGER CODE ACTIVATED!
Directive	Preprocessor error msgs ::ERROR [num] string	::IF CONFLICTING_OPTIONS ::ERROR 911 Conflicting Options Detected!
Directive	Include a file unconditionally	::INCLUDE MyLocalData.dat
Directive	Include a file if not already included earlier	::CINCLUDE printServices.dyalog