Requests and Open Questions

Peter Occil

This version of the document is dated 2025-10-25.

Peter Occil

This page lists questions and issues relating to my articles posted on this site. They span topics in mathematics, probability, random numbers, programming, and image files. Any answers to these questions will greatly improve those articles. If you can answer any of them, post an issue in the **GitHub issues page**¹.

1 Contents

- Contents
- My Probability Questions
- Randomization and Sampling Methods
- Bernoulli Factory Algorithms
- Partially-Sampled Random Numbers
- Randomized Estimation Algorithms
- Color Topics for Programmers
- Questions on Image Formats
- Notes
- License

2 My Probability Questions

The following two pages describe questions I have also posted on *MathOverflow* and other *Stack Exchange* sites. Can you help answer any of these? Answers to them will greatly improve my articles on this site.

- Open Questions on the Bernoulli Factory Problem²
- Other Open Questions on Probability³

3 Randomization and Sampling Methods

Size Reduction Sought:

Of the articles in this repository, Randomization and Sampling Methods⁴ and More Random Sampling Methods⁵ combined are very long.

¹https://github.com/peteroupc/peteroupc.github.io/issues

²https://peteroupc.github.io/bernreq.html

³https://peteroupc.github.io/requestsother.html

⁴https://peteroupc.github.io/randomfunc.html

⁵https://peteroupc.github.io/randomnotes.html

These articles describe numerous algorithms to generate random variates (from discrete and continuous distributions) as well as perform random sampling with and without replacement, shuffling, geometric sampling, and more, assuming a source of "truly" random numbers is available.

I would like to reduce the size of these articles while maintaining the most relevant algorithms for random variate generation.

Here are my goals for both articles:

- To shorten the **Randomization with Real Numbers**⁶ section as much as possible, while still describing the most general (and exact) algorithms possible for sampling real numbers of any distribution.
- To put emphasis on algorithms that work with random integers (or, if necessary, rational numbers), rather than random floating-point numbers.
- To put emphasis on algorithms that sample a distribution *exactly*, or at least with a controlled upper bound on the error. For discussion, see "Exact, Error-Bounded, and Approximate Algorithms⁷".
- To ensure the documents are easy for programmers to understand and implement.

4 Bernoulli Factory Algorithms

• https://peteroupc.github.io/bernoulli.html

This page shows algorithms to turn a coin with an unknown probability of heads into a coin with a different probability of heads, also known as *Bernoulli factories*. A factory function is a function that relates the old probability to the new one. Roughly speaking, a function can be a factory function only if it is the constant 0 or 1, or if it is continuous on its domain and equals neither 0 nor 1 on the open interval (0, 1) (Keane and O'Brien 1994)⁸.

For open questions, see "Open Questions on the Bernoulli Factory Problem9".

5 Partially-Sampled Random Numbers

 $\bullet \ https://peteroupc.github.io/exporand.html$

This page describes a structure for storing a random variate with arbitrary precision.

- 1. We would like to see new implementations of the following:
 - Algorithms that implement **InShape** for specific closed curves, specific closed surfaces, and specific signed distance functions. Recall that **InShape** determines whether a box lies inside, outside, or partly inside or outside a given curve or surface.
 - Descriptions of algorithms for nondiscrete distributions that satisfy the **properties for partially-sampled random number algorithms**¹⁰.
 - Descriptions of new arbitrary-precision algorithms that use the skeleton given in the section "Building an Arbitrary-Precision Sampler".
- 2. Take a polynomial $f(\lambda)$ of even degree n of the form $\operatorname{choose}(n,n/2)^* \lambda^{/2} *(1-\lambda)^{/2} *k$, where k is greater than 1 (thus all f's Bernstein coefficients are 0 except for the middle one, which equals k). Suppose f(1/2) lies in the interval (0, 1). If we do the degree elevation enough times (at least r times), then f's Bernstein coefficients will all lie in [0, 1]. The question is: how many degree elevations are

 $^{^6}$ https://peteroupc.github.io/randomfunc.html#Randomization_with_Real_Numbers

 $^{^{7}} https://peteroupc.github.io/randomnotes.html \# Exact_Error_Bounded_and_Approximate_Algorithms$

⁸Keane, M. S., and O'Brien, G. L., "A Bernoulli factory", ACM Transactions on Modeling and Computer Simulation 4(2), 1994.

⁹https://peteroupc.github.io/bernreq.html

 $^{^{10} \}rm https://peteroupc.github.io/exporand.html \# Properties$

enough? A MathOverflow answer¹¹ showed that r is at least $m = (n/f(1/2)^2)/(1 - f(1/2)^2)$, but is it true that floor(m)+1 elevations are enough?

For other open questions, see "Other Open Questions on Probability¹²".

6 Randomized Estimation Algorithms

https://peteroupc.github.io/estimation.html

For open questions, see "Questions on Estimation Algorithms¹³" and "The Sampling Problem¹⁴".

7 Color Topics for Programmers

https://peteroupc.github.io/colorgen.html

Should this document cover the following topics, and if so, how?

- The CAM02 color appearance model.
- Color rendering metrics for light sources, including color rendering index (CRI) and the metrics given in TM-30-15 by the Illuminating Engineering Society.

Does any of the following exist?

- A method for performing color calibration and color matching using a smartphone's camera and, possibly, a color calibration card or white balance card, provided that method is not covered by any active patents or pending patent applications.
- Reference source code for a method to match a desired color on paper given spectral reflectance curves
 of the paper and of the inks being used in various concentrations, provided that method is not covered
 by any active patents or pending patent applications.

8 Questions on Image Formats

To improve the handling of certain now-rarely seen image file types, such as OS/2 Presentation Manager icon files or Apple icon resources, answers to the following questions would be welcome:

- 1. When OS/2 Presentation Manager draws a color icon, does Presentation Manager ignore the color table of the icon's AND/XOR mask (a two-level image with the AND mask at the top and the XOR mask at the bottom)?
- 2. Can an Apple icon resource (.icns) have two or more icons of the same type (such as 'il32' or 'l8mk')? If so, is the first icon of a given type used? The last icon? All icons of that kind?
- 3. For icon types with a separate mask (such as 'ich4'), can an Apple icon resource (.icns) have an icon of that type but not its corresponding mask ('ich#' in this example)?

The following issues with Windows bitmap files give points that I also seek clarification on. You need not answer them, as they relate to unclear documentation from Microsoft.

- https://github.com/MicrosoftDocs/windows-dev-docs/issues/5241
- https://github.com/MicrosoftDocs/windows-dev-docs/issues/5265

¹²https://peteroupc.github.io/requestsother.html

¹³https://peteroupc.github.io/requestsother.html#Questions_on_Estimation_Algorithms

¹⁴https://peteroupc.github.io/sampling.html

9 Notes

10 License

Any copyright to this page is released to the Public Domain. In case this is not possible, this page is also licensed under Creative Commons $Zero^{15}$.

 $^{^{15} \}rm https://creative commons.org/public domain/zero/1.0/$