

NAUTITECH 46, performance version

Best Boatspeeds (kt)

		TWS (kts)							
		6	8	10	12	14	20	25	30
TWA (°)	45	2.33	3.06	3.9	4.68	6.88	7.39	7.15	6.91
	52	3.28	4.34	5.33	6.25	7.74	8.36	8.69	8.82
	60	4.00	5.20	6.29	7.32	8.27	9.41	9.91	10.24
	70	4.50	5.77	6.94	8.03	9.02	10.73	11.20	11.76
	75	4.64	5.93	7.13	8.23	9.24	10.98	11.81	12.48
	80	4.73	6.05	7.30	8.44	9.49	11.46	12.41	13.19
	90	4.88	6.24	7.51	8.66	9.76	12.37	13.53	14.49
	100	4.87	6.23	7.50	8.65	9.76	12.68	14.49	15.67
	110	4.71	6.04	7.28	8.42	9.49	13.22	15.22	16.67
	120	4.42	5.69	6.87	7.98	9.01	12.37	15.71	17.29
	130	4.03	5.23	6.34	7.40	8.39	11.38	14.36	17.83
	140	3.61	4.73	5.77	6.76	7.72	10.42	12.97	15.87
	150	3.22	4.25	5.21	6.13	7.02	9.51	11.67	14.11
	160	2.91	3.86	4.76	5.63	6.47	8.84	10.78	12.94
	170	2.76	3.66	4.53	5.37	6.18	8.49	10.34	12.36

Mainsail + self-tacking jib

Mainsail + code 0

Mainsail + gennaker

Mainsail + assymetric spinnaker

Sails set : Mainsail
Self-tacking jib
Code 0
Gennaker
Assymetric spinnaker

Hypothesis : foldable propeler Ø510mm
hull roughness 0.05mm
standard roof
masthead wind speed
flat water
salted water
14.5t