

Garlock 7992



MATERIAL PROPERTIES*

Color:	Black
Composition:	Neoprene diaphragm with 22oz. hose duck fabric insert
Durometer, Shore A, +/- 5:	50
Temperature², Maximum, °F (°C):	+250 (+121)
Pressure², Maximum, psig (bar):	N/A
Finish Available	
Thru 1/8":	Smooth
Over 1/8":	Smooth
Number of Plies	
1/16", 3/32, 1/8":	1
3/16":	2
1/4":	3
Thread Count per Inch	
Warp:	20 +/- 1
Fill:	20 +/- 1
Yarns (ply):	4

PHYSICAL PROPERTIES*

ASTM D412	Elastomer Tensile Strength, psi (N/mm²):	1500 (10.4)
ASTM D412	Insert Tensile Strength, warp and fill, psi (N/mm²):	150 (1.04)
ASTM D412	Elastomer Ultimate Elongation, %:	375
ASTM D751	Burst test across 2" (50mm) dia. opening	
	1/8" -1 ply, psi (bar):	290 (20)
ASTM F586	Design Factors	
	"m" factor:	1.25
	"y" factor, psi (N/mm ²):	400 (2.8)
ASTM D2000	Line Call Out:	2BC520A14B14E014E034F17 ⁽³⁾

Notes:

This is a general guide and should not be the sole means of selecting or rejecting this material.

* Values do not constitute specification Limits

² When approaching the maximum or minimum ratings consult Garlock Applications Engineering

³ For rubber compound only, not fabric