

Link Seal

LINK-SEAL® is a modular, elastomer sealing system that creates a permanent, hydrostatic seal for nearly any cylindrical object as it passes through a barrier. LINK-SEAL® modular seals are considered to be the premier method for permanently sealing pipes of any size passing through walls, floors and ceilings. In fact, any cylindrical object may be quickly, easily and permanently sealed against the entry of water, soil or backfill material

Features

- **SAVES TIME AND MONEY**

LINK-SEAL® modular seals install in up to 75% less time compared to hand fitting flashings, mastics or casing boots.

- **POSITIVE HYDROSTATIC SEAL**

LINK-SEAL® modular seals are rated at 20 psig (40 feet of static head), which exceeds the performance requirements of most applications.

- **LONG SEAL LIFE**

LINK-SEAL® modular seals are designed for use as a permanent seal. Seal elements are specially compounded to resist aging and attack from ozone, sunlight, water and a wide range of chemicals.

- **MAXIMUM PROTECTION AGAINST CORROSION**

Standard fasteners have a proprietary corrosion inhibiting coating. Corrosion resistant 316 stainless steel hardware selected for maximum corrosion protection.

- **ISO QUALITY ASSURANCE**

LINK-SEAL® modular seals are manufactured in an ISO 9001:2015 certified facility.

- **CONFIGURE A LINK-SEAL® MODULAR SEAL TO MATCH YOUR APPLICATION**

16 sizes, color coded EPDM, Nitrile, & Silicone elastomers may be used with various hardware options to match performance characteristics with service conditions.

LINK-SEAL® MODULAR SEALS

The best way to permanently seal any cylindrical object, of any size, passing through any type of concrete barrier (wall, floor or ceiling) is to use LINK-SEAL® modular seals. From ductile iron to pre-stressed concrete to metal or plastic pipe, conduit or cables - whatever your application - LINK-SEAL® modular seals will affect a hydrostatic seal capable of holding 20 psig (40 feet of static head) between the pipe and the penetration cylinder through which the pipe passes.




CENTURY-LINE® Engineered Sleeves

CENTURY-LINE® Sleeves are used to create circular holes in concrete poured barriers of all types including; walls, floors and ceilings. Molded from non-conductive, high impact resistant HDPE, CENTURY-LINE® sleeves are lightweight and easily installed by one construction worker without use of cranes or hoists. The best way to guarantee a perfect seal is to use CENTURY-LINE® sleeves with LINK-SEAL® modular seals. They're engineered and sized to provide a stable hole that matches dimensionally with LINKSEAL® modular seals. It makes ordering quick and easy and guarantees a perfect fit - and seal - each and every time



CELL-CAST® Interlocking Hole Forming Disks

CELL-CAST® Interlocking Hole Forming Disks are designed to produce large diameter holes in poured concrete structures. Molded from non-conductive plastic, CELL-CAST® disks are lightweight and may be installed by one construction worker. For larger holes in poured concrete structures, (29.25" to 64.75"Ø) CELL-CAST® disks are used to produce a dimensionally stable hole and smooth concrete surface that is perfect for use with LINKSEAL® modular seals



WS Steel Wall Sleeves

WS Wall Sleeves are constructed from steel and available in a wide range of diameters and lengths. They are an excellent choice for installations where the LINK-SEAL® Modular Seal and WS sleeve assembly would be subject to extremely high temperatures or where fire seals are specified.

