

PKM13EPYH4000-A0

Note: This datasheet may be out of date.

Please download the latest datasheet of PKM13EPYH4000-A0 from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=PKM13EPYH4000-A0











Appearance & Shape









Manufacturing Co., Ltd.

Features

Taking advantage of extensive automatic insertion design technology and materials experience, Murata has developed standard taping type piezoelectric sounders. This Murata technology supports labor and cost saving activities.

Features

- 1. Lead dimension: Improved mouting reliability (cut & clinch) due to round terminal
- 2. High and stable mountability
- 3. Ammo packaging



Applications

Other Usage Consumer/Industrial



Packaging Information

Packaging	Specifications	Standard Packing Quantity
-A0	Radial Taping	500

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ PKM13EPYH4000-A0\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=PKM13EPYH4000-A0

PKM13EPYH4000-A0



Specifications

Oscillation circuits	Not built-in	
Oscillation circuits	Not built-in	
Size	φ12.6×6.9 mm	
Frequency	4.0kHz	
Sound Pressure Level	78dB (typ.)	
Sound Pressure Level	70dB (min.)	
Measure Condition of Sound Pressure Level	[±1.5Vo-p,4.0kHz,square wave, 10cm]	
Capacitance	5.5nF	
Capacitance Tolerance	±30%	
Measurement Condition of Capacitance	[1kHz]	
Maximum input voltage	±15.0Vo-p max.	
Operating Temperature Range	-40°C to 85°C	
Storage Temperature Range	-40°C to 85°C	
Shape	Lead	
Lead Shape	Pin type	
Drive Type	External Drive	
EIAJ Part Number	PS-RP2-C13-40	
Mass	799mg	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




PKM13EPYH4000-A0

Note: This datasheet may be out of date.

Please download the latest datasheet of PKM13EPYH4000-A0 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=PKM13EPYH4000-A0





The following are examples of externally driven circuits.

- (1) Unstable multi-vibrator using Tr.
- (2) Circuits using inverters or NAND gates.



Frequency Response

Recommended Circuit

3 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata:

PKM13EPYH4000-A0 PKM13EPYH40S2-B0