


Scrolls (S)

Flat(F)

1:With 2:Without

Material
Housing Material: LCP, UL94V-0, black
Contact Terminal: Copper Alloy
Metallic Shell: Brass
Electrical
Voltage Rating: 30 V AC
Current Rating: Signal (Pins 2,3,4): 1.0A, Power (Pins 1,5): 1.8A
Contact Resistance: 30mΩ Max
Insulation resistance: 1000MΩ Min
Dielectric withstanding voltage: 250V AC/Minute
Mechanical
Durability: 3,000 cycles
Mating Force: 35N (3.57Kgf) Max
Unmating Force: 8N (0.82Kgf) Min.

U-E-05XX-4BH21-X-X-B
1:Au 1U*
6:Au 30U*
T:TIN
N:NICKEL
B:Brass
1:With 2:Without
S:Scrolls F:Flat
B:BLACK W:WHITE
1:PBT
2:PA6T
3:PA9T
4:LCP

							DSND		DATE		SCALE: N/A	MODEL TYPE: MICRO USB		
					ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.: U-E-05XX-4BH21		
△x					L≤4	±0.2			DATE					
△x					4<L≤	±0.3	CHKD		DATE		UNIT: mm	DWG NO.: U-E-05XX-4BH21-XXB		
△x					16<L≤63	±0.4		DATE						
MARK	DESCRIPTION		DATE	REVISED	APPROVED	L>63	APPD		DATE		SIZE: A4			
REVISIONS						UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED				WEIGHT	SHEET	REVISION
www.xk-da.cn www.helloxkb.com www.helloxkb.cn												1.0g	1/1	A0