Smoothly Coupled Remodeling with Nonlocal Stimulus and Fabric-Guided Anisotropy

Petr Henyš[a]

[a] *Institute of New Technologies and Applied Informatics, Faculty of Mechatronics, Informatics and Interdisciplinary Studies, Technical University of Liberec, Studentská 1402/2, Liberec, 461 17, Czechia*

Abstract

We propose a four-field bone-remodeling formulation that co-evolves displacement $\mathbf{u}$, apparent density ρ, fabric $\mathbf{A}$, and a nonlocal mechanotransductive stimulus S. The elastic response couples a density-scaled isotropic baseline with a nonnegative rank-one reinforcement aligned to a trace-safe normalization of $\mathbf{A}$ (without explicit PSD projection). The stimulus follows a diffusion–reaction balance driven by elastic energy; density evolves via anisotropic transport guided by $\widehat{\mathbf{A}}$ and a smooth stimulus-gated relaxation to $[\rho_{\min}, \rho_{\max}]$; fabric relaxes toward a trace-safe normalization of $\boldsymbol{\varepsilon}^\top \boldsymbol{\varepsilon}$ with spatial diffusion. Time integration is fully implicit Backward–Euler; space is discretized by conforming H^1 finite elements in a unified weak-form notation. Nonlinear coupling is solved by a partitioned block Gauss–Seidel sweep (mechanics $\to$ stimulus $\to$ density $\to$ fabric) wrapped in Type-I Anderson acceleration with Tikhonov regularization and residual safeguards. A single smoothing policy used across clamping, stimulus splits, and normalizations ensures differentiability and preserves coercivity, while the solver architecture yields stable, mesh-robust convergence without monolithic Jacobians.

Keywords: Bone remodeling, finite element method, Backward–Euler, Anderson acceleration, Gauss–Seidel splitting, anisotropic transport, fabric tensor, diffusion–reaction stimulus.

Introduction

Bone is a living composite that continually reorganizes its microstructure to balance mechanical function with metabolic cost. Four mechanobiologically distinct processes drive this adaptation: (i) the elastic response of the solid matrix to loads, (ii) the evolution of mass (apparent density/porosity), (iii) the reorientation of the trabecular/collagen network (fabric anisotropy), and (iv) the production and spatial transport of cell-mediated biochemical signals that couple local mechanics to osteoblast/osteoclast activity. Robust numerical prediction of morphology and stiffness therefore requires a model that co-evolves these *four* fields—displacement u, density ρ, fabric tensor $\mathbf{A}$, and a diffusive mechanotransductive stimulus S—within a single, tightly coupled formulation.

Mechanobiology supports this coupling. First, the mechanical field is not merely a passive input: Turner's "three rules" assert that the magnitude, rate (frequency), and rest intervals of *dynamic* loading govern the osteogenic response [1]. Spatial *strain gradients*—proxies for lacuno–canalicular (LCN) fluid flow—localize bone formation more reliably than strain magnitude alone, as shown in turkey radius models [2] and in exercise-induced periosteal activation in rooster models [3]. These gradients act through osteocytes embedded in the LCN, where fluid shear induces Ca^{2+}/Wnt signaling; acute loading suppresses sclerostin (Sost), while unloading elevates it, shifting the local formation/resorption balance [4]. While mechanosensitive channels such as PIEZO1 contribute to skeletal homeostasis, their cell-type-specific roles in load adaptation

Email address: `petr.henys@tul.cz` (Petr Henyš)
URL: `https://www.fm.tul.cz/personal/petr.henys` (Petr Henyš)

are nuanced and do not obviate the need to resolve the full biophysical cascade from matrix strains to fluid shear to osteocytic signaling [5]. Together, these findings motivate an explicit stimulus field S that is *generated* by mechanical cues and *transported* over osteocytic/vascular pathways (e.g., via diffusion–decay dynamics), rather than a purely local, algebraic "mechanical index."

Second, accurate mechanics–morphology feedback requires density ρ and anisotropy $\mathbf{A}$ to co-evolve and feed back into the elastic moduli. Empirically, bone volume fraction (BV/TV) explains most variance in cancellous stiffness, and fabric anisotropy accounts for nearly all of the remainder; together they reach ∼95–98% explanatory power across anatomical sites, with negligible contribution from other morphometric covariates [6, 7]. Theoretical and constitutive links between $\{\rho, \mathbf{A}\}$ and orthotropic elastic constants are well established—Cowin's fabric–elasticity relations (1985, 1990) and the Zysset–Curnier orthotropic model (1995) connect BV/TV and second-order fabric tensors to the apparent stiffness tensor (including E, G, and ν) [8, 9, 10]. In practice, fabric can be quantified directly from imaging using gray-level structure-tensor or mean-intercept-length methods and validated on HR-pQCT/μCT, enabling evolution laws for $\mathbf{A}$ aligned with principal stress/flow directions [11, 12, 13, 14]. As ρ and $\mathbf{A}$ change through remodeling, the spatial stiffness field—and thus the displacement field u and its gradients—must be updated consistently to avoid spurious transients and mesh-dependent artifacts; morphology–elasticity models with full fabric information achieve the highest predictive accuracy in such coupled simulations [15, 16].

Third, the remodeling stimulus that drives BMU-scale biology is not localized to a voxel or finite element. Experiments and theory both indicate spatial nonlocality through osteocytic/vascular networks; modern formulations therefore promote the stimulus to a *field* obeying a diffusion–reaction equation, which systematically removes unphysical checkerboarding and captures healing or damage–remodeling interactions [17, 18, 19]. Recent work also explores multi-stimulus energetics (e.g., shear vs. normal components) in continuum settings, reinforcing the need to track multiple evolving material parameters beyond a single density variable [20].

From a numerical standpoint, splitting the physics into loosely coupled or explicit updates is in general more fragile than monolithic schemes: density-only algorithms are prone to mesh-dependent checkerboards and near-field oscillations near load singularities [21, 19]. However, our method—using a partitioned fixed-point scheme augmented with Anderson acceleration—substantially mitigates these issues. There is strong evidence in analogous multiphysics settings (e.g., poromechanics) that splitting plus Anderson acceleration can stabilize splitting schemes and produce robust convergence even when classical fixed-point (or Picard/L-scheme) iterations stray near non-contractive regimes [22, 23, 24].

Further, solver technology in our implementation removes many traditional barriers. In particular, we precondition at the block/field level, apply Anderson-accelerated outer fixed-point iterates, and use adaptive damping. This yields numerically stable behavior and quasi-mesh-independent convergence rates despite feedback loops from stimulus diffusion, fabric updates, and constitutive coupling. While monolithic, fully implicit schemes have theoretical robustness, our results suggest that the splitting+Anderson framework achieves a strong balance: minimal invasiveness in existing codes, flexibility to add physiological variables, and performance in experiments consistent with biological data.

Comparison with related models and novelty

Our formulation sits between classical density–only mechanostat models and fully coupled cell–population or damage–remodeling frameworks. In *local* mechanostat models the remodeling drive is a pointwise function of a mechanical index, typically strain or strain–energy density, and only the density ρ evolves; transport and fabric are absent and spatial regularity is supplied ad hoc (cf. early density models and follow–ups reviewed in [17]). Nonlocal and *diffusive* stimulus fields—as in (7)—have been advocated to account for osteocytic/vascular communication and to remove checkerboarding; this strand has gained traction in the last decade [17, 18]. On the elasticity side, orthotropic models that couple BV/TV and second–order fabric tensors to the full fourth–order stiffness tensor (Cowin's relations and the Zysset–Curnier model) are now standard in homogenized micro–FE and hFE pipelines [8, 9, 10, 6, 7]. Our constitutive choice preserves this spirit but adopts an energetically nonnegative, rank–one reinforcement aligned with a unit–trace direction

proxy $\widehat{\mathbf{A}}$, which empirically captures the dominant directional effect while simplifying the numerics; it leaves the isotropic floor strictly coercive through the smooth clamp $\widetilde{\rho} \geq \rho_{\min}$, cf. (5).

In the *evolution* of anisotropy, several authors align fabric with stress or strain measures and regularize it by diffusion or smoothing (e.g. structure–tensor approaches and stress–alignment hypotheses, see [11, 13, 14]). We follow this line by relaxing $\mathbf{A}$ toward the trace–safe normalization $\widehat{\mathbf{M}}$ of $\boldsymbol{\varepsilon}^\top\boldsymbol{\varepsilon}$, which robustly aligns principal directions while avoiding non–differentiable projections and without enforcing positive semidefiniteness of $\widehat{\mathbf{A}}$ (the isotropic fallback and transport floor suffice in practice).

From a *numerical* viewpoint, Backward–Euler time stepping and conforming Galerkin spaces are conventional. What is less common in remodeling is our solver strategy: we retain a partitioned block Gauss–Seidel fixed–point and wrap it in Anderson acceleration with Tikhonov regularization and safeguards [22, 23, 24]. Similar acceleration/stabilization is well established in poromechanics and other multiphysics splittings, but to our knowledge remains underused in bone remodeling. The result is a solver that is simple to implement on top of existing FE components yet markedly more robust than plain Picard/GS in strongly coupled regimes.

Strong form (nondimensionalized) equations

Scaling and nondimensionalization. We adopt characteristic scales L_c (length), u_c (displacement), ρ_c (apparent density), E_0 (reference modulus), and $t_c = 1/\tau_S^{\dim}$ (time). Stresses and energy are measured by $\sigma_c = E_0(u_c/L_c)$ and $\psi_c = E_0(u_c/L_c)^2$. Dimensional fields $(x, t, \mathbf{u}, \rho, S, \mathbf{A})$ map to dimensionless ones via

$$x = L_c\, x', \quad t = t_c\, t', \quad \mathbf{u} = u_c\, \mathbf{u}', \quad \rho = \rho_c\, \rho', \quad S = \frac{1}{\gamma_\rho t_c}\, S', \quad \mathbf{A} = \mathbf{A}'.$$

All equations below are written in primeless variables after dropping the primes. The boundary partition is $\partial\Omega = \Gamma_D \cup \Gamma_N$ with outward unit normal $\mathbf{n}$. The nondimensional traction vector $\mathbf{t}$ is scaled by σ_c; for example, uniaxial compression is expressed as $\mathbf{t} = (-t_p/\sigma_c, 0, \ldots)$ on Γ_N. We use a *single* smoothness parameter $\varepsilon > 0$ consistently across operators whenever possible (density clamp, stimulus split, and trace-safe normalizations); when separate symbols appear (e.g., ε_B in the direction target), they default to ε unless stated otherwise for numerical reasons. Likewise, we keep a single steepness parameter $k > 0$ for gating functions, with $k_B = k$ unless noted.

Mechanical submodel

Kinematics and equilibrium. We adopt small-strain kinematics with the symmetric gradient

$$\boldsymbol{\varepsilon}(\mathbf{u}) := \tfrac{1}{2}\big(\nabla\mathbf{u} + \nabla\mathbf{u}^\top\big) \in \mathbb{R}^{d\times d}_{\mathrm{sym}}, \qquad d \in \{2, 3\}. \tag{1}$$

Under quasi-static conditions the balance of linear momentum reads

$$-\nabla\cdot\boldsymbol{\sigma}(\mathbf{u}, \rho, \mathbf{A}) = \mathbf{0} \ \text{ in } \Omega, \qquad \mathbf{u} = \mathbf{0} \ \text{ on } \Gamma_D, \qquad \boldsymbol{\sigma}(\mathbf{u}, \rho, \mathbf{A})\,\mathbf{n} = \mathbf{t} \ \text{ on } \Gamma_N. \tag{2}$$

Constitutive structure. The stress response consists of an isotropic baseline whose stiffness scales with apparent density and a directional reinforcement aligned with the local fabric. Let $\nu \in (-1, 1/2)$ be Poisson's ratio and $n > 0$ an exponent. The density–modulus relation is

$$\begin{aligned} E(\rho) &= E_0\, \widetilde{\rho}^{\,n}, \\ \lambda(\rho) &= \frac{E(\rho)\,\nu}{(1+\nu)(1-2\nu)}, \\ \mu(\rho) &= \frac{E(\rho)}{2(1+\nu)}. \end{aligned} \tag{3}$$

The stress law is

$$\boldsymbol{\sigma}(\mathbf{u}, \rho, \mathbf{A}) = 2\,\mu(\rho)\,\boldsymbol{\varepsilon}(\mathbf{u}) \ + \ \lambda(\rho)\,\mathrm{tr}\big(\boldsymbol{\varepsilon}(\mathbf{u})\big)\,\mathbf{I} \ + \ \xi_{\mathrm{aniso}}\, E(\rho)\,\big\langle \widehat{\mathbf{A}},\, \boldsymbol{\varepsilon}(\mathbf{u})\big\rangle\, \widehat{\mathbf{A}}. \tag{4}$$

Here $\xi_{\text{aniso}} \geq 0$ scales the anisotropic reinforcement, $\langle \cdot, \cdot \rangle$ denotes the Frobenius inner product, and $\widehat{\mathbf{A}}$ is a symmetric, unit-trace proxy of $\mathbf{A}$ constructed below. The last term is the action of the rank-one fourth-order operator $\widehat{\mathbf{A}} \otimes \widehat{\mathbf{A}}$ on $\boldsymbol{\varepsilon}(\mathbf{u})$ since

$$(\widehat{\mathbf{A}} \otimes \widehat{\mathbf{A}}) : \boldsymbol{\varepsilon} = \langle \widehat{\mathbf{A}}, \boldsymbol{\varepsilon} \rangle \, \widehat{\mathbf{A}}, \qquad \forall \, \boldsymbol{\varepsilon} \in \mathbb{R}^{d \times d}_{\text{sym}}.$$

The associated quadratic contribution is nonnegative:

$$\big(\langle \widehat{\mathbf{A}}, \boldsymbol{\varepsilon} \rangle \, \widehat{\mathbf{A}} \big) : \boldsymbol{\varepsilon} = \langle \widehat{\mathbf{A}}, \boldsymbol{\varepsilon} \rangle^2 \geq 0.$$

Smooth lower density clamp. To maintain uniform strong ellipticity and avoid case distinctions in highly porous regions, we use the same smooth "max" as in the implementation:

$$\widetilde{\rho}(\rho; \rho_{\min}, \varepsilon) := \rho_{\min} + \tfrac{1}{2} \Big[(\rho - \rho_{\min}) + \sqrt{(\rho - \rho_{\min})^2 + \varepsilon^2} \Big]. \tag{5}$$

This monotone, everywhere differentiable approximation of $\max\{\rho, \rho_{\min}\}$ enforces $\widetilde{\rho} \geq \rho_{\min}$ with a single global smoothing width $\varepsilon > 0$. No upper clamp is imposed.

Trace-safe smooth normalization of the direction field. We form the symmetric part $\mathbf{A}_{\text{sym}} := \frac{1}{2}(\mathbf{A} + \mathbf{A}^\top)$ and normalize it to a unit-trace tensor using a smooth Gram construction:

$$\widehat{\mathbf{A}} \;:=\; \frac{\mathbf{A}_{\text{sym}}^\top \mathbf{A}_{\text{sym}} + \varepsilon \, \mathbf{I}}{\operatorname{tr}\big(\mathbf{A}_{\text{sym}}^\top \mathbf{A}_{\text{sym}} + \varepsilon \, \mathbf{I} \big)}. \tag{6}$$

This map yields a *symmetric, unit-trace* tensor; for any $\varepsilon > 0$ it is in fact *positive-definite*. No conditional branching or explicit cone projections are used.

Ellipticity and energy bounds without degeneracy. Define the nondimensional strain-energy density

$$\psi(\mathbf{u}, \rho, \mathbf{A}) := \mu(\rho) \, \boldsymbol{\varepsilon}(\mathbf{u}) : \boldsymbol{\varepsilon}(\mathbf{u}) + \tfrac{1}{2} \, \lambda(\rho) \, \big(\operatorname{tr} \boldsymbol{\varepsilon}(\mathbf{u}) \big)^2 + \tfrac{1}{2} \, \xi_{\text{aniso}} \, E(\rho) \, \big\langle \widehat{\mathbf{A}}, \boldsymbol{\varepsilon}(\mathbf{u}) \big\rangle^2.$$

Using (3)–(5) with $\rho_{\min} > 0$ and $\nu \in (-1, 1/2)$, and applying Korn's inequality on Ω, there exists $c_0 > 0$ depending only on $(\nu, n, \rho_{\min}, E_0)$ and the domain such that

$$\int_\Omega \psi(\mathbf{u}, \rho, \mathbf{A}) \, \mathrm{d}x \;\geq\; c_0 \, \|\mathbf{u}\|^2_{H^1(\Omega)}.$$

The anisotropic contribution is nonnegative because it is quadratic in $\langle \widehat{\mathbf{A}}, \boldsymbol{\varepsilon}(\mathbf{u}) \rangle$. Although the anisotropic reinforcement in (4) is introduced at the constitutive level rather than derived from a fully coupled energy for $(\mathbf{u}, \mathbf{A})$, at each mechanics step with $(\rho, \widehat{\mathbf{A}})$ held fixed it contributes the quadratic term

$$\tfrac{1}{2} \, \xi_{\text{aniso}} \, E(\rho) \, \big\langle \widehat{\mathbf{A}}, \boldsymbol{\varepsilon}(\mathbf{u}) \big\rangle^2 \;\geq\; 0.$$

Hence it cannot deteriorate the Legendre–Hadamard constant of the isotropic baseline; the strong ellipticity inherited from $\mu(\rho) > 0$ and $\lambda(\rho) + \frac{2}{d}\mu(\rho) > 0$ (uniformly ensured by the smooth lower clamp $\widetilde{\rho} \geq \rho_{\min} > 0$) is preserved and may only be improved along the principal directions selected by $\widehat{\mathbf{A}}$. The strain-energy density therefore satisfies the pointwise lower bound

$$\psi(\boldsymbol{\varepsilon}; \rho, \widehat{\mathbf{A}}) \;\geq\; c_{\text{iso}} \, \boldsymbol{\varepsilon} : \boldsymbol{\varepsilon},$$

with a constant $c_{\text{iso}} > 0$ depending only on $(\nu, n, \rho_{\min}, E_0)$. Korn's inequality then yields the standard global coercivity.

Quantitative analysis and biological interpretation. The density–modulus law (3) encodes the empirical power-law scaling between bone volume fraction (BV/TV) and apparent stiffness. The directional reinforcement supplements this isotropic baseline by increasing stiffness along preferred fabric directions, consistent with homogenized tissue-level elasticity models and with observations of strain-adaptive anisotropy in trabecular bone. The smooth lower clamp (5) guarantees strictly positive stiffness even in highly porous regions, thus preventing mechanical degeneracy and preserving differentiability. The normalization (6) filters the computed direction field into a *symmetric, unit-trace* descriptor; with $\varepsilon > 0$ it is *positive-definite*. This combination yields a mechanically transparent, numerically robust model suitable for coupling with remodeling stimuli and evolution equations.

Stimulus submodel

We represent the mechanotransductive drive by a dimensionless scalar field $S : \Omega \times (0,T] \to \mathbb{R}$ that is *generated* by mechanical activity and *transported* through osteocytic/vascular pathways. Positive values correspond to net formation drive and negative values to net resorption drive; downstream remodeling laws act on smooth decompositions $S^{\pm}$ and $|S|$, so the sign of S is intentional and no positivity constraint is imposed on the stimulus itself.

The stimulus obeys a linear diffusion–reaction balance with a source proportional to departures from a homeostatic elastic-energy level,

$$c_S\,\partial_t S \;-\; \kappa_S\,\Delta S \;+\; \tau_S\,S \;=\; r_S\big(\psi(\mathbf{u},\rho,\mathbf{A}) - \psi_{\mathrm{ref}}\big) \quad \text{in } \Omega\times(0,T], \tag{7}$$

supplemented with homogeneous Neumann boundary conditions and an initial state,

$$\nabla S\cdot\mathbf{n} = 0 \;\; \text{on } \partial\Omega\times(0,T], \qquad S(\cdot,0) = S_0 \;\; \text{in } \Omega. \tag{8}$$

Here $c_S > 0$ denotes a temporal capacity, $\kappa_S \geq 0$ a diffusivity, and $\tau_S > 0$ the reaction/turnover rate. (Choosing $t_c = 1/\tau_S^{\mathrm{dim}}$ would set $\tau_S \equiv 1$ in nondimensional variables, but in the implementation we *retain* τ_S explicitly.) The mechanical drive is the instantaneous nondimensional elastic-energy density

$$\psi(\mathbf{u},\rho,\mathbf{A}) \;=\; \tfrac{1}{2}\,\boldsymbol{\sigma}(\mathbf{u},\rho,\mathbf{A}) : \boldsymbol{\varepsilon}(\mathbf{u}) \;\geq 0, \tag{9}$$

with $\boldsymbol{\varepsilon}$ and $\boldsymbol{\sigma}$ defined in the mechanical model.

Quantitative analysis and biological interpretation. Equation (7) acts as a spatio-temporal low-pass filter of the mechanical drive $\psi - \psi_{\mathrm{ref}}$. Regions of sustained supra-homeostatic energy ($\psi > \psi_{\mathrm{ref}}$) accumulate positive stimulus, while sub-homeostatic regions accumulate negative stimulus. Diffusion broadens and smooths these regions over the characteristic length $\ell_S = \sqrt{\kappa_S/\tau_S}$ (in general), while the reaction term damps transient fluctuations with a characteristic time $t_S = c_S/\tau_S$. The capacity c_S thus sets the inertia with respect to temporal fluctuations in the drive, κ_S controls spatial spread via gap-junction/vascular pathways, and τ_S sets the local turnover toward homeostasis. The homogeneous Neumann condition corresponds to zero normal flux of S at $\partial\Omega$.

Density submodel

The nondimensional apparent density $\rho = \rho(x,t)$ evolves under anisotropic transport aligned with the fabric and under a stimulus-driven relaxation toward admissible bounds $\rho_{\min}$ and $\rho_{\max}$ (both nondimensional). The stimulus $S = S(x,t)$ is the dimensionless field introduced in the stimulus submodel; its sign distinguishes formation ($S > 0$) from resorption ($S < 0$). The nondimensional strong form reads, for $(x,t) \in \Omega\times(0,T]$,

$$\partial_t\rho \;-\; \nabla\cdot\big(\mathbf{D}_\rho(x,t)\,\nabla\rho\big) \;+\; \big|S\big|_\varepsilon\,\rho \;=\; S_\varepsilon^+\,\rho_{\max} + S_\varepsilon^-\,\rho_{\min}. \tag{10}$$

supplemented with homogeneous no-flux boundary conditions and an admissible initial state,

$$\big(\mathbf{D}_\rho\,\nabla\rho\big)\cdot\mathbf{n} = 0 \quad \text{on } \partial\Omega\times(0,T], \qquad \rho(\cdot,0) = \rho_0 \;\; \text{in } \Omega, \;\; \rho_{\min} \leq \rho_0 \leq \rho_{\max}. \tag{11}$$

Anisotropic transport. Directional transport is modeled by the symmetric diffusion tensor

$$\mathbf{D}_\rho(x,t) \;=\; \beta_\perp \mathbf{I} \;+\; \big(\beta_\parallel - \beta_\perp\big)\,\widehat{\mathbf{A}}(x,t), \tag{12}$$

where $\beta_\parallel, \beta_\perp > 0$ are nondimensional diffusivities along and transverse to the fabric, respectively, and $\widehat{\mathbf{A}}(x,t)$ is the *unit-trace, symmetric, positive-definite* fabric tensor obtained by the Gram normalisation described above. With $\beta_\parallel, \beta_\perp > 0$ this yields a uniformly positive-definite $\mathbf{D}_\rho$ without any conditional branching or explicit cone projections.

Stimulus split and kinetic rate. To keep the right-hand side and the damping term in (10) smooth at $S = 0$, we adopt a single $\mathcal{C}^\infty$ approximation of the absolute value and use it to define the positive/negative parts:

$$|S|_\varepsilon := \sqrt{S^2 + \varepsilon^2}, \qquad S_\varepsilon^\pm := \tfrac{1}{2}(|S|_\varepsilon \pm S)\,. \tag{13}$$

For $|S| \gg \varepsilon$ this coincides with the exact split; in a small neighborhood of the origin it provides a simple, globally smooth transition used consistently across the scheme.

Quantitative analysis and biological interpretation. Equation (10) combines anisotropic diffusion with a stimulus-gated logistic relaxation. The diffusion term $\nabla\cdot(\mathbf{D}_\rho\nabla\rho)$ spreads mass preferentially along the principal directions of $\widehat{\mathbf{A}}$, while the reaction terms on the right- and left-hand sides drive ρ toward $\rho_{\max}$ where $S > 0$ and toward $\rho_{\min}$ where $S < 0$. The damping $|S|_\varepsilon\,\rho$ guarantees that, in regions of large $|S|$, the relaxation is fast and saturates at the appropriate bound, whereas in regions where $S \approx 0$ the dynamics is transport-dominated. Under the no-flux boundary condition (11) the admissible interval $[\rho_{\min}, \rho_{\max}]$ is invariant in the sense of the parabolic comparison principle: if $\rho_{\min} \le \rho_0 \le \rho_{\max}$ a.e. in Ω, then $\rho_{\min} \le \rho(\cdot,t) \le \rho_{\max}$ for all $t \in (0,T]$. Physically, (10) states that sustained supra-homeostatic stimulus accumulates mass up to $\rho_{\max}$, sustained sub-homeostatic stimulus removes mass down to $\rho_{\min}$, and the anisotropic transport couples neighboring regions along the evolving fabric architecture.

Direction (fabric) submodel

The local fabric is described by a second-order, dimensionless tensor field $\mathbf{A} = \mathbf{A}(x,t) \in \mathbb{R}^{d\times d}$ ($d \in \{2,3\}$), which aligns with mechanically preferred directions and is smoothed in space by diffusion. We regard $\mathbf{A}$ as symmetric and treat its dynamics as a relaxation–diffusion flow toward a unit-trace, positive-definite target extracted from the current mechanical state. The nondimensional strong form on a bounded Lipschitz domain is

$$c_A\,\partial_t\mathbf{A} \;-\; c_A\,\ell^2\,\Delta\mathbf{A} \;+\; \tau_A\,\mathbf{A} \;=\; \tau_A\,\widehat{\mathbf{M}}(\mathbf{u})\,. \tag{14}$$

supplemented with homogeneous no-flux boundary conditions and an admissible initial state,

$$\partial_{\mathbf{n}}\mathbf{A} := \big(\nabla\mathbf{A}\big)\,\mathbf{n} = \mathbf{0} \quad \text{on } \partial\Omega\times(0,T], \qquad \mathbf{A}(\cdot,0) = \mathbf{A}_0 \;\text{ in } \Omega. \tag{15}$$

Here $\ell > 0$ is a nondimensional interaction length, $c_A > 0$ a capacity, and $\tau_A > 0$ a relaxation rate. The Laplacian and normal derivative act componentwise on $\mathbf{A}$. Equation (14) is linear and uniformly parabolic in space–time for $\ell > 0$ (and uniformly elliptic in space at each time with $\tau_A > 0$).

Target construction from mechanics. Let $\boldsymbol{\varepsilon}(\mathbf{u})$ be the small-strain tensor from the mechanical submodel. The instantaneous, dimensionless alignment tensor

$$\mathbf{M}(\mathbf{u}) \;:=\; \boldsymbol{\varepsilon}(\mathbf{u})^\top\,\boldsymbol{\varepsilon}(\mathbf{u}) \tag{16}$$

is symmetric and positive semidefinite. We normalize it by the same *trace-safe shift-and-rescale* used throughout (no blending or gating),

$$\widehat{\mathbf{M}} \;=\; \frac{\mathbf{M} + \varepsilon_M\,\mathbf{I}}{\operatorname{tr}\big(\mathbf{M} + \varepsilon_M\,\mathbf{I}\big)}\,, \tag{17}$$

which is smooth in $\mathbf{M}$, symmetric, *positive-definite for* $\varepsilon_M > 0$, and unit-trace by construction.

Quantitative analysis and biological interpretation. The reaction term $\tau_A(\widehat{\mathbf{M}} - \mathbf{A})$ in (14) drives $\mathbf{A}$ toward the mechanically informed, unit-trace target, while the diffusion $-\ell^2 c_A \Delta \mathbf{A}$ spreads directional information and regularizes spatial oscillations. The homogeneous Neumann boundary condition represents no flux of directional content across $\partial\Omega$. Symmetry is preserved by the dynamics; the choice of a unit-trace target ensures that, at steady state ($\partial_t \mathbf{A} = 0$), the solution coincides with a spatially smoothed version of $\widehat{\mathbf{M}}$. Tracing (14) and using $\operatorname{tr} \widehat{\mathbf{M}} = 1$ gives

$$\partial_t \big(\operatorname{tr} \mathbf{A}\big) - \ell^2 \, \Delta\big(\operatorname{tr} \mathbf{A}\big) + \frac{\tau_A}{c_A} \operatorname{tr} \mathbf{A} \;=\; \frac{\tau_A}{c_A},$$

so the spatial average of $\operatorname{tr} \mathbf{A}$ relaxes monotonically to 1 under no-flux boundaries; pointwise, the relaxation term anchors $\operatorname{tr} \mathbf{A}$ toward unity while diffusion communicates this constraint across Ω. The coupling (16)–(17) aligns principal directions of $\mathbf{A}$ with those of a local strain metric, consistent with strain-adaptation hypotheses in trabecular microstructures, while maintaining global smoothness and avoiding non-differentiable thresholds.

Regularization parameters and defaults. Unless a sensitivity study dictates otherwise, we recommend using a unified smoothness ε (and gate steepness k) across (5), (13), (6), and (17) by setting $\varepsilon_B = \varepsilon_M = \varepsilon$ and $k_B = k_M = k$. With the Gram maps (6) and (17), both $\widehat{\mathbf{A}}$ and $\widehat{\mathbf{M}}$ are *unit-trace and SPD* for any $\varepsilon > 0$; no cone projections or conditional branches are required.

Backward–Euler time discretization (nondimensional)

Let $0 = t^0 < t^1 < \cdots < t^N = T$ be a partition with $\Delta t^n := t^n - t^{n-1} > 0$. For any time-dependent field X, write $X^n \approx X(\cdot, t^n)$. Mechanics is quasi-static (no time derivative); S, ρ, and $\mathbf{A}$ are advanced by fully implicit Backward–Euler steps. Boundary and initial conditions are enforced at each time level exactly as in (8), (11), and (15).

Mechanics at t^n. Find $\mathbf{u}^n$ such that

$$-\nabla\!\cdot\boldsymbol{\sigma}(\mathbf{u}^n, \rho^n, \mathbf{A}^n) = \mathbf{0} \text{ in } \Omega, \qquad \mathbf{u}^n = \mathbf{0} \text{ on } \Gamma_D, \qquad \boldsymbol{\sigma}(\mathbf{u}^n, \rho^n, \mathbf{A}^n)\,\mathbf{n} = \mathbf{t} \text{ on } \Gamma_N, \tag{18}$$

with $\boldsymbol{\sigma}$ given by (4), $E(\rho)$ by (3) with the lower clamp (5), and $\widehat{\mathbf{A}}$ built from $\mathbf{A}^n$ via (6).

Stimulus. (We keep the reaction coefficient τ_S explicit to match the implementation constants.) Given $\psi(\mathbf{u}^n, \rho^n, \mathbf{A}^n)$ from (9), find S^n such that

$$\frac{c_S}{\Delta t^n}\big(S^n - S^{n-1}\big) \;-\; \kappa_S \, \Delta S^n \;+\; \tau_S \, S^n \;=\; r_S\Big(\psi(\mathbf{u}^n, \rho^n, \mathbf{A}^n) - \psi_{\text{ref}}\Big) \quad \text{in } \Omega, \tag{19}$$

with the Neumann condition from (8) and $S^0 = S_0$.

Density. Let $\mathbf{D}_\rho(\widehat{\mathbf{A}}^{\,n})$ be as in (12) and let $|S|_\varepsilon$ and $S_\varepsilon^{\pm}$ be as in (13). Find ρ^n such that

$$\frac{1}{\Delta t^n}\big(\rho^n - \rho^{n-1}\big) \;-\; \nabla\!\cdot\big(\mathbf{D}_\rho(\widehat{\mathbf{A}}^{\,n})\,\nabla\rho^n\big) \;+\; |S^n|_\varepsilon \, \rho^n \;=\; S_\varepsilon^{n,+}\,\rho_{\max} \;+\; S_\varepsilon^{n,-}\,\rho_{\min} \quad \text{in } \Omega, \tag{20}$$

with the no–flux condition from (11) and $\rho^0 = \rho_0$.

Direction/fabric. With $\mathbf{M}(\mathbf{u}^n) = \boldsymbol{\varepsilon}(\mathbf{u}^n)^\top \boldsymbol{\varepsilon}(\mathbf{u}^n)$ and $\widehat{\mathbf{M}}(\mathbf{u}^n)$ from (17), find $\mathbf{A}^n$ such that

$$\frac{c_A}{\Delta t^n}\big(\mathbf{A}^n - \mathbf{A}^{n-1}\big) \;-\; c_A \, \ell^2 \, \Delta \mathbf{A}^n \;+\; \tau_A \, \mathbf{A}^n \;=\; \tau_A \, \widehat{\mathbf{M}}(\mathbf{u}^n) \quad \text{in } \Omega, \tag{21}$$

with the componentwise no–flux condition from (15) and $\mathbf{A}^0 = \mathbf{A}_0$.

Finite element spaces. For displacements we use the conforming space

$$V_h := \{\, \mathbf{v}_h \in [H^1(\Omega)]^d : \ \mathbf{v}_h = \mathbf{0} \text{ on } \Gamma_D \,\},$$

for scalar fields $Q_h \subset H^1(\Omega)$, and for second-order tensors

$$T_h := \{\, \mathbf{Q}_h \in [H^1(\Omega)]^{d\times d} \,\}.$$

Symmetry of $\mathbf{A}$ is respected by using $\boldsymbol{\varepsilon}(\cdot)$ and by taking the symmetric part before the Gram normalisation (6) when building $\widehat{\mathbf{A}}$.

Mechanics at t^n (weak form). Find $\mathbf{u}_h^n \in V_h$ such that for all $\mathbf{v}_h \in V_h$,

$$a_u(\mathbf{u}_h^n, \mathbf{v}_h; \rho^n, \widehat{\mathbf{A}}^{\,n}) \ = \ \ell_u(\mathbf{v}_h), \tag{22}$$

with the bilinear and linear forms

$$\begin{aligned} a_u(\mathbf{w}, \mathbf{v}; \rho, \widehat{\mathbf{A}}) &:= \big(2\,\mu(\rho)\,\boldsymbol{\varepsilon}(\mathbf{w}),\, \boldsymbol{\varepsilon}(\mathbf{v})\big) \ + \ \big(\lambda(\rho)\,\mathrm{tr}\,\boldsymbol{\varepsilon}(\mathbf{w}),\, \mathrm{tr}\,\boldsymbol{\varepsilon}(\mathbf{v})\big) \\ &\quad + \ \big(\xi_{\mathrm{aniso}}\, E(\rho)\,\langle \widehat{\mathbf{A}}, \boldsymbol{\varepsilon}(\mathbf{w})\rangle,\, \langle \widehat{\mathbf{A}}, \boldsymbol{\varepsilon}(\mathbf{v})\rangle\big), \\ \ell_u(\mathbf{v}) &:= \langle \mathbf{t}, \mathbf{v}\rangle_{\Gamma_N}, \end{aligned}$$

where $\mu(\rho)$, $\lambda(\rho)$, and $E(\rho)$ are from (3), and $\widehat{\mathbf{A}}^{\,n}$ is built from $\mathbf{A}^n$ via the Gram normalisation (6).

Stimulus (Backward–Euler weak form). Given $\psi(\mathbf{u}^n, \rho^n, \mathbf{A}^n)$ from (9), find $S_h^n \in Q_h$ such that for all $q_h \in Q_h$,

$$\Big(\frac{c_S}{\Delta t^n} S_h^n, q_h\Big) \ + \ \kappa_S\,(\nabla S_h^n, \nabla q_h) \ + \ \tau_S\,(S_h^n, q_h) \ = \ \Big(\frac{c_S}{\Delta t^n} S_h^{n-1}, q_h\Big) \ + \ \big(r_S(\psi(\mathbf{u}^n, \rho^n, \mathbf{A}^n) - \psi_{\mathrm{ref}}), q_h\big). \tag{23}$$

Density (Backward–Euler weak form). With $\mathbf{D}_\rho(\widehat{\mathbf{A}}^{\,n})$ from (12) and the split $|S^n|_\varepsilon$, $S_\varepsilon^{n,\pm}$ from (13), find $\rho_h^n \in Q_h$ such that for all $p_h \in Q_h$,

$$\Big(\frac{1}{\Delta t^n}\rho_h^n, p_h\Big) \ + \ \big(\mathbf{D}_\rho(\widehat{\mathbf{A}}^{\,n})\,\nabla\rho_h^n, \nabla p_h\big) \ + \ \big(|S^n|_\varepsilon\,\rho_h^n, p_h\big) \ = \ \Big(\frac{1}{\Delta t^n}\rho_h^{n-1}, p_h\Big) \ + \ \big(S_\varepsilon^{n,+}\rho_{\max} + S_\varepsilon^{n,-}\rho_{\min}, p_h\big). \tag{24}$$

Direction/fabric (Backward–Euler weak form). With $\mathbf{M}(\mathbf{u}^n) = \boldsymbol{\varepsilon}(\mathbf{u}^n)^\top\boldsymbol{\varepsilon}(\mathbf{u}^n)$ and $\widehat{\mathbf{M}}(\mathbf{u}^n)$ from (17), find $\mathbf{A}_h^n \in T_h$ such that for all $\mathbf{Q}_h \in T_h$,

$$\Big(\frac{c_A}{\Delta t^n}\mathbf{A}_h^n, \mathbf{Q}_h\Big) \ + \ c_A\,\ell^2\,(\nabla\mathbf{A}_h^n, \nabla\mathbf{Q}_h) \ + \ \tau_A\,(\mathbf{A}_h^n, \mathbf{Q}_h) \ = \ \Big(\frac{c_A}{\Delta t^n}\mathbf{A}_h^{n-1}, \mathbf{Q}_h\Big) \ + \ \tau_A\,(\widehat{\mathbf{M}}(\mathbf{u}^n), \mathbf{Q}_h). \tag{25}$$

Remarks. (i) Dirichlet conditions for mechanics are imposed strongly in V_h; natural boundary conditions enter via $\langle\cdot,\cdot\rangle_{\Gamma_N}$. (ii) The tensor unknown $\mathbf{A}_h^n$ is represented componentwise; symmetry is preserved at the continuous level and is respected numerically through the use of $\boldsymbol{\varepsilon}(\cdot)$ and the trace-safe normalisation (6).

Fixed-point solver at a given time level: block Gauss–Seidel with Anderson acceleration

We describe the nonlinear solver used to obtain $(\mathbf{u}^n, S^n, \rho^n, \mathbf{A}^n)$ at a fixed time level t^n from the Backward–Euler subproblems (18)–(21). Let

$$\mathcal{X} \ := \ V \times Q \times Q \times T, \qquad \mathbf{x} \ = \ (\mathbf{u}, S, \rho, \mathbf{A}) \in \mathcal{X},$$

with the product inner product

$$\langle \mathbf{x}, \mathbf{y}\rangle_{\mathcal{X}} \ = \ \alpha_u\,(\boldsymbol{\varepsilon}(\mathbf{u}), \boldsymbol{\varepsilon}(\mathbf{v})) \ + \ \alpha_S\,(S, q) \ + \ \alpha_\rho\,(\rho, p) \ + \ \alpha_A\,(\mathbf{A}, \mathbf{Q}), \tag{26}$$

for $\mathbf{y} = (\mathbf{v}, q, p, \mathbf{Q})$ and positive weights $\alpha_\bullet$. In the implementation, the *merit/stopping* metric is a projected 2–norm on the flattened state with RMS-per-DOF block weights (i.e., $w_i = 1/N_i$) that projects out Dirichlet DOFs in mechanics; the flattened state order for norms and mixing is $(\mathbf{u}, \rho, \mathbf{A}, S)$.

Block map. Define the block Gauss–Seidel map $\mathcal{G} : \mathcal{X} \to \mathcal{X}$ by

$$\mathcal{G}(\mathbf{u}, S, \rho, \mathbf{A}) := \Big(\underbrace{\mathsf{U}(\rho, \mathbf{A})}_{\text{mech}}, \underbrace{\mathsf{S}(\mathbf{u}, \rho, \mathbf{A})}_{\text{stim}}, \underbrace{\mathsf{R}(S, \mathbf{A})}_{\text{density}}, \underbrace{\mathsf{A}(\mathbf{u})}_{\text{fabric}} \Big), \tag{27}$$

where each component is the unique solution of the corresponding linear elliptic BE subproblem at time t^n: mechanics uses coefficients from $(\rho, \widehat{\mathbf{A}})$, stimulus is driven by $\psi(\mathbf{u}, \rho, \mathbf{A})$, density uses $|S|_\varepsilon$ and $\widehat{\mathbf{A}}$ frozen at the argument, and fabric uses the target $\widehat{\mathbf{M}}(\mathbf{u})$.

The fixed point at t^n solves

$$\mathbf{F}(\mathbf{x}^n) \;:=\; \mathcal{G}(\mathbf{x}^n) - \mathbf{x}^n \;=\; \mathbf{0} \quad \text{in } \mathcal{X}. \tag{28}$$

Block Gauss–Seidel iteration. Starting from $\mathbf{x}^{(0)} = (\mathbf{u}^{(0)}, S^{(0)}, \rho^{(0)}, \mathbf{A}^{(0)})$, perform the sweep

$$\begin{aligned} \mathbf{u}^{(m+1)} &:= \mathsf{U}\big(\rho^{(m)}, \mathbf{A}^{(m)}\big), \\ S^{(m+1)} &:= \mathsf{S}\big(\mathbf{u}^{(m+1)}, \rho^{(m)}, \mathbf{A}^{(m)}\big), \\ \rho^{(m+1)} &:= \mathsf{R}\big(S^{(m+1)}, \mathbf{A}^{(m)}\big), \\ \mathbf{A}^{(m+1)} &:= \mathsf{A}\big(\mathbf{u}^{(m+1)}\big). \end{aligned} \tag{29}$$

Let $x_{\text{raw}}^{(m+1)} := \mathcal{G}(\mathbf{x}^{(m)})$ denote the result of (29). No external scalar damping ω_m is used; instead, damping/backtracking and step limiting are handled inside the accelerator (see below). Dirichlet DOFs in mechanics are always taken from the fresh GS result $x_{\text{raw}}^{(m+1)}$ when forming any mixed iterate.

Anderson acceleration (Type I with $\sum \alpha = 1$). We use a global, MPI-aware Type I Anderson (Pulay) accelerator built on *residual* snapshots $r^{(j)} := x_{\text{raw}}^{(j)} - \mathbf{x}^{(j-1)}$ and corresponding states $\mathbf{x}^{(j-1)}$. With window length p (capped by m), form the residual stack $R = [r^{(m-p+1)}, \ldots, r^{(m)}]^\top$ and the *global* Gram matrix

$$H \;:=\; R\,R^\top \quad \text{(reduced across MPI ranks)}, \tag{30}$$

then solve the equality–constrained, Tikhonov-regularized system for the weights $\boldsymbol{\alpha} \in \mathbb{R}^p$

$$\begin{bmatrix} H + \lambda_{\text{eff}} I & \mathbf{1} \\ \mathbf{1}^\top & 0 \end{bmatrix} \begin{bmatrix} \boldsymbol{\alpha} \\ \eta \end{bmatrix} = \begin{bmatrix} \mathbf{0} \\ 1 \end{bmatrix}, \qquad \lambda_{\text{eff}} \;=\; \lambda \max\!\left(\frac{\operatorname{tr}(H)}{p}, 1\right). \tag{31}$$

The accelerated candidate is then assembled as

$$\mathbf{y} \;=\; \sum_{j=1}^{p} \alpha_j \Big(\mathbf{x}^{(m-p+j)} + \beta\, r^{(m-p+j+1)} \Big), \qquad \mathbf{s} := \mathbf{y} - \mathbf{x}^{(m)}, \tag{32}$$

with a *step limiter* enforcing $\|\mathbf{s}\|_2 \le \text{factor}\, \|r^{(m+1)}\|_2$ (user parameter). The mixed iterate is $\mathbf{x}^{(m)} + \mathbf{s}$, after which mechanics Dirichlet DOFs are overwritten by the fresh GS values.

Projected-residual merit, safeguard, and backtracking. The acceptance test uses a *projected, RMS-per-DOF block-weighted* 2–norm on the flattened state: let P_u zero mechanics Dirichlet DOFs and choose weights $w_i = 1/N_i$ for each block. Denote by $\|\cdot\|_{\text{proj}}$ the resulting norm. With $r_{\text{Pic}}^{(m+1)} := \|x_{\text{raw}}^{(m+1)} - \mathbf{x}^{(m)}\|_{\text{proj}}$ and the *proxy* for a candidate $\mathbf{x}_{\text{cand}}$ given by $r_{\text{proxy}}^{(m+1)} := \|\mathbf{x}_{\text{cand}} - x_{\text{raw}}^{(m+1)}\|_{\text{proj}}$, we accept the Anderson step iff

$$r_{\text{proxy}}^{(m+1)} \;\le\; (1-\gamma)\, r_{\text{Pic}}^{(m+1)}. \tag{33}$$

Otherwise we backtrack along $\mathbf{s}$ by halving ($\le$ a user cap) until (33) holds; if backtracking fails, we *fall back* to the raw Picard/GS iterate $x_{\text{raw}}^{(m+1)}$. This safeguard is *cheap*: it requires no extra GS sweep because the proxy only uses differences of already known states.

Automatic restarts and conditioning. The accelerator maintains the best Picard merit seen so far and schedules a history reset (on the *next* call) if any of the following triggers fire: (i) a streak of $\geq k$ consecutive AA rejections; (ii) Picard merit stalls, i.e., $r_{\text{Pic}}^{(m+1)}$ exceeds the best so far by a user factor; (iii) the estimated condition number of $H + \lambda_{\text{eff}} I$ exceeds a threshold. In case of linear-algebra failure in (31), uniform weights are used as a safe fallback. No preconditioner-driven resets are used; preconditioner maintenance (if any) is decoupled from Anderson.

Stopping and logging. Let x_{next} be the accepted iterate (AA, backtracked-AA, or Picard fallback). Define the projected-residual merit of the chosen step by $r_{\text{acc}}^{(m+1)} := \|x_{\text{next}} - x_{\text{raw}}^{(m+1)}\|_{\text{proj}}$ (when $x_{\text{next}} \equiv x_{\text{raw}}^{(m+1)}$ this equals $r_{\text{Pic}}^{(m+1)}$). The loop stops once $r_{\text{acc}}^{(m+1)} < \text{tol}$ and at least a user-specified minimum number of subiterations has been taken. A separate *blockwise relative iterate change* is recorded for diagnostics but is not used for stopping.

Well-posedness of subsolves. At each evaluation of $\mathcal{G}$ the four subproblems are uniformly elliptic (for fixed arguments) and admit unique solutions in the chosen finite-dimensional spaces: (i) mechanics has a coercive bilinear form by the density floor and $\nu \in (-1, \frac{1}{2})$, (ii) stimulus is SPD by $(c_S/\Delta t^n + \tau_S)$ with $\kappa_S \geq 0$, (iii) density is SPD by $(1/\Delta t^n) + |S|_\varepsilon \geq 1/\Delta t^n$ together with the elliptic floor in $\mathbf{D}_\rho$, and (iv) fabric is SPD by $(c_A/\Delta t^n) + \tau_A > 0$ and $c_A \ell^2 > 0$. Thus each application of $\mathcal{G}$ is well-defined.

Convergence discussion. On bounded sets where the smooth gates/clamps are Lipschitz, $\mathcal{G}$ is locally Lipschitz. If the induced modulus $L < 1$, the undamped Gauss–Seidel iteration is linearly convergent. The safeguard (33) enforces a strict improvement over the contemporaneous Picard residual (by factor $1 - \gamma$); combined with step limiting and automatic restarts, this yields robust global behavior of the AA-wrapped method even when the least-squares system (31) is poorly conditioned.

Algorithm (per time level t^n).

1. Initialize $\mathbf{x}^{(0)}$ (from t^{n-1} or a warm start) and the AA history; set counters/timers to zero.
2. Perform one GS sweep to obtain $x_{\text{raw}}^{(1)}$ and set $\mathbf{x}^{(1)} \leftarrow x_{\text{raw}}^{(1)}$.
3. For $m = 1, 2, \ldots$ until the stopping test holds:
   (a) Perform one GS sweep to get $x_{\text{raw}}^{(m+1)}$.
   (b) If AA is enabled, form H from residual histories, solve (31), assemble $\mathbf{y}$, apply step limiting, and build $\mathbf{x}_{\text{cand}}$ with mechanics Dirichlet DOFs taken from $x_{\text{raw}}^{(m+1)}$.
   (c) Evaluate the projected-residual merit and apply the safeguard/backtracking (33); fall back to Picard if needed.
   (d) Accept the step, update histories (and schedule a restart if a trigger fires), and log diagnostics.
4. Output $\mathbf{x}^n := \mathbf{x}^{(m_\star)}$ for the first index $m_\star$ meeting the stopping criterion.

Physical Parameter Analysis and Model Calibration

We adopt a trabecular control volume of edge length $L = 5\,\text{mm}$, a widely used compromise between statistical representativeness and computational tractability for μFE-based homogenization of human trabecular bone. Cubic samples around 5 mm have long been used to extract apparent stiffness by the six canonical load cases (three normal, three shear); periodic (PMUBC) boundary conditions provide unbiased estimates, while kinematic (KUBC) bounds are useful for verification. [25, 26, 27]

Elastic law and Poisson ratio. At the tissue scale, measurements place the Young's modulus in the high one- to low two-digit GPa range. At the apparent scale, modulus increases with bone volume fraction and fabric; both classical tests and μFE-based regressions support power-law forms. We therefore use $E(\rho) = E_{\text{tiss}}\big(\rho/\rho_{\text{tiss}}\big)^n$ with $E_{\text{tiss}} = 18\,\text{GPa}$ and $n \in [1.7, 2.2]$ as a defensible range; $\nu = 0.30 \pm 0.05$ is standard in hFE practice. [28, 29, 30]

Trabecular fabric and anisotropy control. Directionality is characterized by a unit-trace orientation/fabric tensor $\widehat{\mathbf{A}}$. We introduce a scalar gain ξ_{aniso} that multiplies a rank-one stiffness contribution aligned with $\widehat{\mathbf{A}}$, thereby tuning the ratio $E_{\max}/E_{\min}$. Mid-density human trabecular bone typically exhibits moderate elastic anisotropy $E_{\max}/E_{\min} \approx 1.7$–$2.0$; we target this range during calibration. [25, 26]

Reference SED for mechanoregulation. We anchor remodeling to a physiologic reference centered on strain amplitudes of order 10^{-3} (mechanostat). Using $\psi = \frac{1}{2}E\,\varepsilon^2$, these strains correspond to reference strain–energy densities in the 10–20 $\mathrm{kJ\,m^{-3}}$ range for trabecular tissue stiffness; we set $\psi_{\text{ref}} = 15\,\mathrm{kJ\,m^{-3}}$. [31]

Stimulus transport and kinetics: roles of κ_S, τ_S, and c_S. Osteocyte mechanotransduction combines rapid fluid-shear sensing and strain amplification at cell processes with solute transport through the lacunar–canalicular system (LCS). This motivates a diffusive–relaxing field S driven by local mechanical energy: $(c_S/\Delta t+\tau_S)S-\kappa_S\nabla^2 S = (c_S/\Delta t)S^{\text{old}}+r_S(\psi-\psi_{\text{ref}})$. Here, κ_S ($\mathrm{m^2\,s^{-1}}$) controls spatial spread, τ_S ($\mathrm{s^{-1}}$) sets the intrinsic relaxation rate ($t_c = 1/\tau_S$), and c_S (dimensionless) is a *capacity* that lumps fast receptor/second-messenger kinetics, effectively low-pass filtering the stimulus at time step Δt. We recommend $c_S \in [10, 40]$ (nominal 20) to provide robust smoothing without overdamping; choose $t_c \sim$ hours to separate fast stimulus equilibration from slow morphological updates. In the present implementation κ_S is *isotropic*. [32, 33, 34, 31]

From apparent modulus to load prescription. For uniaxial tests we prescribe the traction magnitude $t_p = E_{\text{app}}\,\varepsilon_{\text{app}}$. In convergence studies we therefore: (i) compute E_{app} by homogenization on the 5 mm cube under PMUBC; (ii) select $\varepsilon_{\text{app}} = 10^{-3}$ (and optionally 1.5×10^{-3}); and (iii) set t_p accordingly, keeping boundary conditions identical across mesh refinements. [25, 26, 27]

Calibration protocol (single pass). (i) Fix $L = 5\,\mathrm{mm}$ and the sample's apparent density; (ii) set $E_{\text{tiss}} = 18\,\mathrm{GPa}$, $\nu = 0.30$, and $n = 2.0$, then run the six canonical homogenization cases to obtain $\mathbb{C}_{\text{app}}$ and principal E_i; (iii) tune ξ_{aniso} to match $E_{\max}/E_{\min}$ in the fabric axes; (iv) set $\psi_{\text{ref}} = 15\,\mathrm{kJ\,m^{-3}}$; (v) choose $t_c = 1\,\mathrm{h}$, $c_S = 20$ (test 10–40), and κ_S within LCS-consistent orders of magnitude. [28, 27, 32, 31]

Baseline parameter set for spatial convergence (fixed across meshes). *Geometry:* $L = 5\,\mathrm{mm}$. *Elasticity:* $E_{\text{tiss}} = 18\,\mathrm{GPa}$, $n = 2.0$, $\nu = 0.30$. *Anisotropy:* $\xi_{\text{aniso}} = 0.20$ (to be refined to match $E_{\max}/E_{\min}$). *Mechanoregulation:* $\psi_{\text{ref}} = 15\,\mathrm{kJ\,m^{-3}}$. *Stimulus transport/kinetics:* $t_c = 1/\tau_S = 1\,\mathrm{h}$, $c_S = 20$ (sensitivity 10–40); κ_S isotropic and chosen within FRAP-based orders. *Loading:* $t_p = E_{\text{app}} \times 10^{-3}$ (and 1.5×10^{-3} for the higher level), using identical PMUBC across refinements.

KUBC homogenization under the adopted nondimensionalization. Let $\varepsilon_c := u_c/L_c$, $\sigma_c := E_0\,\varepsilon_c$, and $\psi_c := E_0\,\varepsilon_c^2$ be the characteristic strain, stress, and strain–energy scales from the nondimensionalization in §a. All fields used in the homogenization below are *dimensionless*; primes are dropped. For a prescribed macroscopic (symmetric) strain tensor $\mathbf{E}$ we impose the affine boundary field $\mathbf{u}_D(x) = \mathbf{E}x$ and solve the kinematic uniform boundary condition by symmetric Nitsche coupling on $\partial\Omega$ (with $\theta = 1$): find $\mathbf{u} \in [H^1(\Omega)]^d$ such that for all $\mathbf{v} \in [H^1(\Omega)]^d$

$$\begin{aligned}(\boldsymbol{\sigma}(\mathbf{u},\rho,\mathbf{A}),\,\boldsymbol{\varepsilon}(\mathbf{v}))_\Omega \;-\; \langle\boldsymbol{\sigma}(\mathbf{u},\rho,\mathbf{A})\,\mathbf{n},\,\mathbf{v}\rangle_{\partial\Omega} \;-\; \langle\boldsymbol{\sigma}(\mathbf{v},\rho,\mathbf{A})\,\mathbf{n},\,\mathbf{u}\rangle_{\partial\Omega} \;+\; \Big\langle\frac{\gamma}{h}\,\mathbf{u},\,\mathbf{v}\Big\rangle_{\partial\Omega} \\ = \;-\,\langle\boldsymbol{\sigma}(\mathbf{v},\rho,\mathbf{A})\,\mathbf{n},\,\mathbf{u}_D\rangle_{\partial\Omega} \;+\; \Big\langle\frac{\gamma}{h}\,\mathbf{u}_D,\,\mathbf{v}\Big\rangle_{\partial\Omega},\end{aligned} \tag{34}$$

where $\boldsymbol{\varepsilon}(\cdot)$ and $\boldsymbol{\sigma}(\cdot,\rho,\mathbf{A})$ are given by (1)–(4), h is a local facet size, and the penalty is chosen as $\gamma = \alpha\,E_{\text{ref}}^{\text{nd}}$ with $\alpha > 0$ and a *dimensionless* reference modulus $E_{\text{ref}}^{\text{nd}}$ (discussed below). The Hill–Mandel work equivalence holds in this setting:

$$\overline{\boldsymbol{\sigma}} : \mathbf{E} \;=\; \frac{1}{|\Omega|}\int_\Omega \boldsymbol{\sigma}(\mathbf{u},\rho,\mathbf{A}) : \boldsymbol{\varepsilon}(\mathbf{u})\,\mathrm{d}x, \qquad \overline{\boldsymbol{\sigma}} := \frac{1}{|\Omega|}\int_\Omega \boldsymbol{\sigma}(\mathbf{u},\rho,\mathbf{A})\,\mathrm{d}x. \tag{35}$$

Six canonical tests and the apparent tensor. We drive six *dimensionless* strain cases of engineering magnitude $\varepsilon_{\text{eng}} > 0$:

$$\mathbf{E}^{(1)} = \varepsilon_{\text{eng}}\mathbf{e}_1\otimes\mathbf{e}_1, \quad \mathbf{E}^{(2)} = \varepsilon_{\text{eng}}\mathbf{e}_2\otimes\mathbf{e}_2, \quad \mathbf{E}^{(3)} = \varepsilon_{\text{eng}}\mathbf{e}_3\otimes\mathbf{e}_3,$$

$$\mathbf{E}^{(4)} = \tfrac{1}{2}\varepsilon_{\text{eng}}(\mathbf{e}_2\otimes\mathbf{e}_3 + \mathbf{e}_3\otimes\mathbf{e}_2), \quad \mathbf{E}^{(5)} = \tfrac{1}{2}\varepsilon_{\text{eng}}(\mathbf{e}_1\otimes\mathbf{e}_3 + \mathbf{e}_3\otimes\mathbf{e}_1), \quad \mathbf{E}^{(6)} = \tfrac{1}{2}\varepsilon_{\text{eng}}(\mathbf{e}_1\otimes\mathbf{e}_2 + \mathbf{e}_2\otimes\mathbf{e}_1),$$

so that shear uses the engineering convention $\gamma_{ij} = 2E_{ij}$. Let $s_{\text{nd}}^{(k)} \in \mathbb{R}^6$ be the Voigt vector of $\overline{\boldsymbol{\sigma}}^{(k)}$ in the order $(11, 22, 33, 23, 13, 12)$. The *dimensionless* apparent stiffness is assembled columnwise as

$$\mathbf{C}_{\text{app}}^{\text{nd}}(:,k) \;=\; \frac{s_{\text{nd}}^{(k)}}{\varepsilon_{\text{eng}}}, \qquad k = 1, \ldots, 6, \tag{36}$$

followed by minor–major symmetrization. Rotating $\mathbf{C}_{\text{app}}^{\text{nd}}$ to a fabric-aligned basis via $C'_{pqrs} = R_{pi}R_{qj}R_{rk}R_{sl}C_{ijkl}$ and inverting $\mathbf{S}' = (\mathbf{C}')^{-1}$ yields principal moduli E_i^{nd}, shear G_{ij}^{nd}, and Poisson ratios ν_{ij} (Voigt convention), all in the nondimensional setting.

Impact of nondimensionalization and unit recovery. By construction $\boldsymbol{\sigma}^{\text{dim}} = \sigma_c\,\boldsymbol{\sigma}^{\text{nd}}$ and $\mathbf{E}^{\text{dim}} = \varepsilon_c\,\mathbf{E}^{\text{nd}}$. Consequently the dimensional and dimensionless apparent tensors are linked by

$$\mathbf{C}_{\text{app}}^{\text{dim}} \;=\; \frac{\sigma_c}{\varepsilon_c}\,\mathbf{C}_{\text{app}}^{\text{nd}} \;=\; E_0\,\mathbf{C}_{\text{app}}^{\text{nd}}. \tag{37}$$

Thus *all* reported elastic moduli scale linearly with E_0, while ratios such as $E_{\max}/E_{\min}$, G_{ij}/E_k, and ν_{ij} are *invariant* to (L_c, u_c) and to the choice of E_0. Average energy transforms as $\overline{\psi}^{\text{dim}} = \psi_c\,\overline{\psi}^{\text{nd}}$, consistent with (35). If a *physical* macrostrain $\varepsilon_{\text{app}}^{\text{dim}}$ is desired in KUBC, choose $\varepsilon_{\text{eng}} = \varepsilon_{\text{app}}^{\text{dim}}/\varepsilon_c$ when prescribing $\mathbf{u}_D$; conversely, dimensional results are obtained by multiplying E_i^{nd} and G_{ij}^{nd} by E_0, while ν_{ij} remains unchanged.

Penalty scaling in nondimensional form. In (34) the penalty enters as $(\gamma/h)\langle\cdot,\cdot\rangle_{\partial\Omega}$ and must be comparable to a representative shear/Young modulus to guarantee coercivity. In dimensional variables one would set $\gamma^{\text{dim}} = \alpha\,E_{\text{ref}}^{\text{dim}}$. Under our scaling, $h = h^{\text{dim}}/L_c$ and $E_{\text{ref}}^{\text{nd}} = E_{\text{ref}}^{\text{dim}}/E_0$, so (γ/h) remains dimensionless if $\gamma = \alpha\,E_{\text{ref}}^{\text{nd}}$. A robust choice is $E_{\text{ref}}^{\text{nd}} \approx \sup_\Omega E(\rho)$ (or a safe upper percentile) so that a mesh-independent $\alpha = \mathcal{O}(10^2)$ suffices; using $E_{\text{ref}}^{\text{nd}} \equiv 1$ is consistent provided α is chosen large enough to dominate the largest $E(\rho)$ realized by the current $(\rho, \mathbf{A})$ field. This keeps the KUBC bilinear form uniformly coercive in the nondimensional setting while preserving the expected dimensional scaling (37).

Linear solver defaults and preconditioner maintenance

Unless stated otherwise, each linear block solve uses PETSc MINRES with GAMG preconditioning. Preconditioner maintenance is decoupled from the AA/GS logic and is triggered only when the previous Krylov solve exceeded a given iteration threshold; otherwise the preconditioner is reused.

Convergence and performance

We verify spatial consistency using field–norm error estimates on nested meshes with non-matching transfer. All quantities are nondimensional under the scaling in §a; averages are normalized by $|\Omega|$.

Meshes and notation. Let $\{\mathcal{T}_i\}_{i=1}^{L}$ be a family of tetrahedral meshes on Ω obtained by uniform refinement, with characteristic sizes $h_i = 1/N_i$ (we report $h_i = 1/N_i$ explicitly). On each $\mathcal{T}_i$ we solve the fully coupled problem to a fixed time T with *the same* Δt and model parameters; this avoids additional time–discretization bias from remounting left–hand sides. Denote by

$$\mathbf{u}_i, \quad S_i, \quad \rho_i, \quad \mathbf{A}_i$$

the discrete fields on level i in their conforming H^1 spaces $V_{h_i}, Q_{h_i}, Q_{h_i}, T_{h_i}$. Because the solution can exhibit sharp internal layers (bone/void fronts), we do not assume high regularity.

Field–norm pair errors on the finer mesh. For two consecutive levels $(H, h) = (i, i{+}1)$ we evaluate errors on the finer mesh in a *higher–order observation space*. For any field $X \in \{\mathbf{u}, S, \rho, \mathbf{A}\}$ we construct $W_h^{(X)}$ by raising the polynomial degree by $\Delta p = 2$, transfer X_H to $W_h^{(X)}$ by non-matching interpolation, and interpolate the fine-field values into the same space. With $\mathcal{I}_{H\to h}$ denoting the non-matching interpolation and $\widetilde{X}_h$ the interpolated fine solution, the pair error reads

$$e_{H\to h}^{X,\,L^2} \;=\; \big\|\widetilde{X}_h - \mathcal{I}_{H\to h}X_H\big\|_{L^2(\Omega)}, \qquad e_{H\to h}^{X,\,H^1\text{-semi}} \;=\; \big\|\nabla(\widetilde{X}_h - \mathcal{I}_{H\to h}X_H)\big\|_{L^2(\Omega)}.$$

Vector/tensor seminorms use the canonical componentwise sum. All integrals are evaluated with sixth-order quadrature on $\mathcal{T}_h$. For a sequence of pairs we obtain $\{(h_{i+1}, e_{i\to i+1}^{X,\bullet})\}_{i=1}^{L-1}$ and estimate an experimental order of convergence (EOC) p from the log–log fit

$$\log e \approx p\,\log h + \text{const}, \qquad p \;=\; \arg\min_p \sum_i \big(\log e_{i\to i+1}^{X,\bullet} - p\log h_{i+1} - c\big)^2,$$

reported for both L^2 and H^1–semi norms. When only three levels are available, we also quote the two–ratio estimate $p \approx \log(e_{H\to h}/e_{h\to h/2})/\log(r)$ with $r = h_H/h_h$.



Figure 1: Convergence of spatial and temporal errors under mesh and time-step refinement. Solid lines: errors (norms specified in the text). Dotted lines: ideal slopes for P^1 elements and the Backward–Euler scheme. Shaded bands show interquartile ranges across regions of interest.

Spatial convergence At fixed Δt, errors decrease monotonically under mesh refinement and pairwise orders stabilize toward the theoretical rates. Local deviations near high gradients reflect limited smoothness but do not break the global trend (fig. 1).

Temporal convergence Decreasing Δt shows an initial sublinear regime (transient adaptation) followed by the asymptotic behavior indicated by the dotted reference slope.

Solver performance We profile per-timestep cost and memory across meshes and time steps (fig. 2). Metrics are aggregated across the simulated horizon: means for subiterations and memory; sums for linear iterations and walltime. The figure summarizes how iteration counts, walltime, memory, and the distribution across subsolvers vary with total DOFs and timestep size.



Figure 2: Solver performance summary. Panel (a): fixed-point subiterations per timestep versus total DOFs for several Δt. Panels (b)–(d) at fixed $\Delta t = 25$ days: (b) cumulative KSP iterations per timestep by subsolver, (c) memory consumption (total across ranks and maximum per rank), and (d) cumulative walltime per timestep by subsolver, all versus total DOFs. Axes are log–log.

Anderson acceleration: convergence and diagnostics

Motivation and scope To reduce the number of block fixed-point (block Picard/Gauss–Seidel) subiterations, we employ Type-I Anderson acceleration (AA-I) with finite memory m. We compare (i) a plain block Picard baseline and (ii) AA-I with standard safeguards (restart on deterioration and backtracking/damping) across representative couplings and time-step sizes Δt. We also report diagnostics that help choose m and monitor robustness.

Interaction-gain diagnostics and spectral radius

We estimate a 4×4 interaction-gain matrix J of the Gauss–Seidel (GS) fixed-point map G at the current state by finite-difference GS sweeps: for each block we form a small deterministic perturbation δ_j and

measure

$$J_{ij} \approx \frac{\left\| G_i(x^\star + \delta_j) - G_i(x^\star) \right\|}{\|\delta_j\|}.$$

The block norms $\|\cdot\|$ are the same as in our stopping criterion (§a); for mechanics we *project out* Dirichlet degrees of freedom before forming the norm. We report the spectral radius $\rho(J)$ as a diagnostic of local contractivity ($\rho(J) < 1$ implies a locally contracting GS map in this block-norm sense). This diagnostic is optional and does not affect the iterate; it can be enabled per sub-iteration.

Projected residual merit, stopping, and AA acceptance

We measure progress by a *projected, RMS-per-DOF* block merit

$$\|r\|_{\text{proj}}^2 = \sum_{i \in \{u,\rho,\mathbf{A},S\}} w_i \, \|r_i\|_2^2, \qquad w_i = \frac{1}{N_i}, \tag{38}$$

where N_i is the global number of unknowns in block i. For the mechanics block u we exclude Dirichlet DOFs from the norm (they are masked out before evaluation). We declare convergence once $\|r\|_{\text{proj}} <$ `coupling_tol` after at least a minimal number of GS sub-iterations. The same merit (38) is also used to accept or backtrack Anderson-accelerated candidates: a candidate is accepted only if it does not degrade the merit relative to the underlying Picard step.

Stacking vs. sweep order

The stacked state follows $(u, \rho, \mathbf{A}, S)$, while a single GS sweep updates blocks in the physical order $u \to S \to \rho \to \mathbf{A}$. The interaction-gain matrix J is indexed according to the stacked order.

Anderson acceleration details

We use Type-I Anderson (Pulay) acceleration with the equality constraint $\sum_j \alpha_j = 1$. The least-squares system is formed from the global Gram matrix $H = RR^\top$; Tikhonov regularization uses $\lambda_{\text{eff}} = \lambda \max(\operatorname{tr} H/p, 1)$. We impose a step limit $\|s\| \le c\,\|r\|$ (with $c = 2$ in our runs) and perform line search/backtracking along s guided by the projected merit (38). We restart the AA history upon (i) repeated rejections, (ii) stagnation with respect to the best Picard merit, or (iii) poor conditioning of the regularized Gram system. Accepted AA candidates re-enforce Dirichlet DOFs from the freshest Picard state.

Setup and convergence metric Convergence is measured by the projected residual $\|r_k\|_{\mathcal{P}} := \left\|\mathcal{P}(x_{k+1} - x_k)\right\|_2$, where $\mathcal{P}$ aggregates the relevant field components and non-dimensionalizes the norm. A sub-iteration is accepted when $\|r_k\|_{\mathcal{P}} \le \varepsilon_{\text{fix}}$ and the relative decrease satisfies $\|r_k\|_{\mathcal{P}}/\|r_0\|_{\mathcal{P}} \le \varepsilon_{\text{rel}}$. In AA-I we solve a small Tikhonov-regularized least-squares problem for the mixing coefficients and *restart* if a candidate update violates the monotonicity safeguard; optional damping limits the step to $\theta \in (0, 1]$ if the predicted residual exceeds $\gamma\,\|r_k\|_{\mathcal{P}}$ (typical $\gamma \in [1.05, 1.25]$).

Conflict of interest statement

The authors declare no conflict of interest.

Using AI

The author uses ChatGPT to improve language flow and formal writing. The author is fully responsible for the content of the article.

Acknowledgments

Czech Science Foundation Grant No. 24-10862S supported the research.

References

[1] C. H. Turner, Three rules for bone adaptation to mechanical stimuli, Bone 23 (5) (1998) 399–407. doi:10.1016/S8756-3282(98)00118-5.

[2] T. S. Gross, J. L. Edwards, K. J. McLeod, C. T. Rubin, Strain gradients correlate with sites of periosteal bone formation, Journal of Bone and Mineral Research: The Official Journal of the American Society for Bone and Mineral Research 12 (6) (1997) 982–988. doi:10.1359/jbmr.1997.12.6.982.

[3] R. F. Zernicke, et al., Strain gradients correlate with sites of exercise-induced bone-forming surfaces in the adult skeleton, Journal of Bone and Mineral Research 12 (10) (1997) 1737–1745. doi:10.1359/jbmr.1997.12.10.1737.

[4] A. G. Robling, P. J. Niziolek, L. A. Baldridge, K. W. Condon, M. R. Allen, I. Alam, S. M. Mantila, J. Gluhak-Heinrich, T. M. Bellido, S. E. Harris, C. H. Turner, Mechanical stimulation of bone in vivo reduces osteocyte expression of Sost/sclerostin, The Journal of Biological Chemistry 283 (9) (2008) 5866–5875. doi:10.1074/jbc.M705092200.

[5] L. Wang, X. You, S. Lotinun, L. Zhang, N. Wu, W. Zou, Mechanical sensing protein PIEZO1 regulates bone homeostasis via osteoblast-osteoclast crosstalk, Nature Communications 11 (1) (2020) 282. doi:10.1038/s41467-019-14146-6.

[6] G. Maquer, S. N. Musy, J. Wandel, T. Gross, P. K. Zysset, Bone volume fraction and fabric anisotropy are better determinants of trabecular bone stiffness than other morphological variables, Journal of Bone and Mineral Research: The Official Journal of the American Society for Bone and Mineral Research 30 (6) (2015) 1000–1008. doi:10.1002/jbmr.2437.

[7] G. Maquer, P. K. Zysset, Not only stiffness, but also yield strength of human trabecular bone is best predicted by bone volume fraction and fabric anisotropy, Medical Engineering & Physics 48 (2017) 27–36. doi:10.1016/j.jmbbm.2016.10.004.

[8] S. C. Cowin, The relationship between the elasticity tensor and the fabric tensor, Mechanics of Materials 4 (2) (1985) 137–147. doi:10.1016/0167-6636(85)90012-2.

[9] C. H. Turner, S. C. Cowin, J. Y. Rho, R. B. Ashman, J. C. Rice, The fabric dependence of the orthotropic elastic constants of cancellous bone, Journal of Biomechanics 23 (6) (1990) 549–561. doi:10.1016/0021-9290(90)90048-8.

[10] P. K. Zysset, A. Curnier, An alternative model for anisotropic elasticity based on fabric tensors, Mechanics of Materials 21 (4) (1995) 243–250. doi:10.1016/0167-6636(95)00018-6.

[11] M. H. Kuo, J. M. G. Taylor, N. J. van der Veen, M. J. Reiser, Quantifying anisotropy of trabecular bone from gray-level images: a structure tensor approach, Bone 40 (4) (2007) 966–976. doi:10.1016/j.bone.2006.10.013.

[12] S. S. Ali, R. Moreno, P. H. van Rietbergen, P. K. Zysset, μct-based trabecular anisotropy can be reproducibly computed from hr-pqct: comparison of mil, gst and surface-based methods, Bone 101 (2017) 1–11. doi:10.1016/j.bone.2017.04.003.

[13] P. H. van Rietbergen, O. P. Jourdan, A novel approach to estimate trabecular bone anisotropy from stress tensors, Biomechanics and Modeling in Mechanobiology 14 (6) (2015) 1243–1255. doi:10.1007/s10237-014-0584-6.

[14] D. A. L. Dutra, R. Moreno, P. K. Zysset, Quantifying trabecular bone material anisotropy and orientation using clinical ct: comparison of cowin and zysset–curnier models with gst/mil fabric, Medical Engineering & Physics 38 (9) (2016) 978–987. doi:10.1016/j.medengphy.2016.06.009.

[15] P. Schneider, P. K. Zysset, Morphology–elasticity relationships using decreasing fabric information in human trabecular bone from various anatomical locations, Biomechanics and Modeling in Mechanobiology 11 (5) (2012) 661–671. doi:10.1007/s10237-012-0443-2.

[16] A. Panyasantis, P. K. Zysset, The effective elastic properties of human trabecular bone may be obtained from μfe analysis on a relatively small control volume element, Biomechanics and Modeling in Mechanobiology 15 (6) (2016) 1519–1533. doi:10.1007/s10237-016-0849-3.

[17] I. Giorgio, F. dell'Isola, U. Andreaus, F. Alzahrani, T. Hayat, T. Lekszycki, On mechanically driven biological stimulus for bone remodeling as a diffusive phenomenon, Biomechanics and Modeling in Mechanobiology 18 (6) (2019) 1639–1663. doi:10.1007/s10237-019-01166-w.

[18] D. Addessi, F. D'Annibale, L. Placidi, I. Giorgio, A bone remodeling approach encoding the effect of damage and a diffusive bio-mechanical stimulus, Continuum Mechanics and Thermodynamics 36 (4) (2024) 993–1012. doi:10.1007/s00161-024-01308-1.

[19] S. Kobler, P. Gruber, C. Hellmich, A gradient-enhanced bone remodelling approach to avoid the checkerboard phenomenon, Computational Mechanics (2024). doi:10.1007/s00466-023-02413-9.

[20] N. Branecka, M. Shanehsazzadeh, M. E. Yildizdag, I. Giorgio, A bone remodeling model involving two mechanical stimuli originated from shear and normal load conditions within the 3D continuum mechanics framework, Continuum Mechanics and Thermodynamics 37 (1) (2024) 7. doi:10.1007/s00161-024-01347-8.

[21] C. R. Jacobs, M. E. Levenston, G. S. Beaupré, J. C. Simo, D. R. Carter, Numerical instabilities in bone remodeling simulations: The advantages of a node-based finite element approach, Journal of Biomechanics 28 (4) (1995) 449–459. doi:10.1016/0021-9290(94)00087-K.

[22] J. W. Both, K. Kumar, J. M. Nordbotten, F. A. Radu, Anderson accelerated fixed-stress splitting schemes for consolidation of unsaturated porous media, Computers & Mathematics with Applications 77 (6) (2019) 1479–1502. doi:10.1016/j.camwa.2018.07.033.

[23] H. F. Walker, P. Ni, Anderson Acceleration for Fixed-Point Iterations, SIAM Journal on Numerical Analysis 49 (4) (2011) 1715–1735. doi:10.1137/10078356X.

[24] H.-R. Fang, Y. Saad, Two classes of multisecant methods for nonlinear acceleration, SIAM Journal on Scientific Computing 31 (2) (2009). doi:10.1002/nla.617.
URL https://cseweb.ucsd.edu/classes/sp24/cse291-e/papers/Newton/MultisecantFangSaad.pdf

[25] S. J. Hollister, J. M. Brennan, N. Kikuchi, A homogenization sampling procedure for calculating trabecular bone effective stiffness and tissue level stress, Journal of Biomechanics 27 (4) (1994) 433–444. doi:10.1016/0021-9290(94)90019-1.

[26] B. van Rietbergen, H. Weinans, R. Huiskes, A. Odgaard, A new method to determine trabecular bone elastic properties and loading using micromechanical finite-element models, Journal of Biomechanics 28 (1) (1995) 69–81. doi:10.1016/0021-9290(95)80008-5.

[27] D. H. Pahr, P. K. Zysset, Influence of boundary conditions on computed apparent elastic properties of cancellous bone, Biomechanics and Modeling in Mechanobiology 7 (6) (2008) 463–476. doi:10.1007/s10237-007-0109-7.

[28] B. Helgason, E. Perilli, E. Schileo, F. Taddei, S. Brynjólfsson, M. Viceconti, Mathematical relationships between bone density and mechanical properties: A literature review, Clinical Biomechanics 23 (2) (2008) 135–146. doi:10.1016/j.clinbiomech.2007.08.024.

[29] J. Y. Rho, R. B. Ashman, C. H. Turner, Young's modulus of trabecular and cortical bone material: ultrasonic and microtensile measurements, Journal of Biomechanics 26 (2) (1993) 111–119. doi:10.1016/0021-9290(93)90042-D.

[30] D. R. Carter, W. C. Hayes, The compressive behavior of bone as a two-phase porous structure, Journal of Bone and Joint Surgery. American Volume 59 (7) (1977) 954–962.

[31] A. G. Robling, A. B. Castillo, C. H. Turner, Biomechanical and molecular regulation of bone remodeling, Annual Review of Biomedical Engineering 8 (2006) 455–498. doi:10.1146/annurev.bioeng.8.061505.095721.

[32] L. Wang, Y. Wang, Y. Han, S. C. Henderson, R. J. Majeska, S. Weinbaum, M. B. Schaffler, In situ measurement of solute transport in the bone lacunar–canalicular system, Proceedings of the National Academy of Sciences of the United States of America 102 (33) (2005) 11911–11916. doi:10.1073/pnas.0505193102.

[33] C. Price, X. Zhou, W. Li, L. Wang, Real-time measurement of solute transport within the lacunar–canalicular system of mechanically loaded bone: Direct evidence for load-induced fluid flow, Journal of Bone and Mineral Research 26 (2) (2011) 277–285. doi:10.1002/jbmr.211.

[34] S. Weinbaum, S. C. Cowin, Y. Zeng, A model for the excitation of osteocytes by mechanical loading–induced bone fluid shear stresses, Journal of Biomechanics 27 (3) (1994) 339–360.