# SOC Incident Report

**Summary:**
File: Bongo
Date Range of the file: March08, 2024-March16, 2024
Number of Events: 2073
Overall Severity: Low

The “Bongo” dataset shows multiple signs of suspicious HTTP activity, mostly matching automated scanning. The traffic appears in short bursts, usually coming from a single IP address. Most of the requests returned 404, with a few 200 responses.
This suggests opportunistic scanning to find accessible endpoints, rather than a targeted attack. Since the dataset is limited, these findings may not show the full picture.

Overview:

| # | Source IP | Date | Preliminary Classification | Severity |
|---|---|---|---|---|
| 1 | 143.198.224.235 | March 15, 2024 | PhpMyAdmin Discovery/PhpMyAdmin exposure | Low-Medium |
| 2 | 128.199.237.7 | March 10-11, 2024 | Repeated Configuration File Discovery | Medium |
| 3 | 172.208.51.79 | March 08, 2024 | WordPress Discovery | Low-Medium |
| 4 | 107.151.182.58 | March 12, 2024 | Multi-Technology Reconnaissance | Low |
| 5 | 80.94.92.60 | March 09-16, 2024 | RCE Attempt | Medium |
| 6 | 104.248.13.156 | March 09, 2024 and March 13-16, 2024 | Files Discovery Scans | Low |
| | 104.248.208.185 | | | |
| | 143.110.180.85 | | | |
| | 147.182.149.137 | | | |
| | 157.230.160.116 | | | |
| | 165.22.211.43 | | | |
| | 165.232.56.207 | | | |
| | 167.172.65.15 | | | |
| 7 | 38.75.137.222 | March 13-14, 2024 | WordPress Configuration Scan | Low |
| | 38.121.43.104 | | | |
| | 142.202.48.16 | | | |
| | 167.88.61.92 | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

**1) 143.198.224.235 – phpMyAdmin Discovery**

Facts:

| | |
|---|---|
| Date | March 15, 2024 19:52:15–19:52:26 (14 seconds) |
| Total Requests | 127 |
| HTTP Status | All requests returned 404 (Not Found) |
| User-Agent | Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/122.0.0.0 Safari/537.36 |

Observation:

- High number of requests (127) in a very short time window (14 seconds)
- Requests came in uneven bursts
- Multiple phpMyAdmin-related paths were tested (e.g. /phpmyadmin, /pma, /dbadmin, /sql)
- Some requests targeted specific versions (e.g. phpMyAdmin-5.2.1, phpMyAdmin-4.9.7)
- Repeated pattern: /index.php?lang=en
- All responses were 404
- User-Agent looks like a normal browser

Analysis:

- The request volume and variety of paths point to automated scanning using a wordlist
- The uneven bursts in a short time window confirm this is not human activity
- Since all responses were 404, no phpMyAdmin instance was found
- The User-Agent looks legitimate, but given the behavior, it was likely spoofed or used by a tool

This time chart visualization shows short bursts of activity within a limited time window, supporting the assumption of automated scanning:




Conclusion:

This activity looks like opportunistic scanning for exposed phpMyAdmin panels. No signs of successful access or further exploitation were found.

Severity:

Low to Medium (no successful access and no follow-up activity observed)

**2) 128.199.237.7 – Configuration File Discovery**

Facts:

| | |
|---|---|
| Date | March 10-11, 2024 |
| Total Requests | 27 (3 bursts)<br>• March 10, 2024 – 07:00<br>• March 10, 2024 – 11:00<br>• March 11, 2024 – 04:00 |
| HTTP Status | all requests returned 404 (Not Found) |
| User-Agent | Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:77.0) Gecko/20100101 Firefox/77.0 |

Observation:

- Repeated requests targeting FTP/SFTP config file paths
- Each burst contains the same set of 9 requests
- Includes hidden/dev paths (e.g. `/.ftpconfig`, `/.vscode/sftp.json`)
- Activity spread across multiple time intervals, not one continuous scan
- All 3 bursts follow the same sequence of endpoints

Analysis:

- The repeated pattern suggests automated scanning with retries
- The fixed set of paths points to a focused wordlist for config files
- Time gaps between bursts may indicate scheduled or periodic activity
- Compared to high-volume scans, this is lower noise but more persistent
- Since all responses were 404, no config files were exposed

The chart visualization shows 3 different bursts of low-volume activity across different time intervals, supporting the assessment of repeated automated probing.




Conclusion:

This looks like repeated, low-volume scanning for configuration files (likely targeting FTP/SFTP credentials). No successful access was observed, but the repeated attempts suggest persistence.

Severity:
Medium (low impact, but repeated behavior increases risk if it continues)

**3) 172.208.51.79 – WordPress Discovery**

Facts:

| | |
|---|---|
| Date | March 08, 2024 17:15:00 |
| Total Requests | 21 |
| HTTP Status | 18 → 404 (Not Found)<br>2 → 200 (OK) |
| User-Agent | Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/78.0.3904.108 Safari/537.36 |

Observation:
- Requests targeting common WordPress endpoints (/wlwmanifest.xml, /xmlrpc.php)
- Multiple directory variations tested (e.g. /blog, /wordpress, /site, /2018, /2019)
- All requests share the same timestamp, suggesting automated execution
- A few 200 responses among mostly 404s

Analysis:
- The pattern points to automated scanning for a WordPress installation
- The 200 responses were only for the root path (`/`), which just confirms the site is up
- No WordPress-specific endpoint returned 200, so WordPress presence is not confirmed
- Requests to `/xmlrpc.php` may indicate preparation for further attacks (e.g. brute force)
- The identical timestamp and consistent User-Agent support automated activity

Conclusion:
This looks like a basic scan for WordPress. The site responded on `/`, but no WordPress endpoints were accessible, so no exposure was confirmed.

Severity:
Low to Medium (No confirmed WordPress exposure, but endpoints commonly used in attacks were targeted)

Requested distribution of URI and status code. Only the root path / returned HTTP 200, while all WordPress-related endpoints returned HTTP 404




| uri | status | count |
|---|---|---|
| / | 200 | 3 |
| /2018/wp-includes/wlwmanifest.xml | 404 | 1 |
| /2019/wp-includes/wlwmanifest.xml | 404 | 1 |
| /blog/wp-includes/wlwmanifest.xml | 404 | 1 |
| /cms/wp-includes/wlwmanifest.xml | 404 | 1 |

**4) 107.151.182.58 – Multi-Technology Reconnaissance**

Facts:

| | |
|---|---|
| Date | March 12, 2024 08:39-08:42 (3 minutes) |
| Total Requests | 21 |
| HTTP Status | 17 → 404 (Not Found) |
| | 4 → 200 (OK) |
| Activity Distribution | 08:39 → 2 requests |
| | 08:40 → 6 requests |
| | 08:41 → 6 requests |
| 08:42 → 7 requests | |
| User-Agent | Mozilla/5.0 (Windows NT 10.0; WOW64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/66.0.3359.117 Safari/537.36 |
| | Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/60.0.3112.113 Safari/537.36 |

Observation:

- Requests target multiple technologies (e.g. /admin/, /cgi-bin/, /solr/, /sitecore/)
- Activity spread over several minutes in small batches
- Most endpoints were requested only once
- Repeated requests only for / and /favicon.ico
- 200 responses observed only for the root path (/)
- Two very similar User-Agent strings

Analysis:

- The pattern suggests a broad automated scan across different technologies
- Small batches over time may indicate basic rate limiting or staged execution
- The wide range of endpoints points to generic reconnaissance, not targeted activity
- 200 responses only on / confirm the server is reachable, but no specific service was identified
- Slight variations in User-Agent suggest automated tooling rather than real users

Conclusion:

This looks like a generic scan for common entry points across multiple technologies. No specific application or exposed endpoint was identified.

Severity:

Low (no meaningful responses and no signs of follow-up activity)

```
index=bongo sourcetype=access_combined clientip=107.151.182.58
| stats count by uri status
```

Time range: All time

✓ **21 events** (before 4/13/26 3:19:43.000 PM) No Event Sampling Job Smart Mode

Events Patterns **Statistics (17)** Visualization

Show: 50 Per Page Format Preview: On

| uri | status | count |
|---|---|---|
| / | 200 | 4 |
| /favicon.ico | 404 | 2 |
| /Telerik.Web.UI.WebResource.axd?type=rau | 404 | 1 |
| /admin/ | 404 | 1 |
| /api/session/properties | 404 | 1 |

Distribution of requests by URI and status code. Only the root path / returned HTTP 200, while all other endpoints returned HTTP 404

**5) 80.94.92.60 – Remote Command Execution Attempt**

<u>Facts:</u>

| | |
|---|---|
| Date | March 09-16, 2024 |
| Total Requests | 30 |
| HTTP Status | 13 → 404 (Not Found)<br>17 → 200 (OK) |
| Activity Distribution | March 09, 2024 → 5 requests<br>March 10, 2024 → 4 requests<br>March 11, 2024 → 1 request<br>March 12, 2024 → 4 requests<br>March 13, 2024 → 2 requests<br>March 14, 2024 → 5 requests<br>March 15, 2024 → 5 requests<br>March 16, 2024 → 4 requests |
| User-Agent | Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/42.0.2311.135 Safari/537.36 Edge/12.246<br>Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/90.0.4430.85 Safari/537.36 Edg/90.0.818.46 |

<u>Observation:</u>

- Activity spread over several days with a small number of requests per day
- Most requests target the root path (/) and return 200
- A few requests target /board.cgi and /cgi-bin/luci/
- Two requests contain URL-encoded payloads with command-like structure (wget, chmod, script execution)
- Payloads attempt to download and run a script from an external IP
- Both payload requests returned 404
- User-Agent strings are very similar

<u>Analysis:</u>

- The activity looks like automated, low-volume probing over time
- The encoded payloads match typical command injection attempts
- The use of wget + chmod + execution suggests an attempt to download and run a script on the target
- This pattern is commonly used in attacks against exposed web interfaces or network devices
- Even though the payload is clearly malicious, the requests returned 404, so the targeted endpoints were not accessible
- No signs of successful command execution were found
- Similar User-Agents and repeated behavior support automated activity

Conclusion:
This looks like an attempt to exploit a command injection vulnerability and execute remote code. The attempts were unsuccessful, as the targeted endpoints were not accessible.

Severity:
Medium (exploit attempt with malicious payload, but no successful execution)

Time Distribution of requests showing low-volume activity spread across multiple days, without a clear spike of pattern




**6) Multiple IP Addresses – File Discovery Scans**

Facts:

| | |
|---|---|
| Date | March 09, 2024 and March 13, 2024 |
| Total Requests | 80 |
| HTTP Status | 100% → 404 (Not Found) |
| Targeted URIs | /1.php, /info.php, /upl.php, /password.php, /systembc/password.php /bundle.js, /favicon.ico, /files/, /form.html, /geoip/ |

Observation:
- Requests came from multiple IPs (8 total), all targeting the same endpoints
- Mix of potentially sensitive PHP files and common web files
- All high-risk endpoints returned 404
- Most endpoints were requested the same number of times
- Pattern is consistent across all sources

Analysis:
- Identical requests from multiple IPs suggest automated scanning using a shared wordlist
- Focus on generic PHP filenames points to searching for exposed scripts or backdoors
- Requests to common files (e.g. /favicon.ico, /bundle.js) are likely just part of the scan template
- Since all responses were 404, none of the targeted files were accessible
- No additional useful signal from User-Agent

Conclusion:
This looks like automated scanning for exposed files and possible backdoors across multiple sources. No accessible endpoints were found.

Severity:
Low (no successful access and no follow-up activity observed)

Distribution of requests by URI and status code. All targeted endpoints returned HTTP 404, indicating no accessible files

```
1 index=bongo sourcetype=access_combined (uri="/1.php" OR uri="/bundle.js" OR uri="/favicon.ico" OR
    uri="/files/" OR uri="/form.html" OR uri="/geoip/" OR uri="/info.php" OR uri="/password.php"
    OR uri="/systembc/password.php" OR uri="/upl.php")
2 | stats count by uri status
```

Time range: All time

✓ 161 events (before 4/14/26 3:47:56.000 AM) No Event Sampling Job Smart Mode

Events Patterns Statistics (10) Visualization

Show: 50 Per Page Format Preview: On

| uri | status | count |
|---|---|---|
| /1.php | 404 | 8 |
| /bundle.js | 404 | 8 |
| /favicon.ico | 404 | 89 |
| /files/ | 404 | 8 |
| /form.html | 404 | 8 |
| /geoip/ | 404 | 8 |
| /info.php | 404 | 8 |
| /password.php | 404 | 8 |
| /systembc/password.php | 404 | 8 |
| /upl.php | 404 | 8 |

**7) Multiple IP Addresses – WordPress Configuration Scan**

Facts:

| | |
|---|---|
| Date | March 13-14, 2024 |
| Total Requests | 30 |
| HTTP Status | 100% → 404 (Not Found) |
| Targeted URLs | /wordpress/wp-admin/setup-config.php?step=1<br>/wp-admin/setup-config.php?step=1<br>/wp-content/plugins/royal-elementor-addons/assets/css/frontend.min.css<br>/wp-content/themes/bricks/style.css |

Observation:

- Four different IPs requested the same set of WordPress-related endpoints
- Targets include setup/config paths and plugin/theme files
- Each IP sent a different number of requests but followed the same pattern
- All responses were 404

Analysis:

- Requests to setup-config.php suggest scanning for unconfigured or exposed WordPress setups
- Plugin and theme file requests are likely used to confirm WordPress presence
- Identical URLs across multiple IPs point to a shared scanning template
- Differences in request volume are likely due to scanner settings, not coordination
- Since all responses were 404, no WordPress instance or files were accessible

Conclusion:
This looks like automated scanning for WordPress installations and misconfigurations. No accessible endpoints were found.

Severity:
Low (no successful access and no follow-up activity observed)

Requests grouped by URI, source IP, and status. All 4 IP addresses targeted the same endpoints, with varying request count, and all responses returned HTTP 404.

New Search

Save As ▾ Create Table View Close

```
1 index=bongo sourcetype=access_combined ((uri="/wordpress/wp-admin/setup-config.php?step=1" OR uri="
    /wp-admin/setup-config.php?step=1" OR uri="/wp-content/plugins/royal-elementor-addons/assets
    /css/frontend.min.css" OR uri="/wp-content/themes/bricks/style.css")
2 | stats count by uri clientip status
```

Time range: All time

✓ 32 events (before 4/14/26 6:38:00.000 AM) No Event Sampling ▾ Job ▾ Smart Mode ▾

Events Patterns Statistics (16) Visualization

Show: 50 Per Page ▾ Format ▾ Preview: On

| uri | clientip | status | count |
|---|---|---|---|
| /wordpress/wp-admin/setup-config.php?step=1 | 38.75.137.222 | 404 | 2 |
| /wp-admin/setup-config.php?step=1 | 38.75.137.222 | 404 | 2 |
| /wp-content/plugins/royal-elementor-addons/assets/css/frontend.min.css | 38.75.137.222 | 404 | 2 |
| /wp-content/themes/bricks/style.css | 38.75.137.222 | 404 | 2 |
| /wordpress/wp-admin/setup-config.php?step=1 | 38.121.43.104 | 404 | 1 |
| /wp-admin/setup-config.php?step=1 | 38.121.43.104 | 404 | 1 |
| /wp-content/plugins/royal-elementor-addons/assets/css/frontend.min.css | 38.121.43.104 | 404 | 1 |
| /wp-content/themes/bricks/style.css | 38.121.43.104 | 404 | 1 |
| /wordpress/wp-admin/setup-config.php?step=1 | 142.202.48.16 | 404 | 3 |
| /wp-admin/setup-config.php?step=1 | 142.202.48.16 | 404 | 3 |
| /wp-content/plugins/royal-elementor-addons/assets/css/frontend.min.css | 142.202.48.16 | 404 | 3 |
| /wp-content/themes/bricks/style.css | 142.202.48.16 | 404 | 3 |
| /wordpress/wp-admin/setup-config.php?step=1 | 167.88.61.92 | 404 | 2 |
| /wp-admin/setup-config.php?step=1 | 167.88.61.92 | 404 | 2 |
| /wp-content/plugins/royal-elementor-addons/assets/css/frontend.min.css | 167.88.61.92 | 404 | 2 |
| /wp-content/themes/bricks/style.css | 167.88.61.92 | 404 | 2 |

Overall Summary:

- The “Bongo” dataset shows multiple types of suspicious HTTP activity, mostly related to automated scanning. The observed behavior includes targeted scans (phpMyAdmin, WordPress, configuration files), broad multi-technology reconnaissance, and one case of an exploit attempt using a command injection payload.
- Most activity was low-volume and resulted in HTTP 404 responses, indicating that the targeted resources were not accessible.
- In one case, repeated requests over multiple days suggest persistent probing rather than a one-time scan. Another case included a clearly malicious payload attempting remote command execution.
- Overall, the activity appears to be opportunistic rather than targeted.

Overall Assessment:

- No evidence of successful compromise was found in the dataset.
- Most activity falls into common internet background noise (automated scanning), with one higher-risk case involving an exploit attempt that was unsuccessful.

Overall Severity:

**Low**
(No confirmed access to sensitive resources. Severity would increase if any of the targeted endpoints were accessible or if similar activity persisted over time.)

Recommendations:

- Continue monitoring for repeated or persistent activity from the same IPs
- Ensure unnecessary endpoints (e.g. admin panels, config files) are not exposed
- Consider restricting access to sensitive paths (e.g. /wp-admin, /phpmyadmin)
- Monitor for exploit patterns such as command injection attempts
- Keep systems and web applications up to date