

xl2roefact python library API Reference

- [xl2roefact python library API Reference](#)
- [app_cli](#)
 - [about](#)
 - [settings](#)
 - [xl2json](#)
 - [called_when_no_command](#)
 - [run](#)
- [chkisId](#)
- [chkxml](#)
- [config_settings](#)
 - [DEFAULT_SUPPLIER_COUNTRY](#)
- [ldxml](#)
- [libutils](#)
 - [complete_sexe_file](#)
 - [invoice_taxes_summary](#)
 - [dict_sum_by_key](#)
 - [isnumber](#)
 - [find_str_in_list](#)
- [rdinv](#)
 - [rdinv](#)
 - [get_excel_data_at_label](#)
 - [mk_kv_invoice_items_area](#)
 - [get_invoice_items_area](#)
- [wrxml](#)
- [__init__](#)
 - [__version__](#)
- [__main__](#)
- [__version__](#)
 - [normalized_version](#)

- [data](#)

app_cli

app_cli: the command line application for all xl2roefact functionalities.

Identification:

- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

about

```
@app_cli.command()  
def about():
```

provide a short application description.

settings

```
@app_cli.command()  
def settings(rules: Annotated[  
    bool,  
    typer.  
    Option("--rules", "-r", help="show settings recommended update rules"),  
] = False)
```

display application configuration parameters and settings that are subject to be changed by user.

Arguments:

- `rules` - show recommended rules to follow when change application configurable settings (available in both RO & EN languages). Defaults to `False`.

xl2json

```
@app_cli.command()
def xl2json(
    file_name: Annotated[
        str, typer.Argument(
            help="files to process (wildcards allowed)")
        ] = "*.xlsx",
    files_directory: Annotated[
        Path,
        typer.Option(
            "--files-directory",
            "-d",
            exists=False,
            file_okay=False,
            dir_okay=True,
            writable=True,
            readable=True,
            resolve_path=True,
            help=
                "directory to be used to look for Excel files (if default directory does not exists
                will consider current directory instead).",
        ),
    ] = "invoice_files/",
    verbose: Annotated[
        bool,
        typer.
            Option("--verbose", "-v", help="show detailed processing messages"),
    ] = False)
```

extract data from an Excel file (save data to JSON format file with the same name as original file but `.json` extension).

Arguments:

- `file_name` - files to process (wildcards allowed).
- `files_directory` - directory to be used to look for Excel files. Defaults to `invoice_files/`. NOTE: if default directory does not exists will consider current directory instead
- `verbose` - show detailed processing messages". Defaults to `False`.

called_when_no_command

```
@app_cli.callback(invoked_without_command=True)
def called_when_no_command(
    ctx: typer.Context,
    version: Annotated[
        bool,
        typer.Option("--version", help="show application version"),
    ] = False)
```

function called when no command is invoked and to provide only application version (for external users to test it!).

run

NOTE: for `run` "reason to be" as copy of `app_cli` see iss `0.1.22b 240216piu_a`

chkisld

chkisld: modul de verificare a starii de incarcare a unei facturi emise

Identification:

- code-name: `chkisld`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section `Componenta xl2roefact`
- INTRARI: fisier `f-XLSX` sau numarul / cheia / codul facturii
- IESIRI: valoarea echivalent `TRUE` daca factura a fost deja incarcata sau valoare echivalent `FALSE` daca factura nu a fost incarcata

chkxml

chkxml: modul de validare a facturii in sistemul ANAF E-Factura

Identification:

- code-name: `chkxml`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section `Componenta xl2roefact`
- INTRARI: fisier `f-XML`
- IESIRI: raport cu eventualele erori de validare

config_settings

Configuration and setting parameters.

Regulile recomandate se gasesc in documentul [doc/README_app_config_rules.md](#)

Public objects:

`rules_content`: contains the rules text (rendered)

- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

DEFAULT_SUPPLIER_COUNTRY

NOTE: "pattern-uri" (sabioane) de identificare si regasire a datelor folositi de

__ comanda `x12json` reprezentind functionalitatea de extragere a datelor din Excel si exportul lor in formatul JSON (modulul ``rdinv``)__

ldxml

ldxml: modul de incarcare a facturii in sistemul ANAF E-Factura

Identification:

- code-name: `ldxml`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section Componenta `x12roefact`
- INTRARI: fisier `f-XML`
- IESIRI: raport cu validarea si identificatorul incarcarii

libutils

general utilities library for all `x12roefact` components and modules.

Identification:

- code-name: `libutils`
- copyright: (c) 2023, 2024 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Components:

- `complete_sexe_file()` -> `bool`: Rename and move resulted exe file (called from `build_sexe` script)
- `dict_sum_by_key(dict, str)` -> `float`: Sum a dictionary for a given key at all depth levels
- `find_str_in_list(list, list)` -> `int`: Search more strings (ie, a list) in list of strings
- `invoice_taxes_summary(list[dict])` -> `dict`: Calculates invoice taxes summary as required by ROefact requirements
- `isnumber(str)` -> `bool`: Test a string if it could be used as number (int or float)

complete_sexe_file

```
def complete_sexe_file(drop_source: bool = True) -> bool
```

Rename and move resulted exe file. This function is dedicated only to development phase, so various objects are hard coded.

- Specs: file to process `../dist_sexe/xl2roefact_to_update_name.exe` --> `../dist/xl2roefact-version-win64.exe`
- NOTE: all function code suppose that current directory is root of `xl2roefact`, ie where is located `pyproject.toml` of package

Arguments:

- `drop_source` - indicate to delete source file after copying, ie make a "move" operation, otherwise make a copy keeping the source file. Default behaviour is to delete source.

Returns:

- `bool` - True if file was found, renamed and moved with no error

invoice_taxes_summary

```
def invoice_taxes_summary(invoice_lines: list[dict]) -> list
```

Calculates invoice taxes summary as required by ROefact requirements.

Arguments:

- `invoice_lines` - section with item lines from 'big' invoice dictionary

Returns:

- `list` - usable for "cac_TaxSubtotal" key

dict_sum_by_key

```
def dict_sum_by_key(search_dict: dict | list[dict], sum_key: str) -> float
```

Sum all dictionary (or list of dictionaries) items, at all levels, for a given key.

Arguments:

- `search_dict` - dictionary to be searched for
- `sum_key` - key to be searched

Returns:

- `float` - with required sum

isnumber

```
def isnumber(a_string: str) -> bool
```

test if a string is valid as any kind of number.

Arguments:

- `a_string` - input string.

Returns:

- `True` - if input string is valid as any kind of number, otherwise `False`.

find_str_in_list

```
def find_str_in_list(list_of_str_to_find: list, list_to_search: list) -> int
```

find a substring from `list_of_str_to_find` in elements of `list_to_search`.

Arguments:

- `list_of_str_to_find` - list of strings to search for.
- `list_to_search` - list where to search for substrings.

Returns:

- `index` - the index of list item which contains `str_to_find` (first found) or `None` if not found.

rdinv

rdinv: modul de procesare a fisierului Excel ce contine factura si colectare a datelor aferente.

Formatul acceptat fisier Excel este `XLSX`.

Identification:

- code-name: `rdinv`

- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Specifications:

- document cerinte initiale: 110-SRE-api_to_roefact_requirements.md section Componenta xl2roefact
- INTRARI: fisier format XLSX ce contine factura emisa (cod: f-XLSX)
- IESIRI: fisier format JSON imagine a datelor facturii (cod: f-JSON)

rdinv

```
def rdinv(file_to_process: str,
          invoice_worksheet_name: str = None,
          *,
          debug_info: bool = False) -> dict
```

read Excel file for invoice data.

Produce a dictionary structure + JSON file with all data regarding read invoice: canonical KV data, meta data, map to convert to XML and original Excel data.

Arguments:

- `file_to_process` - the invoice file (exact file with path).
- `invoice_worksheet_name` - the worksheet containing invoice, optional, defaults to first found worksheet.
- `debug_info` - key only, show debugging information, default `False`.

Returns:

- `dict` - the invoice extracted information from Excel file as `dict(Invoice: dict, meta_info: dict, excel_original_data: dict)` TODO subject of documentation update.

NOTE ref important variables: * `db: pylightxl object`: EXCEL object with invoice (as a whole) * `ws: pylightxl object`: WORKSHEET object with invoice

get_excel_data_at_label

```
def get_excel_data_at_label(pattern_to_search_for: list[str],
                             worksheet: xl.Database.ws,
                             area_to_scan: list[list[int]] = None,
                             targeted_type: Callable = str,
                             down_search_try: bool = True) -> dict
```

get "one key Excel values", like invoice number or invoice issue date.

Arguments:

- `pattern_to_search_for` - for example for inv number, will pass the `PATTERN_FOR_INVOICE_NUMBER_LABEL`.
- `worksheet` - the worksheet containing invoice (as object of `pyxl` library).

- `area_to_scan` - area of cells to be searched, default whole worksheet.
- `targeted_type` - what type expect (will try to convert to, if cannot will return str), default `str`.
- `down_search_try` - establish if DOWN search method is tried, default `True`.

Returns:

`None` if not found OR `dictionary` containing: * `"value": int | float | str` - the value found converted to requested `targeted_type` if possible or `str` otherwise; if "out of space" then returns `None` * `"location": (row, col)` - adrees of cell where found value

Notes:

- normal scan order is 1.RIGHT, 2.DOWN (if allowed), 3.IN-LABEL only in given area and pattern.

mk_kv_invoice_items_area

```
def mk_kv_invoice_items_area(invoice_items_area_xl_format) -> dict
```

transform `invoice_items_area` in "canonical JSON format" (as kv pairs).

Arguments:

- `invoice_items_area_xl_format` - invoice items area in Excel format (ie, DataFrame with row, col, data).

Returns:

- `invoice_items_area_xl_format` - dictionary with invoice items in Excel format (ie, rows, columns).

Notes:

- for ROefact XML model (& plan) see `invoice_files/__model_test_factura_generat_anaf.xml`.

get_invoice_items_area

```
def get_invoice_items_area(worksheet, invoice_items_area_marker,
                           wks_name) -> dict
```

get invoice for `invoice_items_area`, process it and return its Excel format.

Process steps & notes: * find invoice items subtable. * clean invoice items subtable. * extract relevenat data. *

NOTE: all Excel cell addresses are in `(row, col)` format (ie, Not Excel format like "A:26, C:42, ...")

Arguments:

- `worksheet` - the worksheet containing invoice (as object of `pyxllight` library).
- `invoice_items_area_marker` - string with exact marker of invoice items table.
- `NOTE` - this is the UPPER-LEFT corner and is determined before calling this procedure.
- `wks_name` - the wroksheet name (string) of the `worksheet` object.

Returns:

- `invoice_items_area` - dictionary with invoice items in Excel format (ie, rows, columns).

wrxml

wrxml: modul de generare a fisierului format XML

Identification:

- code-name: `wrxml`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section `Componenta xl2roefact`
- INTRARI: fisier `f-JSON`
- IESIRI: fisier format XML conform cerintelor si sistemului ANAF E-Factura (cod: `f-XML`)

__init__

__version__

default conversion takes place over xl2roefact actual version

__main__

xl2roefact.main: Python package standard file to assure run as `python -m xl2roefact`.

Identification:

- code-name: `__main__`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Deployments:

- Windows: MSI installer with EXE application.
- Linux: `xl2roefact` executable shell as wrapper for `xl2roefact.py`.

Specifications:

- command general format: `python -m xl2roefact [OPTIONS] COMMAND [ARGS]...`

- help: `python -m xl2roefact --help.`

__version__

```
xl2roefact version info.
```

##### #####	##### #####
# # # # #	# # ## #
## ## # #	### ### # ## #
## ## # #	# # # ## #
## ## # #	# # # ## #
# ## # # #####	# # # ## #
# ## # # #	# # ## #
##### #####	#### #####

#####	#####	#####	#####	#####
# # # #	# # # #	# # # #	# # # #	# # # #
# ## ## #####	# ##### # #####	# ## # # #	# # # #	### ##
# ## # # # # #	# # # # #	# # # #	#####	# #
# ##### # ## # #####	# ##### # #####	# ## # #	#####	# #
# # # # # #	# ##### # #	# ## # #	# #	# #
# # # ## #	# # # #	# ## # ##	# #	# #
#### # #####	##### ##	#####	#####	####

normalized_version

```
def normalized_version(raw_version: str = __version__) -> str
```

transform version string in canonical form.

```
Usage:- import xl2roefact - xl2roefact.__version__.normalized_version()
```

Arguments:

`raw_version` (str): a raw version string. Defaults to package current version string.

Returns:

str: canonical version string

data