

# xl2roefact python library API Reference

- [xl2roefact python library API Reference](#)
- [app\\_cli](#)
  - [about](#)
  - [settings](#)
  - [xl2json](#)
  - [called\\_when\\_no\\_command](#)
  - [run](#)
- [chkisId](#)
- [chkxml](#)
- [config\\_settings](#)
  - [DEFAULT\\_SUPPLIER\\_COUNTRY](#)
  - [python\\_object](#)
- [ldxml](#)
- [libutils](#)
  - [complete\\_sexe\\_file](#)
  - [invoice\\_taxes\\_summary](#)
  - [dict\\_sum\\_by\\_key](#)
  - [isnumber](#)
  - [find\\_str\\_in\\_list](#)
- [rdinv](#)
  - [rdinv](#)
  - [get\\_excel\\_data\\_at\\_label](#)
  - [mk\\_kv\\_invoice\\_items\\_area](#)
  - [get\\_invoice\\_items\\_area](#)
  - [get\\_partner\\_data](#)
- [wrxml](#)
- [\\_\\_init\\_\\_](#)
  - [\\_\\_version\\_\\_](#)
- [\\_\\_main\\_\\_](#)

- `__version__`
  - `normalized_version`
- `data`

## app\_cli

`app_cli`: the command line application for all xl2roefact functionalities.

Identification:

- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

### about

```
@app_cli.command()  
def about():
```

provide a short application description.

### settings

```
@app_cli.command()  
def settings(rules: Annotated[  
    bool,  
    typer.  
    Option("--rules", "-r", help="show settings recommended update rules"),  
] = False)
```

display application configuration parameters and settings that are subject to be changed by user.

### Arguments:

- `rules` - show recommended rules to follow when change application configurable settings (available in both RO & EN languages). Defaults to `False`.

## xl2json

```

@app_cli.command()
def xl2json(
    file_name: Annotated[
        str, typer.Argument(
            help="files to process (wildcards allowed)")] = "*.xlsx",
    files_directory: Annotated[
        Path,
        typer.Option(
            "--files-directory",
            "-d",
            exists=False,
            file_okay=False,
            dir_okay=True,
            writable=True,
            readable=True,
            resolve_path=True,
            help=
                "directory to be used to look for Excel files (if default directory does not exists
will consider current directory instead).",
        ),
    ] = "invoice_files/",
    verbose: Annotated[
        bool,
        typer.
            Option("--verbose", "-v", help="show detailed processing messages"),
    ] = False)

```

extract data from an Excel file (save data to JSON format file with the same name as original file but `.json` extension).

### Arguments:

- `file_name` - files to process (wildcards allowed).
- `files_directory` - directory to be used to look for Excel files. Defaults to `invoice_files/`. NOTE: if default directory does not exists will consider current directory instead
- `verbose` - show detailed processing messages". Defaults to `False`.

### called\_when\_no\_command

```

@app_cli.callback(invoked_without_command=True)
def called_when_no_command(
    ctx: typer.Context,
    version: Annotated[
        bool,
        typer.Option("--version", help="show application version"),
    ] = False)

```

function called when no command is invoked and to provide only application version (for external users to test it!).

## run

NOTE: for `run` "reason to be" as copy of `app_cli` see iss `0.1.22b 240216piu_a`

## chkisld

chkisld: modul de verificare a starii de incarcare a unei facturi emise

### Identification:

- code-name: `chkisld`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

### Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section `Componenta xl2roefact`
- INTRARI: fisier `f-XLSX` sau numarul / cheia / codul facturii
- IESIRI: valoarea echivalent `TRUE` daca factura a fost deja incarcata sau valoare echivalent `FALSE` daca factura nu a fost incarcata

## chkxml

chkxml: modul de validare a facturii in sistemul ANAF E-Factura

### Identification:

- code-name: `chkxml`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

### Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section `Componenta xl2roefact`
- INTRARI: fisier `f-XML`
- IESIRI: raport cu eventualele erori de validare

## config\_settings

Configuration and setting parameters.

Regulile recomandate se gasesc in documentul (recommended rules are in document)

[doc/README\\_app\\_config\\_rules.md](#)

Public objects:

``rules_content``: contains the rules text (rendered)

- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

**DEFAULT\_SUPPLIER\_COUNTRY**

**NOTE: "pattern-uri" (sabioane) de identificare si regasire a datelor folositi de**

\_\_ comanda `x12json` reprezentind functionalitatea de extragere a datelor din Excel si exportul lor in formatul JSON (modulul ``rdinv``)\_\_

**python\_object**

suppose no info found

`ldxml`

ldxml: modul de incarcare a facturii in sistemul ANAF E-Factura

Identification:

- code-name: `ldxml`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section Componenta `x12roefact`
- INTRARI: fisier `f-XML`
- IESIRI: raport cu validarea si identificatorul incarcarii

`libutils`

general utilities library for all `x12roefact` components and modules.

Identification:

- code-name: `libutils`
- copyright: (c) 2023, 2024 RENWare Software Systems

- **author:** Petre Iordanescu (petre.iordanescu@gmail.com)

#### Components:

- `complete_sexe_file()` -> `bool`: Rename and move resulted exe file (called from `build_sexe` script)
- `dict_sum_by_key(dict, str)` -> `float`: Sum a dictionary for a given key at all depth levels
- `find_str_in_list(list, list)` -> `int`: Search more strings (ie, a list) in list of strings
- `invoice_taxes_summary(list[dict])` -> `dict`: Calculates invoice taxes summary as required by ROefact requirements
- `isnumber(str)` -> `bool`: Test a string if it could be used as number (int or float)

#### **complete\_sexe\_file**

```
def complete_sexe_file(drop_source: bool = True) -> bool
```

Rename and move resulted exe file. This function is dedicated only to development phase, so various objects are hard coded.

- **Specs:** file to process `../dist_sexe/xl2roefact_to_update_name.exe` --> `../dist/xl2roefact-version-win64.exe`
- **NOTE:** all function code suppose that current directory is root of `xl2roefact`, ie where is located `pyproject.toml` of package

#### **Arguments:**

- `drop_source` - indicate to delete source file after copying, ie make a "move" operation, otherwise make a copy keeping the source file. Default behaviour is to delete source.

#### **Returns:**

- `bool` - True if file was found, renamed and moved with no error

#### **invoice\_taxes\_summary**

```
def invoice_taxes_summary(invoice_lines: list[dict]) -> list
```

Calculates invoice taxes summary as required by ROefact requirements.

#### **Arguments:**

- `invoice_lines` - section with item lines from 'big' invoice dictionary

#### **Returns:**

- `list` - usable for "cac\_TaxSubtotal" key

### dict\_sum\_by\_key

```
def dict_sum_by_key(search_dict: dict | list[dict], sum_key: str) -> float
```

Sum all dictionary (or list of dictionaries) items, at all levels, for a given key.

#### Arguments:

- `search_dict` - dictionary to be searched for
- `sum_key` - key to be searched

#### Returns:

- `float` - with required sum

### isnumber

```
def isnumber(a_string: str) -> bool
```

test if a string is valid as any kind of number.

#### Arguments:

- `a_string` - input string.

#### Returns:

- `True` - if input string is valid as any kind of number, otherwise `False`.

### find\_str\_in\_list

```
def find_str_in_list(list_of_str_to_find: list, list_to_search: list) -> int
```

find a substring from `list_of_str_to_find` in elements of `list_to_search`.

#### Arguments:

- `list_of_str_to_find` - list of strings to search for.
- `list_to_search` - list where to search for substrings.

#### Returns:

- `index` - the index of list item which contains `str_to_find` (first found) or `None` if not found.

## rdinv

rdinv: modul de procesare a fisierului Excel ce contine factura si colectare a datelor aferente.

Formatul acceptat fisier Excel este `XLSX`.

**Identification:**

- code-name: `rdinv`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

**Specifications:**

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section `Componenta xl2roefact`
- INTRARI: fisier format XLSX ce contine factura emisa (cod: `f-XLSX`)
- IESIRI: fisier format JSON imagine a datelor facturii (cod: `f-JSON`)

**rdinv**

```
def rdinv(file_to_process: str,
          invoice_worksheet_name: str = None,
          *,
          debug_info: bool = False) -> dict
```

read Excel file for invoice data.

Produce a dictionary structure + JSON file with all data regarding read invoice: canonical KV data, meta data, map to convert to XML and original Excel data.

**Arguments:**

- `file_to_process` - the invoice file (exact file with path).
- `invoice_worksheet_name` - the worksheet containing invoice, optional, defaults to first found worksheet.
- `debug_info` - key only, show debugging information, default `False`.

**Returns:**

- `dict` - the invoice extracted information from Excel file as `dict(Invoice: dict, meta_info: dict, excel_original_data: dict)`

NOTE ref important variables: \* `db: pylightxl object`: EXCEL object with invoice (as a whole) \* `ws: pylightxl object`: WORKSHEET object with invoice

**get\_excel\_data\_at\_label**

```
def get_excel_data_at_label(pattern_to_search_for: list[str],
                             worksheet: xl.Database.ws,
                             area_to_scan: list[list[int]] = None,
                             targeted_type: Callable = str,
                             down_search_try: bool = True) -> dict
```

get "one key Excel values", like invoice number or invoice issue date.



**Arguments:**

- `pattern_to_search_for` - for example for inv number, will pass the `PATTERN_FOR_INVOICE_NUMBER_LABEL`.
- `worksheet` - the worksheet containing invoice (as object of `pyxllight` library).
- `area_to_scan` - area of cells to be searched, default whole worksheet.
- `targeted_type` - what type expect (will try to convert to, if cannot will return str), default `str`.
- `down_search_try` - establish if DOWN search method is tried, default `True`.

**Returns:**

`None` if not found OR dictionary containing: \* `"value": int | float | str` - the value found converted to requested `targeted_type` if possible or `str` otherwise; if "out of space" then returns `None` \* `"location": (row, col)` - adrees of cell where found value

**Notes:**

- normal scan order is 1.RIGHT, 2.DOWN (if allowed), 3.IN-LABEL only in given area and pattern.

**mk\_kv\_invoice\_items\_area**

```
def mk_kv_invoice_items_area(invoice_items_area_xl_format) -> dict
```

transform `invoice_items_area` in "canonical JSON format" (as kv pairs).

**Arguments:**

- `invoice_items_area_xl_format` - invoice items area in Excel format (ie, DataFrame with row, col, data).

**Returns:**

- `invoice_items_area_xl_format` - dictionary with invoice items in Excel format (ie, rows, columns).

**Notes:**

- for ROefact XML model (& plan) see `invoice_files/_model_test_factura_generat_anaf.xml`.

**get\_invoice\_items\_area**

```
def get_invoice_items_area(worksheet, invoice_items_area_marker,
                           wks_name) -> dict
```

get invoice for `invoice_items_area`, process it and return its Excel format.

Process steps & notes: \* find invoice items subtable. \* clean invoice items subtable. \* extract relevenat data. \*

NOTE: all Excel cell addresses are in `(row, col)` format (ie, Not Excel format like "A:26, C:42, ...")

**Arguments:**

- `worksheet` - the worksheet containing invoice (as object of `pyxllight` library).

- `invoice_items_area_marker` - string with exact marker of invoice items table.
- `NOTE` - this is the UPPER-LEFT corner and is determined before calling this procedure.
- `wks_name` - the worksheet name (string) of the `worksheet` object.

#### Returns:

- `invoice_items_area` - dictionary with invoice items in Excel format (ie, rows, columns).

#### get\_partner\_data

```
def get_partner_data(partner_type: str, *, wks,
                    param_invoice_header_area: dict) -> None
```

Get invoice partner data from Excel.

For developers note: function works by generating side effects and must be located in `rdinv.py`

#### Arguments:

- `partner_type` - one of "CUSTOMER", "SUPPLIER" or "OWNER" to specify for what kind of partner get data. The value "OWNER" is designed to get data from an outside database / file (master data)
- `wks` - current work-on `pylightxl Worksheet` object
- `param_invoice_header_area` - outside `param_invoice_header_area` as used and needed in `rdinv()`. This function will write back in this variable

#### Returns:

- `None` - all data is produced directly in parameters as side effect

## wrxml

wrxml: modul de generare a fisierului format XML

#### Identification:

- code-name: `wrxml`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

#### Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section `Componenta xl2roefact`
- INTRARI: fisier `f-JSON`
- IESIRI: fisier format XML conform cerintelor si sistemului ANAF E-Factura (cod: `f-XML`)

\_\_init\_\_

\_\_version\_\_

default conversion takes place over xl2roefact actual version

\_\_main\_\_

**xl2roefact.main:** Python package standard file to assure run as `python -m xl2roefact`.

Identification:

- code-name: `__main__`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Deployments:

- Windows: MSI installer with EXE application.
- Linux: `xl2roefact` executable shell as wrapper for `xl2roefact.py`.

Specifications:

- command general format: `python -m xl2roefact [OPTIONS] COMMAND [ARGS]...`
- help: `python -m xl2roefact --help`.

\_\_version\_\_

xl2roefact version info.

[illegible]

```
def normalized_version(raw_version: str = __version__) -> str
```

```
Usage:- import xl2roefact - xl2roefact.__version__.normalized_version()
```

`raw_version` (str): a raw version string. Defaults to package current version string.

**str:** canonical version string

Last update: March 30, 2024