

# Table of Contents

- [app\\_cli](#)
- [about](#)
- [settings](#)
- [xl2json](#)
- [called\\_when\\_no\\_command](#)
- [chkisld](#)
- [chkxml](#)
- [config\\_settings](#)
- [DEFAULT\\_SUPPLIER\\_COUNTRY](#)
- [ldxml](#)
- [libutils](#)
- [isnumber](#)
- [find\\_str\\_in\\_list](#)
- [rdinv](#)
- [rdinv](#)
- [get\\_excel\\_data\\_at\\_label](#)
- [mk\\_kv\\_invoice\\_items\\_area](#)
- [get\\_invoice\\_items\\_area](#)
- [wrxml](#)
- [\\_\\_init\\_\\_](#)
- [\\_\\_main\\_\\_](#)
- [\\_\\_version\\_\\_](#)

## app\_cli

app\_cli: the command line application for all xl2roefact functionalities.

Identification:

- code-name: `xl2roefact`
- copyright: (c) 2023 RENWare Software Systems

- author: Petre Iordanescu (petre.iordanescu@gmail.com)

#### Deployments:

- Windows: MSI installer with EXE application.
- Linux: `x12roefact` executable shell as wrapper for `x12roefact.py`.

#### Specifications:

- command general format: `x12roefact [file(s)-to-convert] COMMAND [OPTIONS]`.
- help: `x12roefact [COMMAND] --help`.

#### about

```
@app_cli.command()  
def about():
```

provide a short application description.

#### settings

```
@app_cli.command()  
def settings(rules: Annotated[  
    bool,  
    typer.  
    Option("--rules", "-r", help="show settings recommended update rules"),  
] = False)
```

display application configuration parameters and settings that are subject to be changed by user.

#### Arguments:

- `rules` - show recommended rules to follow when change application configurable settings (available in both RO & EN languages). Defaults to `False`.

## xl2json

```
@app_cli.command()
def xl2json(
    file_name: Annotated[
        str, typer.Argument(
            help="files to process (wildcards allowed)"] = "*.xlsx",
    files_directory: Annotated[
        Path,
        typer.Option(
            "--files-directory",
            "-d",
            exists=False,
            file_okay=False,
            dir_okay=True,
            writable=True,
            readable=True,
            resolve_path=True,
            help=
                "directory to be used to look for Excel files (if default directory does not exists
will consider current directory instead).",
        ),
    ] = "invoice_files/",
    verbose: Annotated[
        bool,
        typer.
            Option("--verbose", "-v", help="show detailed processing messages"),
    ] = False)
```

extract data from an Excel file (save data to JSON format file with the same name as original file but `.json` extension).

### Arguments:

- `file_name` - files to process (wildcards allowed).
- `files_directory` - directory to be used to look for Excel files. Defaults to `invoice_files/`. NOTE: if default directory does not exists will consider current directory instead
- `verbose` - show detailed processing messages". Defaults to `False`.

### called\_when\_no\_command

```
@app_cli.callback(invoked_without_command=True)
def called_when_no_command(
    ctx: typer.Context,
    version: Annotated[
        bool,
        typer.Option("--version", help="show application version"),
    ] = False)
```

function called when no command is invoked and to provide only application version (for external users to test it!).

## chkisld

chkisld: modul de verificare a starii de incarcare a unei facturi emise

### Identification:

- code-name: `chkisld`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

### Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section `Componenta xl2roefact`
- INTRARI: fisier `f-XLSX` sau numarul / cheia / codul facturii
- IESIRI: valoarea echivalent `TRUE` daca factura a fost deja incarcata sau valoarea echivalent `FALSE` daca factura nu a fost incarcata

## chkxml

chkxml: modul de validare a facturii in sistemul ANAF E-Factura

### Identification:

- code-name: `chkxml`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

### Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section `Componenta xl2roefact`
- INTRARI: fisier `f-XML`
- IESIRI: raport cu eventualele erori de validare

## config\_settings

Configuration and setting parameters.

(en-us) README before making changes:

- each parameter has a short help (lines starting with `#` character) - read it before changing that parameter
- do not change parametrs name as specified before equal (`=`) sign
- lists are enclosed in sqaured brackets (`[...]`) and items are separated by comma character (`,`)

- strings are enclosed in " characters
- if you want to clear a list (for example you do not want any options inside) just let it as `<PARAMETR NAME> = []` - do not drop that parameter
- do not add supplementary parameters, they will not be used without software changes (also risk to induce potential errors)
- for calendaristic dates Excel cells use `date` format and change it as display option to show wanted format

(ro) README înainte de a face modificari:

- fiecare parametru are un hep scurt (liniile ce incep cu caracterul #) - citi-l inainte de a modifica un parametru
- nu schimbati numele parametrilor asa cum este el specificat inainte de semnul egal (=)
- listele sunt incluse intre paranteze drepte ( [...]) si elementele lor sunt separate prin caracterul virgula ( , )
- sirurile de caractere sunt incluse intre ghilimele (caracterul " )
- daca doriti stergerea unei liste (de ex daca nu doriti nici o optiune pentru acea lista) doar lasati acel parametru cu valoarea [] - nu stergeti in nici un caz acel parametru
- nu adaugati parametrii suplimentari (altii decit cei specificati aici), acestia nu vor fi utilizati fara a modifica aplicatia (de asemenea riscati sa induceti erori in cod)
- pentru datele calendaristice in celula Excel a se utiliza formatul standard de data ( date ) si modificati formatul de afisare in formatul dorit pe factura tiparibila

## DEFAULT\_SUPPLIER\_COUNTRY

### NOTE: "pattern-uri" (sabioane) de identificare si regasire a datelor folositi de

\_\_ comanda `x12json` reprezentind functionalitatea de extragere a datelor din Excel si exportul lor in formatul JSON (modulul ``rdinv``)\_\_

## ldxml

ldxml: modul de incarcare a facturii in sistemul ANAF E-Factura

Identification:

- code-name: `ldxml`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section Componenta `x12roefact`

- INTRARI: fisier `f-XML`
- IESIRI: raport cu validarea si identificatorul incarcarii

## libutils

general utilities library for all `x12roefact` components and modules.

### Identification:

- code-name: `libutils`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

### Components:

- `isnumber(a_string: str) -> bool` Test a string if it could be used as number (int or float)
- `find_str_in_list(list_of_str_to_find: list, list_to_search: list) -> int` Search more strings (ie, a list) in list of strings

### isnumber

```
def isnumber(a_string: str) -> bool
```

test if a string is valid as any kind of number.

#### Arguments:

- `a_string` - input string.

#### Returns:

- `True` - if input string is valid as any kind of number, otherwise `False`.

### find\_str\_in\_list

```
def find_str_in_list(list_of_str_to_find: list, list_to_search: list) -> int
```

find a substring from `list_of_str_to_find` in elements of `list_to_search`.

#### Arguments:

- `list_of_str_to_find` - list of strings to search for.
- `list_to_search` - liste where to search for substrings.

#### Returns:

- `index` - the index of list item which contains `str_to_find` (first found) or `None` if not found.

# rdinv

rdinv: modul de procesare a fisierului Excel ce contine factura si colectare a datelor aferente.

Formatul acceptat fisier Excel este `XLSX`.

Identification:

- code-name: `rdinv`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section Componenta `xl2roefact`
- INTRARI: fisier format `XLSX` ce contine factura emisa (cod: `f-XLSX`)
- IESIRI: fisier format `JSON` imagine a datelor facturii (cod: `f-JSON`)

## rdinv

```
def rdivn(file_to_process: str,
          invoice_worksheet_name: str = None,
          *,
          debug_info: bool = False) -> dict
```

read Excel file for invoice data.

Produce a dictionary structure + JSON file with all data regarding read invoice: canonical KV data, meta data, map to convert to XML and original Excel data.

### Arguments:

- `file_to_process` - the invoice file (exact file with path).
- `invoice_worksheet_name` - the worksheet containing invoice, optional, defaults to first found worksheet.
- `debug_info` - key only, show debugging information, default `False`.

### Returns:

- `dict` - the invoice extracted information from Excel file as `dict(Invoice: dict, meta_info: dict, excel_original_data: dict)` TODO subject of documentation update.

NOTE ref important variables: \* `db: pylightxl object`: EXCEL object with invoice (as a whole) \* `ws: pylightxl object`: WORKSHEET object with invoice

## get\_excel\_data\_at\_label

```
def get_excel_data_at_label(pattern_to_search_for: list[str],
                           worksheet: xl.Database.ws,
                           area_to_scan: list[list[int]] = None,
                           targeted_type: Callable = str,
                           down_search_try: bool = True) -> dict
```

get "one key Excel values", like invoice number or invoice issue date.

### Arguments:

- `pattern_to_search_for` - for example for inv number, will pass the `PATTERN_FOR_INVOICE_NUMBER_LABEL`.
- `worksheet` - the worksheet containing invoice (as object of `pyxllight` library).
- `area_to_scan` - area of cells to be searched, default whole worksheet.
- `targeted_type` - what type expect (will try to convert to, if cannot will return str), default `str`.
- `down_search_try` - establish if DOWN search method is tried, default `True`.

### Returns:

`None` if not found OR `dictionary` containing: \* `"value": int | float | str` - the value found converted to requested `targeted_type` if possible or `str` otherwise; if "out of space" then returns `None` \* `"location": (row, col)` - adrees of cell where found value

### Notes:

- normal scan order is 1.RIGHT, 2.DOWN (if allowed), 3.IN-LABEL only in given area and pattern.

## mk\_kv\_invoice\_items\_area

```
def mk_kv_invoice_items_area(invoice_items_area_xl_format)
```

transform `invoice_items_area` in "canonical JSON format" (as kv pairs).

### Arguments:

- `invoice_items_area_xl_format` - invoice items area in Excel format (ie, DataFrame with row, col, data).

### Returns:

- `invoice_items_area_xl_format` - dictionary with invoice items in Excel format (ie, rows, columns).

### Notes:

- for ROefact XML model (& plan) see `invoice_files/__model_test_factura_generat_anaf.xml`.

## get\_invoice\_items\_area

```
def get_invoice_items_area(worksheet, invoice_items_area_marker, wks_name)
```



get invoice for `invoice_items_area` , process it and return its Excel format.

Process steps & notes: \* find invoice items subtable. \* clean invoice items subtable. \* extract relevant data. \*

NOTE: all Excel cell addresses are in `(row, col)` format (ie, Not Excel format like "A:26, C:42, ...")

#### Arguments:

- `worksheet` - the worksheet containing invoice (as object of `pyxllight` library).
- `invoice_items_area_marker` - string with exact marker of invoice items table.
- `NOTE` - this is the UPPER-LEFT corner and is determined before calling this procedure.
- `wks_name` - the worksheet name (string) of the `worksheet` object.

#### Returns:

- `invoice_items_area` - dictionary with invoice items in Excel format (ie, rows, columns).

## wrxml

wrxml: modul de generare a fisierului format XML

#### Identification:

- code-name: `wrxml`
- copyright: (c) 2023 RENWare Software Systems
- author: Petre Iordanescu (petre.iordanescu@gmail.com)

#### Specifications:

- document cerinte initiale: `110-SRE-api_to_roefact_requirements.md` section `Componenta xl2roefact`
- INTRARI: fisier `f-JSON`
- IESIRI: fisier format XML conform cerintelor si sistemului ANAF E-Factura (cod: `f-XML`)

`__init__`

`__main__`

**xl2roefact.main:** Python package standard file to assure run as `python -m xl2roefact`.

#### Identification:

- code-name: `__main__`
- copyright: (c) 2023 RENWare Software Systems

- Deployments:

- Specifications:

- \_\_version\_\_

xl2roefact version info.

[illegible]

Page 10 of 10