



**ALPHAREN Integrator (ARINT) System**

*(c) 2021 RENware Software Systems. RESTRICTED only for project internal use*

Outgoing (channels)

Product 0000-0156 0.0 to current version

- 210731 me new doc
- 210801 me last update

**Table of contents:**

- [Outgoing \(channels\)](#)
    - [Outgoing channels overview](#)
    - [REST outgoing definition](#)
- 

## Outgoing channels overview

An outgoing channel is a **output endpoint** from a service. It will act as an endpoint usable by a service to access an external system. They will be named as short *OUTGOING* or *OUTCONNS*.

Outgoings can use multiple standard destinations, SAP queues (ex AMQPz IBM), databases, mail and so on.

Outconns are typically invoked (by a service) using attributes from self.out, e.g. self.out.rest, self.out.amqp, self.out.sap and so on, maintaining a connection pool internally when needed so that services can just focus on the invocation part.

## REST outgoing definition

For an **outgoing**, the following parameters must be provided:

- Name
- Host
- URL path
- Data format
- Service
- Security definition

(*NOTE*: it is important to retain the default HEAD ping method, because it will be used to check the endpoint availability)

**Name** is the ARCLST name of the channel.

**URL path** is the address of channel endpoint. This is part of ARCLST route, ie `ARCLST_path.../URL_path`.

**Data format** is the format of data that will be exchanged through this channel. Usual (for REST channels at least) is to specify here *JSON*.

**Service** is the name of the service that will be called when channel is invoked.

**Security** represents the security domain that will be applied to this channel.

Other parameters could also be specified here, for example if there are supplementary parameters (like those with ? after the route), header info (for out channels) and so on.

---

Last update: August 20, 2023