

Last modified on

Sports Data Soccer API - Match Facts Betting Feed (MA15)

Get automated betting match facts for a specific game

Overview

The Soccer **Match Facts betting feed** delivers automated match betting facts for a specific game. The betting facts are generated from a pre-determined list and have a consistent structure and wording - These are different from the MA9 manually generated facts by our Data Editorial department.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you do not exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

An initial feed for each game is triggered seven days before the match, with updates sent after any other games are played by one of the teams involved the match or another game in the competition takes place

Match Facts Betting (MA15) Guide

USAGE	FEED
GET match betting facts by fixture UUID (path parameter)	/soccerdata/matchfactsbetting/{outletAuthKey}
GET match betting facts by fixture UUID (fx parameter - supports legacy IDs)	/soccerdata/matchfactsbetting/{outletAuthKey}

If your request URL is as follows (does not contain a fixture UUID), the feed returns an error:
/soccerdata/matchfactsbetting/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other. However, you must query the **/matchfactsbetting** feed by a specific fixture (match) UUID.

Legacy IDs: You can use the **fx** parameter to filter by legacy IDs - only one ID is supported (you cannot pass multiple IDs in a comma-separated list).

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example **GET** requests (rather than cURL, for example). All URIs are case-sensitive - this means that URI strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid **{outletAuthKey}** (Outlet Authorisation Key), query parameters for **_rt={mode}** (operating mode) and **_fmt={dataFormat}** (response format), entity query parameter and UUID.
- Begin the query parameter string with **?** (question mark) - this must be after the Outlet Authorisation Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the **&** (ampersand) operator. Values must be separated by the correct operator, for example **&** (multiple values, 'AND'), or - if a parameter supports it - **,** (multiple values, 'OR') or **!** ('NOT').
- Use the required **_** (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces **{ }** from your calls (we include these as an example only).
- If using the JSONP format (**_fmt=jsonp**) you **MUST** use it in combination with the callback parameter (**_clbk**) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
{fixtureUuid} Fixture UUID	GET match betting facts by the specified fixture UUID (path parameter method). Pass the fixture UUID in the request URL directly as the {assetId} (asset/resource ID). <pre>GET https://api.performfeeds.com/soccerdata/matchfactsbetting/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}</pre>
fx	Get match betting facts by the specified fixture UUID (query parameter method). Pass the fixture UUID to the fx parameter. <pre>GET https://api.performfeeds.com/soccerdata/matchfactsbetting/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&fx={fixtureUuid}</pre>
_lcl	Specify the language/locale value to the _lcl parameter to return the feed in a particular language. If you do not specify the parameter, the feed language defaults to English. For example, _lcl=en-en . For more languages, please refer to the Supported Languages.

Query parameter	Value and description
	GET https://api.performfeeds.com/soccerdata/matchfactsbetting/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&fx={fixtureUuid}&lcl={value} Note: If translations for the requested language are unavailable, the feed response will fall back to the default language, English.

Supported Languages

The match fact betting feed is currently available in the following languages:

- German
- Italian
- Spanish
- Korean
- Chinese
- Romanian
- Greek
- Polish
- Czech
- Portuguese (POR)
- Portuguese (BRA)
- Dutch
- Bulgarian
- Turkish
- French
- Russian
- Swedish
- Hungarian
- Danish
- Slovak
- Croatian
- Japanese
- Georgian

You must specify the language/locale value to the _lcl parameter to return the feed in a particular language. If you do not specify the parameter, the feed language defaults to English. For example, _lcl=en-en

Supported Languages

LANGUAGE	PARAMETER VALUE
English (United Kingdom)	en-en
German (Deutsch, Germany)	de-de
Italian (Italy)	it-it
Spanish (Spain)	es-es
Korean (Korea)	ko-kr
Chinese (China)	zh-cn

LANGUAGE	PARAMETER VALUE
Romanian (Romania)	ro-ro
Greek (Greece)	el-gr
Polish (Poland)	pl-pl
Czech (Czechia)	cs-cz
Portuguese (POR)	pt-pt
Portuguese (BRA)	pt-br
Dutch	nl-nl
Bulgarian	br-br
Turkish (Türkiye)	tr
French (France)	fr
Russian (Russia)	ru
Swedish (Sweden)	sv
Hungarian (Hungary)	hu
Danish (Denmark)	dk
Slovak (Slovakia)	sk
Croatian (Croatia)	hr
Japanese (Japan)	jp
Georgian (Georgia)	ge

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML](#)
- [XML - fx parameter](#)
- [JSON](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<matchFactsBeting> (XML only)

▶<matchInfo>

▶<description>

▶<sport>

▶<ruleset>

▶<competition>

▶<country>

▶<tournamentCalendar>

▶<stage>

▶<series>

▶<contestants>

▶<contestant>

▶<country>

▶<venue>

▶<messages>

▶<message>

▶<marketTypes>

▶<marketType>