

Last modified on

Sports Data Soccer API - Deletions Feed (DEL)

Get a list of matches, teams or players that have been deleted within the last 72 hours.

Overview

The Soccer **Deletions feed** provides a way for you to show which matches, teams or players have been deleted within the last 72 hours.

You can also use the `_dlt` parameter to specify the exact time that you would like to return assets for. For example, within the previous 24 hours, 9 hours, and so on, but not more than 72 hours in the past. If you do not use the `_dlt` parameter then the default behaviour of the feed will be to return data from within a maximum period of 72 hours.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us, this can vary depending on whether you make requests as a B2B or B2C outlet. If you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
-	We suggest polling the feed once an hour - it is unlikely you will need to poll it more frequently than this							

Deletions (DEL) Guide

USAGE	FEED
GET a list of either deleted matches, teams, or players according to the specified query parameter criteria	/soccerdata/deletions

If your request URL is as follows or does not contain the data type parameter and value, the feed returns an error:
/soccerdata/deletions/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other. However, you must query the `/deletions` feed by a specific `type` of entity (match/team/person)).

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL ({protocol}://{requestDomain}/{feedResource}), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid {outletAuthKey} (Outlet Authentication Key), query parameters for _rt={mode} (operating mode) and _fmt={dataFormat} (response format), entity query parameter and UUID.
- Begin the query parameter string with ? (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the & (ampersand) operator. Values must be separated by the correct operator, for example & (multiple values, 'AND'), or - if a parameter supports it - , (multiple values, 'OR') or ! ('NOT').
- Use the required _ (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces {} from your calls (we include these as an example only).
- If using the JSONP format (_fmt=jsonp) you MUST use it in combination with the callback parameter (_clbk) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
type	GET only data of a certain type that has been deleted within the last 72 hours - filter the feed to show either matches, teams, or players. Values: One of the following: <code>match</code> <code>team</code> <code>person</code> GET https://api.performfeeds.com/soccerdata/deletions/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&type={dataType}&{queryParameters}
_dlt + type	GET data that has been deleted within the specified time period (up to 72 hours) for the specified data type. Pass a date/time value to the <code>_dlt</code> parameter. Note: You cannot use this parameter without passing the data type in the call. Value: Use {dateTime} to specify the date and time - in the format (UTC/GMT): YYYY-MM-DDThh:mm:ssZ GET https://api.performfeeds.com/soccerdata/deletions/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&_dlt={dateTime}&type={dataType}&{queryParameters}

Query parameter	Value and description
<code>_pgNm</code> + <code>_pgSz</code>	GET data only in the specified page size and/or page number. All results are returned in pages and these parameters help limit the page size in order to optimise the efficiency of the SDAPI. Note: You cannot use this parameter without passing the <code>data_type</code> in the call. <code>_pgNm</code> - Specify the <code>{pageNumber}</code> to return - indexed from <code>1</code>. If this value is not provided, then page <code>1</code> is returned by default. <code>_pgSz</code> - Specify the size of the page to return - the number of article definitions in a page. Valid <code>{pageSize}</code> values depend on the operating mode of an outlet. For B2B requests, the maximum value is <code>1000</code> (default is 50). For B2C requests, the maximum value is <code>50</code> (the default is 20). GET <code>https://api.performfeeds.com/soccerdata/deletions/{outletAuthKey}?_pgSz={pageSize}&_pgNm={pageNumber}&{queryParams}</code>

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML - type=match](#)
- [JSON - type=match](#)
- [XML - type=team](#)
- [XML - type=person](#)
- [XML - type=match + _dlt](#)

type + _dlt example: This example will return error `10213` because the timestamp is greater than 72 hours in the past. To view an example without receiving an error, change the timestamp value for `_dlt` to a timestamp within the last 72 hours of your current time.

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<transfers> (XML only)

▶<entity>