

Last modified on

Sports Data Soccer API - In-Venue Aggregated Events Feed (MA40)

Get *aggregated* list of all *pressure stats* and *line breaking pass stats* of each player, of the teams playing in a match, based on “in venue” data.

Overview

The **In-Venue Aggregated Events** soccer feed provides the *aggregated* list of all *pressure* and *line breaking pass* stats of each player in the lineup of the teams playing in a match, based on “in venue” data, along with contestants, goals, cards, substitutes and match official's detail.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Contact your Stats Perform representative for a full list of available comps.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 13	TIER 8+9+10+11	TIER 6+7	TIER 5	TIER 1+2+3
Updated on every stop in play during the game, including for the following types of events: goal, shot at goal, assist, free kick, offside given, cards, start of the half, end of the half, corner, substitution, lineup Note: There will always be a gap of at least 30 seconds between files unless a goal is scored	See Tier 13	Post-match	n/a	No more frequently than one URL poll every 30 seconds for range: <KO - 1h; KO + 4h> Up to 1-hour interval for range: <KO + 4h; KO + 8h> Up to 24-hour interval 8h+ of match ending, lasting a maximum of 7 days	n/a	n/a	n/a	n/a

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 13	TIER 8+9+10+11	TIER 6+7	TIER 5	TIER 1+2+3
Updated on every stop in play during the game, including for the following types of events: goal, shot at goal, assist, free kick, offside given, cards, start of the half, end of the half, corner, substitution, lineup Note: There will always be a gap of at least 30 seconds between files unless a goal is scored	See Tier 13	Post-match	n/a	No more frequently than one URL poll every 30 seconds for range: <KO - 1h; KO + 4h> Up to 1-hour interval for range: <KO + 4h; KO + 8h> Up to 24-hour interval 8h+ of match ending, lasting a maximum of 7 days	n/a	n/a	n/a	n/a

In-Venue Aggregated Events (MA40)

USAGE	FEED
GET In-Venue Aggregated Events list by fixture UUID inline URL path	/soccerdata/invenueaggregatedevents/{outletAuthKey}{queryParameters}
GET In-Venue Aggregated Events list by fixture UUID	/soccerdata/invenueaggregatedevents/{outletAuthKey}{queryParameters}

If your request URL is as follows (does not contain a mandatory fixture UUID), the feed returns an error:
/soccerdata/invenueaggregatedevents/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed also makes use of the [Global query parameters](#), and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/invenueaggregatedevents` feed by a fixture (match) UUID.

Legacy IDs: You can use the `fx` query parameter to filter by an Opta legacy ID (only one ID is supported - you cannot specify a comma-separated list of IDs).

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the [main guide](#) and [API Overview and Authorisation guide](#).

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for

`_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.

- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or `-` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
fixture/match UUID	GET In-Venue Aggregated for fixture UUID by passing the fixture/match UUID as a path parameter (the asset/resource) in the URL. <pre>GET https://api.performfeeds.com/soccerdata/invenueaggregatedevents/{outletAuthKey}/{fixture Uuid?_rt={mode}&_fmt={dataFormat}</pre>
fx	GET In-Venue Aggregated list for a fixture UUID by passing a fixture UUID or legacy Opta match ID to the fx parameter. <pre>GET https://api.performfeeds.com/soccerdata/invenueaggregatedevents/{outletAuthKey}?fx={fixt ureUuid&_rt={mode}&_fmt={dataFormat}</pre>
_lcl	You can return assets from a specific locale using the associated <code>{localeValue}</code> code, or use the <code>*</code> wildcard operator (asterisk) to return assets in any locale/language. You can also include additional query parameters in the URL. Refer to the Locales table for supported languages and locations, and corresponding values. Note: You cannot specify a <code>*</code> wildcard in combination with a locale code otherwise, the feed returns the error code <code>10202</code> (invalid request parameter value). <pre>GET https://api.performfeeds.com/soccerdata/invenueaggregatedevents/{outletAuthKey}/{fixt ureUuid?_rt={mode}&_fmt={dataFormat}&_lcl={localeValue}</pre>

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML](#)
- [JSON](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<inVenueAggregatedEvents> (XML only)

▶<matchInfo>

▶<description>

▶<sport>

▶<ruleset>

▶<competition>

▶<country>

▶<tournamentCalendar>

▶<stage>

▶<contestants>

▶<contestant>

▶<country>

▶<venue>

▶<liveData>

▶<matchDetails>

▶<periods> (XML only)

▶<period>

▶<suspensions>

▶<suspension>

▶<scores>

▶<ht>

▶<ft>

▶<total>

▶<goal>

▶<missedPen>

▶<card>

- ▶<substitute>
- ▶<VAR>
- ▶<penaltyShootout>
- ▶<penaltyShot>
- ▶<lineUp>
- ▶<player>
- ▶<lineBreakingPassAggregates>
- ▶<stat>
- ▶<pressureAggregates>
- ▶<stat>
- ▶<lineBreakingActionAggregates>
- ▶<stat>
- ▶<lineBreakingCarryAggregates>
- ▶<stat>
- ▶<teamOfficial>
- ▶<teamStats>
- ▶<lineBreakingPassAggregates>
- ▶<stat>
- ▶<pressureAggregates>
- ▶<stat>
- ▶<matchDetailsExtra>
- ▶<attendance>
- ▶<matchOfficials> (XML only)
- ▶<matchOfficial>

How Are VAR Events Reported?

when a VAR (Video Assistant Referee) review takes place our analysts will collect the type of event being reviewed, the team and player involved, and the decision of the review (outcome) which also describes what happens next.

Please [click here](#) for more details on VAR outcomes.

Statistic Types

Statistics are returned for the given contestant and for each player, and are delivered under the `stat` object. Stats are split into the following elements (where available):

- Line Breaking Pass Aggregates - Player Stats
- Line Breaking Pass Aggregates - Team Stats
- Pressure Aggregates - Player Stats
- Pressure Aggregates - Team Stats
- Line Breaking Action Aggregates - Player Stats
- Line Breaking Carry Aggregates - Player Stats

Within these elements, each statistic is shown as a stat and its name and value will appear under it, if it is available.

Click on the buttons below to see the complete lists of statistics names and their description

▶ **Line Breaking Pass Aggregates - Player Stats**

▶ **Line Breaking Pass Aggregates - Contestant/Team Stats**

▶ **Pressure Aggregates - Player Stats**

▶ **Pressure Aggregates - Contestant/Team Stats**

▶ **Line Breaking Action Aggregates - Player Stats**

▶ **Line Breaking Carry Aggregates - Player Stats**