

Last modified on

Sports Data Soccer API - Mappings Feed (MAP)

Match up IDs for competitions, fixtures, contestants/teams, players/people between different suppliers and SDAPI UUIDs.

Overview

The Soccer **Mappings feed** allows you to map entity IDs for competitions, contestants (teams), people (players) and fixtures between your products and supported suppliers - this includes STATS, Opta and UUIDs (SDAPI/Perform Feeds).

You can query the feed one by either a single ID or up to 50 IDs (of the same entity type) from one supplier in order to return the corresponding IDs used by another supplier. Each ID represents the same entity, with their respective data suppliers.

For example:

- pass an SDAPI UUID in the URL to call the feed - this will return the ID from the other supplier and the SDAPI UUID.
- pass an ID or IDs from a third party supplier into the URL to call the feed - this will return the associated SDAPI UUID or UUIDs and the supplier ID.

Latest Updates:

- **31 March 2021:** Added Match Recap (MA26) feed in the left menu.

How to look-up returned entity IDs: The feed returns IDs but no additional metadata about the entity. To find out the metadata associated with the ID, such as the name and other information, you can look up the SDAPI UUID in the relevant feed. Below are some examples but the entity IDs will be supported in many SDAPI feeds:

- Fixture IDs - includes **Fixtures and Results (MA1)** | **Match Stats (MA2)** | **Match Events (MA3)**
- Competition IDs - includes **Fixtures and Results (MA1)** | **Seasonal Stats (TM4)** | **Tournament Calendars (OT2)**
- Contestant IDs - includes **Fixtures and Results (MA1)** | **Squads (TM3)** | **Seasonal Stats (TM4)** | **Tournament Calendars (OT2)**
- Person IDs - includes **Player Career (PE2)** | **Injuries (PE7)**

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our [FAQs](#). We also recommend that you take a look at our [API Overview and Authentication Guide](#). You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

POLLING FREQUENCY

During matchdays: Once every 15 minutes.
On non-match days, poll the feed once per day.

Mappings (MAP) Guide

ENDPOINT

GET IDs and mappings for the specified **entity type/supplier/UUID** according to the given **query parameters** - it is possible to request ma

If your request URL is as follows (without an entity type or ID URI), the feed returns an error:
`/soccerdata/mappings/{outletAuthKey}`

Query Parameters And Example Request Parameters

This feed also makes use of the [Global query parameters](#), and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/mappings` feed by an entity ID or multiple IDs - note that multiple IDs in one call must all be of the same entity type (eg multiple contestant IDs, but not a mix of a contestant ID with a different entity type in the same call).

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the [main guide](#) and [API Overview and Authorisation guide](#).

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').

- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Supplier Name And Entity Type Examples

These examples would replace the placeholders `{supplierName}` and `{entityType}` in our example URLs - you will use these in your calls.

- Supplier Name examples: `opta` | `stats` | `perform`
- Entity Type examples: `competition` | `contestant` | `fixture` | `person` | `venue`

IMPORTANT:
The parameter `idList` has now been made mandatory. Previously it was advised to call by `idList` but due to the sheer volume of entities we now support, we have changed the behaviour of the feed to be mandatory. Failure to do so will result in an error message. Please note, you can pass up to 50 ids in the URL.

Query parameter	Value and description
<code>idList</code> + <code>idType</code>	GET mappings for a specified ID or list of IDs from the specified supplier and entity type, in the same call You can use <code>idList</code> in combination with <code>idType</code> to achieve one of the following: • get mappings for a specific SDAPI/Perform <code>uuid</code> (not filtered by <code>entityType</code> or <code>supplierName</code>) • get mappings for a specific <code>uuid</code> (filtered by <code>entityType</code> or <code>supplierName</code>) • get mappings for multiple IDs, specified in a list, in the same call for a specific supplier and entity type • get mappings for multiple <code>entityType</code> instances in the same call (not filtered by <code>supplierName</code> or SDAPI/Perform UUID) • get mappings for a specific <code>entityType</code> (not filtered by <code>supplierName</code> or SDAPI/Perform UUID) • get mappings for a specific <code>supplierName</code> (not filtered by <code>entityType</code> or SDAPI/Perform UUID) • get mappings for a specific <code>entityType</code> AND <code>supplierName</code> (not filtered by an SDAPI/Perform UUID) Note: • You cannot use <code>idType</code> by itself (it must be used with <code>idList</code>) otherwise, the feed returns an error • To pass multiple IDs in one call, the IDs must be for the same entity type (eg competition) and passed in a comma-separated list. • You can pass up to 50 IDs in one call to the <code>idList</code> parameter. The feed has a limit of 20,000 results.

Query parameter	Value and description
	▶ SHOW EXAMPLE CALLS

We added some further logic to the mappings feed in Feb 2021 when called by **people** to allow IDs for coaches and referees as well as players (as in some case the same person has multiple dependent on whether they were a player and then became coach/manager). Here is a summary:

- If only one ID is returned, the user should associate the id with the entity they are trying to look i.e. whether a player, coach or referee.
- If two IDs are returned then it will be returned in following order: 1) player id, 2) coach id, 3) referee id. The first ID will be player id unless the player doesn't have one and in which case it will be the coach id. The Second ID can be either coach id or referee id.
- If three IDs are returned then it will be returned in following order: 1) player id, 2) coach id, 3) referee id, so users will always know which one is player id, coach id and referee id.

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

Get Mappings By Third Party Supplier ID And Entity Type

Parameters: **idType**, **idList**, **_rt=b**, **_fmt**

- opta (supplierName) & competition (entityType) - mapped to SDAPI UUID - **[XML](#)**
- stats (supplierName) & fixture (entityType) - mapped to SDAPI UUID - **[XML](#)**
- perform (supplierName) SDAPI UUID & person (entityType) - mapped to Opta ID + STATS ID - **[XML](#)**
- IFES (supplierName) SDAPI UUID & person (entityType) - mapped to SDAPI UUID - **[XML](#)**
- IFES (supplierName) SDAPI UUID & contestant (entityType) - mapped to SDAPI UUID - **[XML](#)**
- IFES (supplierName) SDAPI UUID & competition (entityType) - mapped to SDAPI UUID - **[XML](#)**

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<mappings> (XML only)

▶<mapping>

▶<suppliers>

▶<suppliers>