

Last modified on

Sports Data Soccer API - Match Events Feed (MA3)

Get all events in a game - including the player, team, event, type, time (minute and second), and qualifiers for each action

Overview

The Soccer **Match Events feed** is a time-coded feed that lists all individual events and player actions in a match. Each incidence in the feed includes a contestant (team), event, type, and timestamp for each action. Every event has a series of qualifiers describing it. You will find explanations of every possible event and qualifier that could be returned in the response in our complete lists of **Events Types** and **Qualifier Types**. See the **Appendix** to put this into context and get information about the following: **Pitch coordinates and direction of play** | **Goalmouth coordinates** | **Pitch zones** | **Playing positions** | **Formations**

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
Updated on every stop in play during the game, including for the following types of events: goal, shot at goal, assist, free kick, offside given, cards, start of the half, end of the half, corner, substitution, lineup Note: There will always be a gap of at least 30 seconds between files unless a goal is scored	See Tier 13	Post-match	n/a	No more frequently than one URL poll every 30 seconds for range: <KO - 1h; KO + 4h> Up to 1-hour interval for range: <KO + 4h; KO + 8h> Up to 24-hour interval 8h+ of match ending, lasting a maximum of 7 days	n/a	n/a	n/a	n/a

Match Events (MA3) Guide

USAGE

GET **match events** data for a match by fixture UUID.

Required: Fixture UUID as a path parameter (as the resource ID). See the query parameters table below for other possible ways to query

If your request URL is as follows (does not contain a fixture UUID), the feed returns an error:
/soccerdata/matchevent/{outletAuthKey}

How can I get fixture and other entity UUIDs?

Use the **Tournament Calendar (OT2)** or **Fixtures and Results (MA1)** feeds to get fixture metadata, including its unique ID (UII), linked contestants, competition, tournament calendar and other entities.

Query Parameters And Example Request Parameters

You must query the **/matchevent** feed by a fixture (match) UUID. This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other).

Legacy IDs: You can use the **fx** parameter to filter by legacy IDs - only one ID is supported (you cannot pass multiple IDs in a comma-separated list).

Making successful requests: In our guides, we use HTTPS syntax for our example **GET** requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid **{outletAuthKey}** this must be after the Outlet Authentication Key (and endpoint, if applicable). for

`_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format). If required, it should also include an entity UUID (such as a fixture/match UUID).

- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or `-` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{}` from your calls (we include these as an example only).
- If using the JSON format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
<code>{fixtureUuid}</code> Fixture UUID	GET match events for a match by the specified fixture UUID (path parameter method). Pass the fixture UUID in the request URL directly as the <code>{assetId}</code> (asset/resource ID). <pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}</pre>
<code>fx</code>	Get match events for a match by the specified fixture UUID (query parameter method). Pass the fixture UUID to the <code>fx</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&fx={fixtureUuid}</pre>
<code>ctst</code>	Get match events only for the specified contestant in the fixture. Pass the contestant UUID to the <code>ctst</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}</pre>
<code>prsn</code>	Get match events only for a specific person in the fixture. Pass the person UUID to the <code>prsn</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&prsn={personUuid}</pre>
<code>type</code>	Get match events only of a specific event type(s) in the fixture, such as shots, goals, and crosses. Pass the event type ID(s) to the <code>type</code> parameter. You can specify multiple event <code>typeId</code> values to the <code>type</code> parameter in a comma-separated list (up to a maximum of 20 values). single event typeId value: <pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}&prsn={personUuid}&type={typeid}</pre> multiple event typeId values:

Query parameter	Value and description
	<pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}&prsn={personUuid}&type={typeid},{typeid},{typeid}</pre>
ctst + prsn	Get match events only for a specific person and (who is a member of) the contestant in the fixture. Pass the contestant UUID to the <code>ctst</code> parameter, and person UUID to the <code>prsn</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}&prsn={personUuid}</pre>
ctst + type	Get match events only for a specific event type(s) and contestant. Pass the contestant UUID to the <code>ctst</code> parameter, and event type UUID (or UUIDs) to the <code>type</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}&type={typeid}</pre>
prsn + type	Get match events only of a specific event type(s) which are associated with the specified person in the fixture. Pass the event type ID(s) to the <code>type</code> parameter and person UUID to the <code>prsn</code> parameter. Note: You can specify multiple event <code>typeId</code> values to the <code>type</code> parameter in a comma-separated list (up to a maximum of 20 values) - for example: <code>type={typeId},{typeId},{typeId}</code> <pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&prsn={personUuid}&type={typeid}</pre>
ctst + prsn + type	Get match events only of a specific event type(s) which are associated with the specified person and (who is a member of) the contestant in the fixture. Pass the event type ID(s) to the <code>type</code> parameter, contestant UUID to the <code>ctst</code> parameter, and person UUID to the <code>prsn</code> parameter. Note: You can specify multiple event <code>typeId</code> values to the <code>type</code> parameter in a comma-separated list (up to a maximum of 20 values) - for example: <code>type={typeId},{typeId},{typeId}</code> <pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}&prsn={personUuid}&type={typeid}</pre>
_lcl=en-op	Add this parameter-value to return assets with the Opta namings, in English, in the response (instead of Opta Core namings). When the call does not include the <code>_lcl=en-op</code> parameter-value, the feeds will continue to work as they do currently; one example is that the response will be in the default language of English unless the call contains the <code>_lcl</code> parameter and a locale code value to request the response in a different locale/language. Note: You can use this parameter in combination with other valid parameters and values in the request. However, you cannot use it in combination with a locale/language code and <code>_lcl</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/matchevent/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&_lcl=en-op&{queryParameters}</pre> Do not supply both the <code>_lcl</code> (with a locale/language code value) and <code>_lcl=en-op</code> in the same call - this is not supported; otherwise, the feed will return an error and code 10203 (Ambiguous/Invalid request parameters) in the response due to a duplicated <code>_lcl</code> parameter.

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

Each response provides data points about the match and a number of events. Any event-related updates will contain the player, team, event, type, minute and second for each event. Events are delivered under the **events** element. Each **event** has an Event ID, **Event Type ID** and a series of **Qualifiers** describing it.

You can get an explanation of the data contained within the response in **Feed Output** and the **Appendix**.

- **XML**
- **JSON**
- **XML - ctst**
- **JSON - prsn**
- **XML - type**
- **XML - type** (multi-type)
- **JSON - ctst & type**
- **XML - ctst & prsn**
- **XML - ctst & prsn & type**
- **JSON - prsn & type**

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

- The root element can be **matchEvents** or **matchInfo** - see the table below.
- In the scenario where the match has not yet been played (for example, it is a scheduled fixture to be played in the future), not all attributes listed here will be present and we may provide placeholder values for some attributes. For example, the scores, winner, contestant name, position, and ID may not be known (the contestant **id** attribute may also not be returned). However, the feed will be updated with this information once it is available.

▶<matchEvents> (XML only)

▶<matchInfo>

▶<description>

▶<sport>

▶<ruleset>

▶<competition>

▶<country>

▶<tournamentCalendar>

▶<stage>

▶<series>

▶<contestants> (XML only)

▶<contestant>

▶<country>

▶<venue>

▶<liveData>

▶<matchDetails>

▶<periods> (XML only)

▶<period>

▶<suspensions>

▶<suspension>

▶<scores>

▶<ht>

▶<ft>

▶<et>

▶<pen>

▶<total>

▶<totalUnconfirmed>

▶<events> (XML only)

▶<event>

▶<qualifier>

Event Types

Events are delivered as an array (under **events** for XML or **events** for JSON). When an event occurs during a match, it is assigned a unique Event ID. For each unique Event ID, there is an associated Event Type ID (**typeId**) which classifies the general event type that has occurred. It is common for an event instance to be accompanied by a Qualifier array (under **qualifier**). Each Qualifier has an ID and a Qualifier ID (**qualifierId**) and value - these explain and add depth and further information about the event. However, it is not mandatory (some events will not have qualifiers).

Use this table to look-up an Event Type ID and its description. You should also cross-reference any related Qualifier ID values with the [Qualifier Types](#) list.

Event Definitions

We have a long-established, consistent list of 'Event Definitions' in football that are adhered to across all data collection centres. You can find the most up-to-date definitions in the [Opta Glossary](#) (opens the Opta website), where we maintain an up-to-date list of the main football events logged by Opta.

► **SHOW/HIDE: event typeld | name | description | associated qualifierId values**

Qualifier Types

Qualifiers are linked to Event Types and provide more detailed information about the specific event that occurred. Each event can have a series of qualifiers describing it.

The Event Type ID classifies the general event type (such as a Pass event: `"typeId": 1`).

The Qualifier array provides further details (such as pitch coordinates or the type of Pass event) - it contains the following:

- `qualifierId` - this represents the specific event. For example, the type of Pass event, such as a 'Through Ball' (`"qualifierId": 4`).
- `value` - contains any related information. For example, pitch coordinates for the pass start point and pass end point.

Use this table to look-up a Qualifier ID and its description. You should also cross-reference any related Event Type ID values with the [Event types list](#), and check the [Appendix](#) to get more information about the following: [Pitch coordinates and direction of play](#) | [Goalmouth coordinates](#) | [Pitch zones](#) | [Playing positions](#) | [Formations Explained](#) | [Kit IDs](#)

► **SHOW/HIDE: qualifierId | name | associated event typeld values**

Useful Queries

► **SHOW/HIDE: Type_id | outcome | qualifier_id | Extra info | Excluding Events These Qualifiers:**

Appendix

This section helps give further context to some Events and their Qualifiers, such as pitch coordinates and other data. Click on the buttons below to view each section.

Appendix 1 - Pitch Coordinates And Direction Of Play

► **SHOW/HIDE**

Appendix 2 - Goalmouth Coordinates

► **SHOW/HIDE**

Appendix 3 - Pitch Zones

▶ **SHOW/HIDE**

Appendix 4 - Playing Positions

▶ **SHOW/HIDE**

Appendix 5 - Formations Explained

▶ **SHOW/HIDE**

Appendix 6 - Kit IDs

▶ **SHOW/HIDE**

Appendix 7 - Coordinates Transformation

▶ **SHOW/HIDE**