

Last modified on

Sports Data Soccer API - Match Momentum Feed (MA27)

Get match momentum feed data on the swing of the match

Overview

The Soccer **Match Momentum feed** provides information on the swing of the match and on what team is predominant. In addition, the following key events are added:

- Goals
- Cards
- Penalties
- Substitutions

For more details refer: <https://www.theanalyst.com/eu/2021/11/what-is-match-momentum/>

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Contact your Stats Perform representative for a full list of available comps.

UPDATED	POLLING FREQUENCY
Every minute whilst the match is in-flight and at every start/stop of the period	Once 1 day prior to the fixture start date/time and then once every 45 seconds upon KO thereafter

Match Momentum (MA27) Guide

USAGE	FEED
GET match momentum data for the match and the predominant team	/soccerdata/predictions/momentum/{outletAuthKey

If your request URL is as follows (does not contain a mandatory fixture UUID), the feed returns an error:
/soccerdata/predictions/momentum/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/momentum` feed by a fixture (match) UUID.

Legacy IDs: You can use the `fx` query parameter to filter by an Opta legacy ID (only one ID is supported - you cannot specify a comma-separated list of IDs).

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example `GET` requests (rather than `cURL`, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you **MUST** use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Parameter	Value and description
fixture Uuid	GET momentum data for a match by the fixture UUID (as specified, URL path parameter). GET https://api.performfeeds.com/soccerdata/predictions/momentum/{outletAuthKey}/{fixtureUuid?_rt={mode}&_fmt={dataFormat}
fx	GET momentum data for the specified fixture . Pass the fixture/match UUID to the <code>fx</code> parameter. GET https://api.performfeeds.com/soccerdata/predictions/momentum/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&fx={fixtureUuid}

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML](#)
- [JSON](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<matchMomentum> (XML only)

▶<matchInfo>

▶<description>

▶<sport>

▶<ruleset>

▶<competition>

▶<country>

▶<tournamentCalendar>

▶<stage>

▶<series>

▶<contestants> (XML only)

▶<contestant>

▶<country>

▶<venue>

▶<liveData>

▶<matchDetails>

▶<periods> (XML only)

▶<period>

▶<scores>

▶<ht>

▶<ft>

▶<total>

▶<predictions>

▶<prediction>

▶<goal>

▶<missedPen>

▶<card>

▶<substitute>

▶<lineUp>

▶<player>

▶<teamOfficial>

▶<matchDetailsExtra>

▶<matchOfficial>