

Last modified on

Sports Data Soccer API - Match Reference Feed (MAR)

Get a list of matches from your requested feed that have been updated since a date/time specified by you

Overview

The Soccer **Match Reference feed** provides a way for you to find which matches have been updated since a certain point in time. This allows you to limit and refine the number of calls you need to make to your data feed, which will also improve performance.

Currently, this is available only for the following feeds:

- Fixtures And Results (MA1)
- Match Stats (MA2)
- Match Events (MA3)
- Match Preview (MA8)
- Match Expected Goals (MA12)
- Possession Events (MA13)
- Match Events Possession Value (MA32)
- Enriched Soccer Events Remote (MA35)
- Enriched Soccer Event In-Venue (MA36)
- Remote Aggregated Fitness (MA44)
- In Venue Aggregated Fitness (MA45)
- Match Tracking EPTS - Remote (MA49)
- In-Venue Aggregated Runs Feed (MA54)
- Remote Aggregated Runs Feed (MA55)
- In-Venue Aggregated Phases Feed (MA56)
- In-Venue Aggregated Phases Feed (MA57)
- In-Venue Player Runs Feed (MA58)
- Remote Player Runs Feed (MA59)
- In-Venue Phases Of Play Feed (MA60)
- Remote Phases Of Play Feed (MA61)

What is the benefit? It streamlines the queries while improving performance and latency, because you are able to know in which specific matches there have been updates - this is instead of polling a feed (such as MA3 or MA13) for a whole or multiple competition/s or tournament calendar/s and checking each individual match to find out.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our [FAQs](#). We also recommend that you take a look at our [API Overview and Authentication Guide](#). You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
Updates on any update to match data in a feed	Every 30-60 seconds. The feed only accepts a maximum value range from the current time of your request (currentTime) - 36 hours							

Getting Updated Data And Making Streamlined Requests

This feed allows you to see which matches have been updated since a specified date/time, and is intended to benefit and streamline your use of the SDAPI, reduce your polling overheads, and improve latency and overall performance. This allows you to return and ingest only the data that has changed in a specific time period from a feed, instead of checking and receiving all data.

Match Reference (MAR) Guide

USAGE	FEED
GET match reference data for updated matches for the specified feed by a specified reference delta date/time	/soccerdata/match

If your request URL is as follows (does not contain mandatory query parameters and criteria), the feed returns an error: /soccerdata/matchreference/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed also makes use of the [Global query parameters](#), and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the **/matchreference** feed using the below parameters.

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL ({protocol}://{requestDomain}/{feedResource}), in the [main guide](#) and [API Overview and Authorisation guide](#).

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid {outletAuthKey} this must be after the Outlet Authentication Key (and endpoint, if applicable). for

`_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.

- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or `-` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{}` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
<code>_rdlt</code> + <code>type</code>	Get a match reference list for matches updated since a particular date/time (where data has changed) for the specified type of feed. • <code>type</code> - pass the feed code to the parameter. Values: <code>ma3</code> , <code>ma13</code> or <code>ma49</code> (case-sensitive) • <code>_rdlt</code> - pass the date/time to the parameter. Values: Use <code>{xsd:dateTime}</code> (with timezone) or <code>{milliseconds}</code> (since the epoch) to specify the date and time. The format of the date/time for XSD UTC/GMT is: <code>YYYY-MM-DDThh:mm:ssZ</code> Important: The parameter (and feed) only accepts a maximum value range from the current time of your request (currentTime) - 36 hours. If the value exceeds maximum value, error code <code>10213</code> is returned (and HTTP 400). <pre>GET http://api.performfeeds.com/soccerdata/matchreference/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&_rdlt={dateTime}&type={feedCode}&{queryParameters}</pre>
<code>_pgNm</code> + <code>_pgSz</code>	GET data only in the specified page number. All results are returned in pages. <code>_pgNm</code> - Specify the <code>{pageNumber}</code> to return - indexed from <code>1</code> . If this value is not provided, then page 1 is returned by default. <code>_pgSz</code> - Specify the size of the page to return - the number of match definitions in a page. Valid <code>{pageSize}</code> values depend on the operating mode of an outlet. .The maximum value is <code>50</code> (default is 50). <pre>GET http://api.performfeeds.com/soccerdata/matchreference/{outletAuthKey}?&_pgNm={pageNumber}&_pgSz={pageSize}&{queryParameters}&_rt={mode}&_fmt={dataFormat}</pre>

Sample Calls

These sample calls let you see an example of how to format the URL - click on the links below (opens in a new window).

Note: You will receive error code `10213` in the feed response because these sample URLs contain a `_rdlt` date/time value that exceeds the maximum specification of the feed (currentTime - 36 hours). Click on the buttons below to see examples of the feed response when the call is successful (date/time value is within specification).

- XML - MA3 feed
- JSON - MA3 feed

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<matchReference>(XML) or type (JSON)

▶<matchInfo>