

Last modified on

Sports Data Soccer API - Match Stats Points Feed (MA17)

Get detailed OPTA point scores and related match statistics for teams and each individual player, including the passes, shots, crosses, tackles and more.

Overview

The Soccer **OPTA Points Match feed** contains the point score and detailed match statistics for teams and each individual player - this includes Passes, Shots, Crosses, Tackles and much more. You can see a complete list of **match statistic types** in this guide.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you do not exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY
	TIER 13
Updated on stops in play during the game, including for the following types of events: goal, shot at goal, assist, free kick, offside given, cards, corner won, corner lost, substitution, lineup	No more frequently than one URL poll every 30 seconds for range: <KO - 1h; KO + 4h> Up to 1-hour interval for range: <KO + 4h; KO + 8h> Up to 24-hour interval 8h+ of match ending, lasting a maximum of 7 days

Match Points (MA17) Guide

USAGE	FEED
GET Opta Points for a list of fixtures	/soccerdata/matchstatspoints/{out...
GET Opta Points for a fixture by fixture UUID (path parameter)	/soccerdata/matchstatspoints/{out...
GET Opta Points for one or more fixtures by UUID (fx parameter -supports legacy IDs)	/soccerdata/matchstatspoints/{out... {queryParameters}

If your request URL is as follows (does not contain the fixture UUID query criteria), the feed returns an error:
 /soccerdata/matchstatspoints/{outletAuthKey}

How can I get fixture and other entity UUIDs?

Use the **Tournament Calendar (OT2)** or **Fixtures and Results (MA1)** feeds to get fixture metadata, including UUIDs for each fixture and its linked contestants, competition, tournament calendar and other entities.

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the **/matchstatspoints** feed by a fixture (match) UUID.

Legacy IDs: You can use the **fx** query parameter to filter by legacy IDs.

Includes the relevant statistics to calculate the Opta Points plus the calculated point value (not all stats like the MA2 feed). Statistics are broken down into periods to allow the user to create player points per period, for regular time, over time or full time. based on the demanded output.

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example **GET** requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid **{outletAuthKey}** this must be after the Outlet Authentication Key (and endpoint, if applicable). for **_rt={mode}** (operating mode) and **_fmt={dataFormat}** (response format). If required, it should also include an entity UUID (such as a fixture/match UUID).
- Begin the query parameter string with **?** (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the **&** (ampersand) operator. Values must be separated by the correct operator, for example **&** (multiple values, 'AND'), or - if a parameter supports it - **,** (multiple values, 'OR') or **!** ('NOT').
- Use the required **_** (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces **{ }** from your calls (we include these as an example only).
- If using the JSONP format (**_fmt=jsonp**) you **MUST** use it in combination with the callback parameter (**_clbk**) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
tmc1 + week	GET statistics and Opta Points by tournament calendar and game week . Pass the tournament calendar UUID to the tmc1 parameter, and week value (<i>positive integer</i>) to the week parameter.

Query parameter	Value and description
	<pre>GET https://api.performfeeds.com/soccerdata/matchstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmc1={tournamentCalendarUuid}&week={weekNumber}</pre>
<code>tmc1 + week + status</code>	GET statistics and Opta Points by tournament calendar, game week and match status. Pass the tournament calendar UUID to the <code>tmc1</code> parameter, week value (<i>positive integer</i>) to the <code>week</code> parameter, and match status to <code>status</code> parameter. Available match status values: <code>Fixture</code>, <code>Played</code>, <code>Playing</code>, <code>Cancelled</code>, <code>Postponed</code>, <code>Suspended</code>, <code>All</code> (default) <pre>GET https://api.performfeeds.com/soccerdata/matchstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmc1={tournamentCalendarUuid}&week={weekNumber}&status={statusType}</pre>
<code>fx</code>	GET statistics and Opta Points for one fixture or multiple fixtures. - To return one fixture: Pass a fixture UUID or legacy Opta match ID to the <code>fx</code> parameter. - To return multiple fixtures: Pass the fixture UUIDs in a comma-separated list to the <code>fx</code> parameter. For the B2B outlet request type (<code>_rt=b</code>) you can pass up to 50 UUIDs, while a B2C request (<code>_rt=c</code>) allows up to 20 UUIDs. Multiple legacy Opta and Opta Core match IDs are not supported. <pre>GET https://api.performfeeds.com/soccerdata/matchstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&fx={fixtureUuid}</pre>
<code>fixture/match UUID</code>	GET statistics and Opta Points for one fixture by passing the fixture/match UUID as a path parameter (the asset/resource) in the URL. <pre>GET https://api.performfeeds.com/soccerdata/matchstatspoints/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}</pre>
<code>detailed</code>	GET statistics and Opta Points including extended list of (detailed) statistics that are used to calculate the Opta Points value. . Pass a value of <code>yes</code> or <code>no</code> (default) to the <code>detailed</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/matchstatspoints/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&detailed={yes no}</pre>
<code>people</code>	Get statistics and Opta Points for all people within a team (default) or teams only. Pass a value of <code>yes</code> (default, returns all people) or <code>no</code> (teams only, not people) to the <code>people</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/matchstatspoints/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&people={yes no}</pre>
<code>_lcl=en-op</code>	GET assets with the Opta namings in English in the response (instead of Opta Core namings). When the call does not include the <code>_lcl=en-op</code> parameter-value, the feeds will continue to work as they do currently; one example is that the response will be in the default language of English unless the call contains the <code>_lcl</code> parameter and a locale code value to request the response in a different locale/language. Note: You can use this parameter in combination with other valid parameters and values in

Query parameter	Value and description
	the request. However, you cannot use it in combination with a locale/language code and <code>_lcl</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/matchstatspoints/{outletAuthKey}/{fixtureUui d}?_rt={mode}&_fmt={dataFormat}&_lcl=en-op&{queryParameters}</pre>
<code>_pgNm</code> + <code>_pgSz</code>	GET data only in the specified page size and/or page number. All results are returned in pages and these parameters help limit the page size in order to optimise the efficiency of the SDAPI. • <code>_pgNm</code> - Specify the <code>{pageNumber}</code> to return - indexed from <code>1</code>. If this value is not provided, then page 1 is returned by default. • <code>_pgSz</code> - Specify the size of the page to return - the number of match definitions in a page. Valid <code>{pageSize}</code> values depend on the operating mode of an outlet. For B2B requests, the maximum value is <code>1000</code> (default is 20). For B2C requests, the maximum value is <code>50</code> (default is 20). <pre>GET https://api.performfeeds.com/soccerdata/matchstatspoints/{outletAuthKey}/{fixtureUui d}?_rt={mode}&_fmt={dataFormat}&_pgSz={pageSize}&_pgNm={pageNumber}&{queryParameters}</pre>
<code>top</code>	GET statistics and Opta Points only for people with the highest Opta Points value. The result will contain players with statistic <code>matchRank</code> $\leq$ <code>top</code>. Pass the top value (positive integer) to the top parameter <pre>GET https://api.performfeeds.com/soccerdata/matchstatspoints/{outletAuthKey}/{fixtureUui d}?_rt={mode}&_fmt={dataFormat}&top={topValue}</pre>

Do not supply both the `_lcl` (with a locale/language code value) and `_lcl=en-op` in the same call - this is not supported; otherwise, the feed will return an error and code `10203` (Ambiguous/Invalid request parameters) in the response due to a duplicated `_lcl` parameter.

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML - single game](#)
- [XML - season \(tmcl\), week](#)
- [JSON - fx by Opta ID](#)
- [JSON - season \(tmcl\), detailed, top](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<matchesStatsPoints> (XML only)

▶<matchStatsPoints>

▶<matchInfo>

▶<description>

▶<sport>

▶<ruleset>

▶<competition>

▶<country>

▶<tournamentCalendar>

▶<stage>

▶<series>

▶<contestants> (XML only)

▶<contestant>

▶<country>

▶<venue>

▶<liveData>

▶<matchDetails>

▶<periods> (XML only)

▶<period>

▶<suspensions>

▶<suspension>

▶<scores>

▶<ht>

▶<ft>

▶<et>

▶<pen>

▶<total>

▶<totalUnconfirmed>

▶<aggregate>

▶<goal>

▶<missedPen>

▶<card>

▶<substitute>

▶<VAR>

▶<penaltyShootout>

▶<penaltyShot>

▶<lineUp>

▶<teamOfficial>

▶<player>

▶<stat>

▶<teamOfficial>

▶<teamStats>

▶<stat>

▶<matchDetailsExtra>

▶<attendance>

▶<awayAttendance>

▶<matchOfficials>(XML only)

▶<matchOfficial>

Statistic Types

Statistics are delivered under the **stats** object and split into the following elements (where available):

- **team** (contestant)
- **player** (in the team)
- **combinedTeamStats** (a total sum of statistics for each team)

Within these elements, each statistic is shown as a **stat** and its **type** and **value** will appear under it, if it is available. For example, the **yellowCard** stat type would only appear if a yellow card was awarded to a contestant (team) or player (it would not appear if a yellow card was not awarded).

Note:

- **shotOffTarget** = includes all the miss and post events/stat types. Calculated as `attOboxMiss + attIboxMiss + attOboxPost + attIboxPost` (= `shotOffTarget`)
- **total number of missed shots** = shots that went wide or over. Calculated as either a) `attIboxMiss + attOboxMiss` , OR b) `shotOffTarget - postScoringAtt`

Click on the buttons below to see the complete lists of contestant (team) and player statistics.

Contestant/Team Stats

For these stats, the value will be an *integer* with the exception of `formationUsed` which can have an *integer*, or a *string* such as `Unknown` .

►Contestant/Team stats - names and descriptions

Player Stats

For these stats, the value will be an *integer* with the exception of `formationPlace` which can have a *positive integer*, or `0` or a *string* such as `Unknown` .

►Player stats - names and descriptions

The Opta Points - Explained

The comprehensive player metric for soccer that evaluates a player's overall contribution to the game.

The scoring system distinguishes only between field players and goalkeepers, assigning the same number of points to all field players for corresponding actions. A distinctive feature of this system is its exclusive focus on in-game actions, refraining from awarding points for post-game performances, such as securing a victory or allocating bonus points for maintaining a clean sheet.

Positive actions (goals, passes, tackles, etc...) will add to a player's score and, conversely, negative actions (cards, own goals, goals conceded) will reduce a player's points total. Theoretically, a player's points value is unlimited, and players can conclude a game with negative points. However, players who complete the full game duration on the field typically end up with a point total ranging from 10 to 40 points.

Goals (G)

STATS	PLAYER	GOALKEEPER	TOTAL POINTS
Goals (G)	10	10	14 (G+SOnT)
Shots on target (SOnT)	4	4	
Shots off target (SOffT)	2	2	
Blocked shots (BS)	2	2	
Own goal (OG)	-5	-5	
Assists (A)	6	6	
Passes (P)	0.2	0.2	

STATS	PLAYER	GOALKEEPER	TOTAL POINTS
Crosses (C)	0.2	0.2	
Tackles (Tk)	2	2	
Interceptions (INT)	2	2	
Fouls won (FW)	1	1	
Fouls conceded (FC)	-1	-1	
Offsides (O)	-1	-1	
Yellow cards (YC)	-2	-2	
Red cards (RC)	-5	-5	
Goals conceded (GC)	-1	-6	
Penalties won (PW)	4	4	
Saves (SAV)		5	
Pen Saved (PS)		5	10 (SAV+PS)

Assists

The final touch from a teammate, which leads to the recipient of the ball scoring a Goal. If the assist is deflected by an opposition player, it must be deemed as travelling to the Goal-scorer irrespective of the deflection. In the event of an own Goal, direct free kick Goal and direct corner Goal, an assist will not be awarded. This same rule applies to penalties unless the penalty taker chooses to pass the ball for another player to score.

Cards

Cards are collected as yellow, 2nd yellow or red card. We cross-check cards against official sources to match the official statistics and will align our collection unless there is recognition of a clear error.

Crosses

A ball played from a wide position targeting a teammate(s) in a central area within proximity to the Goal. The delivery must have an element of lateral movement from a wider position to more central area in front of Goal.

Foul Won

A Foul Won is defined when a player wins a free kick or penalty for their team after being fouled by an opposing player. There are no fouls won for a handball, dive, back pass, illegal restart, dissent, GK 6-second violation or obstruction where a free kick is conceded.

Foul Conceded

A Foul Conceded is defined as any infringement penalised as foul play by a referee that results in a free-kick or penalty event. Offsides are not given as a foul conceded. Incidents where a match official has played advantage and

subsequently cautioned a player, do not contribute towards the total foul count for the player or team. In these scenarios a free-kick or penalty event must occur for a foul to be awarded.

Goal/Own Goal

Attributing a Goal to the Goal scoring player, or in the case of an Own Goal, to the defending player. Given any contention around assigning a Goal to an appropriate player, Opta will apply their own rules, and when applicable will align decisions to the relevant official competition, governing body.

Interception

This is where a player reads an opponent's pass and intercepts the ball by moving into the line of the intended pass.

Offside

An event attributed to the player deemed to be in an offside position when a free kick is awarded. If two or more players are in an offside position when the ball is played, the player considered to be most actively involved is given offside.

Passes

The attempted delivery of the ball from one player to another player on the same team. A player can use any part of their body (permitted in the laws of the game), to execute a pass. Event categorisation includes open play passes, Goal kicks, corners and free kicks played as a pass. Crosses, keeper throws, and throw ins do not count as a pass.

Penalty (Won, Conceded And Taken)

Attributing a series of sequential penalty events to both appropriate team and player. Collection comprising; Penalty Won, Penalty Conceded and Penalty Taken.

Shot

A shot is defined as any goal attempt.

Shot On Target

A deliberate attempt to score that is on target. Includes all Goals being scored and shots on target saved by the Goalkeeper. It also includes shots on target that are Blocked by a last line defending player, preventing the ball from entering the Goal. Also See 'Shot Off Target.'

Shot Off Target

A deliberate attempt to score that misses the target, without contact from a player diverting the ball from on target to off target. A shot hitting the frame of the Goal is classified as a Shot Off Target unless the ball subsequently enters the net. A Blocked Shot is not classified as a Shot Off Target. Also see 'Shot on Target.'

Tackle

A tackle is defined when a player connects with the ball in a legal, ground level challenge and successfully takes the ball away from the opposition player. The tackled player must be in controlled possession of the ball to be tackled by an

opposition player. Both Tackle Won and Lost are categorised as tackles, but the outcome of the tackle (won or lost) is different based on where the ball goes after the tackle.

Save

A Goalkeeper preventing the ball from entering the Goal with any part of their body when facing an intentional attempt from an opposition player.

Saves have the following attributes:

- Body part - Hands/Feet/Body/Fist.
- Save type - Caught/Collected/Parried Safe/Parried/Fumble.
- Goalkeeper position - Diving/Standing/Sliding/Reaching/Stooping Danger area/Fingertip.

This includes:

- Unintentional or misplaced efforts on target from a Goalkeeper's own teammates, but only if the intervention is not perceived to be a routine collection of the ball.
- If after a Goalkeeper's intervention, a more prominent defensive action from a teammate prevents the ball from entering the Goal, this will be categorised as a Block for the teammate, not a Save for the Goalkeeper.
- If the ball goes behind the Goal because of a Goalkeeper intervention, the match officials must award a corner for it to be recognised as a Save.

Penalty Save

A Goalkeeper preventing the ball from entering the Goal with any part of their body when facing a penalty from an opposition player.