

Last modified on

Sports Data Soccer API - NLG Dynamic Player Bios Feed (PE9)

Get a summary of top-level player information combined with seasonal statistics with dynamic context and team/schedule information.

Overview

NLG stands for Natural Language Generation. It is an automated system that creates textual editorial content from raw data. In the Soccer **NLG Dynamic Player Bios feed**, we provide a player biography that updates after every match round of a domestic league and uses high-end data collection available for over 70 leagues (domestic leagues collected from Opta Data Tiers 9, 10, 11, 13). It gives a headline view of a player's season to date, details of the last match they played in the domestic league, headline stats of their career in that domestic league, position-specific stats (clean sheets for a goalkeeper, for example) as well as details of their debut in that domestic league.

It is 'dynamic' for two reasons: the data will update, plus the NLG template is built in a way where the text elements will also change. No two pieces of NLG content we create will ever read exactly the same.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATES AND POLLING FREQUENCY

The bios will be updated after every game.

NLG Dynamic Player Bios (PE9) Guide

USAGE	FEED
GET a dynamic player bio by person, person UUID, or contestant UUID in XML or JSON.	/soccerdata/nlgdynamicplayerbio/{ou

If your request URL is as follows - that is, it does not contain a person/contestant UUID AND `_lc1` parameter and value - the feed returns an error:
`/soccerdata/nlgdynamicplayerbio/{outletAuthKey}?_fmt={dataFormat}&_rt={mode}`

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/nlgdynamicplayerbio` feed by a specific person/contestant UUID and include the `_lc1` parameter and a **valid locale value**.

Legacy IDs: You can use the `prsn` and `ctst` parameters to filter by legacy IDs - only one ID is supported (you cannot pass multiple IDs in a comma-separated list).

How to use query parameters and make successful requests:
In our guides, we use HTTPS syntax for our example `GET` requests (rather than `cURL`, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you **MUST** use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
<code>personUuid + _lc1</code>	GET Dynamic Player Bio NLG data by the specified person UUID (inline path parameter method). Pass the person UUID in the request URL directly as the <code>{assetId}</code> (asset/resource ID), and the

Query parameter	Value and description
	locale value (for example, <code>_lcl=en-gb</code>) to the <code>_lcl</code> parameter (mandatory). Note: By default, only club data is returned. <pre>GET https://api.performfeeds.com/soccerdata/nlgdynamicplayerbio/{outletAuthKey}/{personUuid}?_rt={mode}&_fmt={dataFormat}&_lcl={value}</pre>
<code>prsn + _lcl</code>	GET Dynamic Player Bio NLG data by the specified person UUID (query parameter method). Pass the person UUID to the <code>prsn</code> parameter, and the locale value (for example, <code>_lcl=en-gb</code>) to the <code>_lcl</code> parameter (mandatory). Note: By default, only club data is returned. <pre>GET https://api.performfeeds.com/soccerdata/nlgdynamicplayerbio/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&prsn={personUuid}&_lcl={value}</pre>
<code>ctst + _lcl</code>	GET Dynamic Player Bio NLG data by the specified contestant UUID (query parameter method). Pass the contestant UUID to the <code>ctst</code> parameter, and the locale value (for example, <code>_lcl=en-gb</code>) to the <code>_lcl</code> parameter (mandatory). <pre>GET https://api.performfeeds.com/soccerdata/nlgdynamicplayerbio/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}&_lcl={value}</pre>
<code>personUuid + bioType</code>	GET Dynamic Player Bio NLG data by the specified person UUID & bio type. Possible values for <code>bioType</code> are <i>national</i> and <i>club</i>. If you are subscribed to this data, calling the API with <i>national</i> <code>bioType</code> will return international bios for the queried person. If <i>club</i> <code>bioType</code> is called, then the API will return only club data. Note: if no param is passed, then by default only club data is returned. <pre>GET https://api.performfeeds.com/soccerdata/nlgdynamicplayerbio/{outletAuthKey}/{personUuid}?_rt={mode}&_fmt={dataFormat}&_lcl={value}&bioType={value}</pre>
<code>_pgNm + _pgSz + ctst</code>	GET Dynamic Player Bio NLG data using the page size and/or page number for the parameter <code>ctst</code>. All results are returned in pages and these parameters help limit the page size in order to optimise the efficiency of the SDAPI. <code>_pgNm</code> - Specify the <code>{pageNumber}</code> to return - indexed from <code>1</code>. If this value is not provided, then page 1 is returned by default. <code>_pgSz</code> - Specify the size of the page to return - the number of match definitions in a page. Valid <code>{pageSz}</code> values depend on the operating mode of an outlet. The maximum value is <code>50</code> (default is 50). <pre>GET https://api.performfeeds.com/soccerdata/nlgdynamicplayerbio/{outletAuthKey}?ctst={contestantUuid}&_rt={mode}&_fmt={dataFormat}&_lcl={language code}&_pgSz={x}&_pgNm={y}</pre>

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- XML - `person UUID (path parameter)`
- JSON - `person UUID (path parameter)`
- XML - `ctst`

- JSON - ctst

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<nlgDynamicPlayerBio> (XML only)

▶<person>

▶<membership>

▶<stat>

▶<messages>

▶<message>