

Last modified on

Sports Data Soccer API - Other Rankings Feed (TM19)

Get latest rankings data for teams in a custom ranking type.

Overview

The Soccer **Other Rankings feed** provides team ranking information outside of standard match and seasonal statistics.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY
Once a day	

Other Rankings (TM19) Guide

USAGE	FEED
GET otherrankings data according to ranking type in a year/month/week	/soccerdata/otherrankings/{outletAuthKey}?{queryParameters}

Query Parameters And Example Request Parameters

This feed makes use of the **Global query parameters** and you can use the following query parameters. See also: **Using Query Parameters** and **Global query parameters** for a guide.

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the [main guide](#) and [API Overview and Authorisation guide](#).

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format). If the feed/call requires it, it should also include an entity UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{}` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
type	Get latest rankings data for the requested ranking type. <pre>GET https://api.performfeeds.com/soccerdata/otherrankings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&type={rankingType}</pre>
type + year	Get latest rankings data for the requested ranking type in a year. <pre>GET https://api.performfeeds.com/soccerdata/otherrankings/{outletAuthKey}?type={rankingType}_rt={mode}&_fmt={dataFormat}&year={year}</pre>
type + year + month	Get latest rankings data for the requested ranking type for the year and month. <pre>GET https://api.performfeeds.com/soccerdata/otherrankings/{outletAuthKey}?type={rankingType}_rt={mode}&_fmt={dataFormat}&year={year}&month={month}</pre>
type + year + week	Get latest rankings data for the requested ranking type for the year and week. <pre>GET https://api.performfeeds.com/soccerdata/otherrankings/{outletAuthKey}?type={rankingType}_rt={mode}&_fmt={dataFormat}&year={year}&week={week}</pre>

Note: URI strings contain the correct case and operators. Make sure you supply the following information in the URL or header and that it is correct for your outlet; otherwise, an error will be returned: `_rt={mode}` (operating

```
mode); {outletAuthKey} (Outlet Authentication Key); _fmt={dataFormat} (format), and at least the ranking type ( type ) parameter and value.
```

Sample File

XML - Fifa Rankings

Feed Output

Here, you can find an explanation of the response fields and data based on the example request and response. This is in XML but the feed response fields are similar for JSON.

▶<otherRankings> (XML only)

▶<type>

▶<ranking>