

Last modified on

Sports Data Soccer API - Person Reference Feed (PER)

Get a list of people from your requested feed that have been updated since a date/time specified by you.

Overview

The Soccer **Person Reference Feed** provides a way for you to find the person level feed have been updated since a certain point in time. This allows you to limit and refine the number of calls you need to make to your data feed, which will also improve performance.

Currently, this is available only for the following feeds:

- Player career (PE2)
- Injuries (PE7) at the person level
- Player contract (PE12)

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our [FAQs](#). We also recommend that you take a look at our [API Overview and Authentication Guide](#). You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

POLLING FREQUENCY

Every 60 seconds. The feed only accepts a maximum value range from the current time of your request (currentTime) - 36 hours

Person Reference (PER) Guide

USAGE	FEED
GET person reference information according to specified parameter values	/soccerdata/personreference/{outletAuthKey}

If your request URL is as follows (does not contain this query criteria), the feed returns an error:
/soccerdata/personreference/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed makes use of the **Global query parameters** and you can use the following query parameters. You must query the `/personreference` feed by a specific UUID of a person or contestant (team) - you can combine additional query parameters in a request. See also: [Using Query Parameters](#) and [Global query parameters](#) for a guide.

How to use query parameters and make successful requests:
In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL ({protocol}://{requestDomain}/{feedResource}), in the [main guide](#) and [API Overview and Authorisation guide](#).

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid {outletAuthKey} this must be after the Outlet Authentication Key (and endpoint, if applicable). for _rt={mode} (operating mode) and _fmt={dataFormat} (response format), entity query parameter and UUID.
- Begin the query parameter string with ? (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the & (ampersand) operator. Values must be separated by the correct operator, for example & (multiple values, 'AND'), or - if a parameter supports it - , (multiple values, 'OR') or ! ('NOT').
- Use the required _ (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces {} from your calls (we include these as an example only).
- If using the JSONP format (_fmt=jsonp) you MUST use it in combination with the callback parameter (_clbk) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
_rdlt + type	Get person reference list for person type feed updated since a particular date/time (where data has changed) for the specified type of feed. • type pass the feed code to the parameter. Values: active parameter. Values: pe2 , pe7 , pe12 • _rdlt pass the date/time to the parameter. Values: Use {xsd:dateTime} (with timezone) or {milliseconds} (since the epoch) to specify the date and time. The format of the date/time for XSD UTC/GMT is: YYYY-MM-DDThh:mm:ssZ

Query parameter	Value and description
	Important: The parameter (and feed) only accepts a maximum value range from the current time of your request (currentTime) - 36 hours. If the value exceeds maximum value, error code 10213 is returned (and HTTP 400). GET https://api.performfeeds.com/soccerdata/personreference/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&_rdlt={dateTime}&type={feedCode}&{queryParameters}
_pgNm + _pgSz	GET person reference list for person type feed by specifying pagination parameters. _pgNm - Specify the {pageNumber} to return - indexed from 1 . If this value is not provided, then page 1 is returned by default. _pgSz - Specify the size of the page to return - the number of match definitions in a page. Valid {pageSize} values depend on the operating mode of an outlet. .The maximum value is 50 (default is 50). GET https://api.performfeeds.com/soccerdata/personreference/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&_pgSz={pageSize}&_pgNm={pageNumber}&{queryParameters}

Sample Calls (Coming Soon)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<personReference>

▶<personInfo>