

Last modified on

Sports Data Soccer API - Player Career Feed (PE2)

Get information about the current and past memberships of players and teams, with very basic season statistics included.

Overview

The Soccer **Player Career feed** provides information on the current and past memberships of players and teams, with very basic season statistics included.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
Updated on any change to player, team, season, season stats, area, competition or transfer	Updated once a day at the end of the given match day							

Player Career (PE2) Guide

USAGE	FEED
GET player career information according to specified parameter values	/soccerdata/playercare
GET player career information for the specified person UUID only (path parameter/resource ID method)	/soccerdata/playercare

If your request URL is as follows (does not contain this query criteria), the feed returns an error:
 /soccerdata/playercareer/{outletAuthKey}

Coverage

The call to the Player Career feed makes extensive use of the Opta Core player database, which we began to populate in the 2006-2007 season. Over time, we have added more leagues and players and now have a comprehensive record of current players worldwide; this feed allows customers to trace their career across multiple seasons.

For some of the biggest leagues and players in the world, we have also 'backfilled' our database to include player records from before 2006. However, customers should be aware that the database is not complete and details of some current players' careers could be missing. There may be instances where we may not have recorded the start of a player's career as a particular league may not have been covered at the time, also there may also be instances where there could be a gap in a career if a player moved to a competition which was not covered. Additionally, there may be a small number of instances where we only recorded player data from a small part of a season (for example a set of season-ending play-offs); in these instances, a player's data will be incomplete for that season.

Contact optasupportdesk@statsperform.com if you need any further clarification.

Query Parameters And Example Request Parameters

This feed makes use of the **Global query parameters** and you can use the following query parameters. You must query the `/playercareer` feed by a specific UUID of a person or contestant (team) - you can combine additional query parameters in a request. See also: [Using Query Parameters](#) and [Global query parameters](#) for a guide.

Legacy IDs: You can combine parameters for `prsn` and `ctst` to filter by legacy IDs.

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example `GET` requests (rather than `cURL`, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the [main guide](#) and [API Overview and Authorisation guide](#).

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{}` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you **MUST** use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
prsn	Get player career data for a specific person (a player). Pass the person UUID to the prsn parameter. <pre>GET https://api.performfeeds.com/soccerdata/playercareer/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&prsn={personUuid}</pre>
{personUuid} (path parameter)	Get player career data for a specific person (a player). Pass the person UUID to the prsn parameter. <pre>GET https://api.performfeeds.com/soccerdata/playercareer/{outletAuthKey}/{personUuid}/?_rt={mode}&_fmt={dataFormat}</pre>
ctst	Get all player career data for the specified contestant - the feed returns careers for all players that have/had membership at the contestant. Pass the contestant UUID to the ctst parameter. <pre>GET https://api.performfeeds.com/soccerdata/playercareer/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}</pre>
ctst + active	Get player careers either for players that: - have an active membership at the specified contestant (pass a value of yes (default) to the active parameter) - or: - have had a membership at any time at the specified contestant (pass a value of no to the or parameter) <pre>GET https://api.performfeeds.com/soccerdata/playercareer/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}&active={yes no}</pre>
_lcl=en-op	GET assets with the Opta namings in English in the response (instead of Opta Core namings). When the call does not include the _lcl=en-op parameter-value, the feeds will continue to work as they do currently; one example is that the response will be in the default language of English unless the call contains the _lcl parameter and a locale code value to request the response in a different locale/language. Note: You can use this parameter in combination with other valid parameters and values in the request. However, you cannot use it in combination with a locale/language code and _lcl parameter. <pre>GET https://api.performfeeds.com/soccerdata/playercareer/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&_lcl=en-op&{queryParams}</pre>

Query parameter	Value and description
<code>_pgNm</code> + <code>_pgSz</code> + <code>ctst</code>	GETplayer career data using the page size and/or page number for the parameter <code>ctst</code> . All results are returned in pages and these parameters help limit the page size in order to optimise the efficiency of the SDAPI. <code>_pgNm</code> - Specify the <code>{pageNumber}</code> to return - indexed from <code>1</code> . If this value is not provided, then page 1 is returned by default. <code>_pgSz</code> - Specify the size of the page to return - the number of match definitions in a page. Valid <code>{pageSize}</code> values depend on the operating mode of an outlet. .The maximum value is <code>50</code> (default is 50). <pre>GET https://api.performfeeds.com/soccerdata/playercareer/{outletAuthKey}?ctst={contestantUuid}&active=no&_rt={mode}&_fmt={dataFormat}&_pgSz={x}&_pgNm={y}</pre>

Do not supply both the `_lcl` (with a locale/language code value) and `_lcl=en-op` in the same call - this is not supported; otherwise, the feed will return an error and code `10203` (Ambiguous/Invalid request parameters) in the response due to a duplicated `_lcl` parameter.

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML - prsn](#)
- [XML - person UUID](#)
- [JSON - ctst](#)
- [XML - ctst & active](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

- ▶<playerCareer> (XML only)
- ▶<person>
- ▶<membership>
- ▶<stat>