

Last modified on

Sports Data Soccer API - Player Possession Value Feed (PE10)

Get Possession Values of a player for a particular tournament calendars queried for.

Overview

The Soccer Player Possession Value feed provides all the traditional data such as player, membership and tournamentCalendar details clubbed with new possession value like match information, competition information and team details of all the players and team part of this match, clubbed with new possession value like

totalPossessionValue , totalPlusPV , totalMinusPV , totalPlusPass , totalMinusPass , totalPlusCross , totalMinusCross , totalPlusTakeOns , totalMinusTakeOn , totalPlusSetPlaysTaken , totalMinusSetPlayTaken , totalPlusSetPlaysDrawn , totalMinusSetPlayConceded , totalPlusRegains and totalMinusLosingPossession

For more details refer: <https://www.theanalyst.com/eu/2021/03/what-is-possession-value/>

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our [FAQs](#). We also recommend that you take a look at our [API Overview and Authentication Guide](#). You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY						
	TIER 13	TIER 11	TIER 10	TIER 9	TIER 8	TIER 7	TIER 3
Once per hour or once per minute in case a match that involves the player is "live".							

Player Possession Value (PE10) Guide

USAGE	FEED
GET player possession values by tournamentCalendar in XML or JSON.	/soccerdata/playerpossessionvalues/{outletAuthKey}?prsn={playerUUID}&{queryParameters}

If your request URL is as follows - that is, it does not contain a tournamentCalendar UUID and a person UUID the feed returns an error: /soccerdata/playerpossessionvalues/{outletAuthKey}?_fmt={dataFormat}&_rt={mode}

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the **/playerpossessionvalues** feed by a tournamentCalendar UUID and person UUID.

Legacy IDs: You can use the **fx** parameter to filter by legacy IDs - only one ID is supported (you cannot pass multiple IDs in a comma-separated list).

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL ({protocol}://{requestDomain}/{feedResource}), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid {outletAuthKey} this must be after the Outlet Authentication Key (and endpoint, if applicable). for _rt={mode} (operating mode) and _fmt={dataFormat} (response format), entity query parameter and UUID.
- Begin the query parameter string with ? (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the & (ampersand) operator. Values must be separated by the correct operator, for example & (multiple values, 'AND'), or - if a parameter supports it - , (multiple values, 'OR') or ! ('NOT').
- Use the required _ (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces {} from your calls (we include these as an example only).
- If using the JSONP format (_fmt=jsonp) you MUST use it in combination with the callback parameter (_clbk) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
tournamentCalendarUuid + playerUUID	GET player Possession values by the specified tournament calendar UUID and person UUID . Pass the tournamentCalendar in the request URL directly

Query parameter	Value and description
	GET https://api.performfeeds.com/soccerdata/playerpossessionvalues/{outletAuthKey}?_fmt=xml&tmcl={tournamentCalendarUuid}&prsn={playerUuid}&rt={mode}

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML](#)
- [JSON](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

- ▶<playerPossessionValues> (XML only)
- ▶<person>
- ▶<tournamentCalander>
- ▶<pvCategories>
- ▶<totalPossessionValue>
- ▶<totalPlusPV>
- ▶<totalMinusPV>
- ▶<totalPlusPass>
- ▶<totalMinusPass>
- ▶<totalPlusCross>
- ▶<totalMinusCross>
- ▶<totalPlusTakeOns>
- ▶<totalMinusTakeOn>
- ▶<totalPlusSetPlaysTaken>
- ▶<totalMinusSetPlayTaken>
- ▶<totalPlusSetPlaysDrawn>
- ▶<totalMinusSetPlayConceded>
- ▶<totalPlusRegains>

▶<totalMinusLosingPossession>

▶<membership>

▶<matches>

▶<matchInfo>

▶<competition>

▶<contestants>

▶<contestant>

▶<country>

▶<pvCategories>

▶<totalPossessionValue>

▶<totalPlusPV>

▶<totalMinusPV>

▶<totalPlusPass>

▶<totalMinusPass>

▶<totalPlusCross>

▶<totalMinusCross>

▶<totalPlusTakeOns>

▶<totalMinusTakeOn>

▶<totalPlusSetPlaysTaken>

▶<totalMinusSetPlayTaken>

▶<totalPlusSetPlaysDrawn>

▶<totalMinusSetPlayConceded>

▶<totalPlusRegains>

▶<totalMinusLosingPossession>