

Last modified on

Sports Data Soccer API - Season Expected Goals Feed (TM9)

Get shot information, 'expected goals' and 'expected goals on target' data, cumulative player, and team totals, in any match.

Overview

The Soccer **Season Expected Goals feed** contains all shot events for a single team across an entire competition with Expected Goals and Expected Goals on Target data points. Cumulative shot data (including total shots and Expected Goals total) for the entire team and all players to have featured in any match, within a season.

You can see a complete list of available **Event Types**, **Qualifier Types**, and **Statistic Types** in this guide.

For more details refer: <https://www.theanalyst.com/eu/2021/07/what-are-expected-goals-xg/> and <https://www.theanalyst.com/eu/2022/04/evolving-expected-goals-xg/>

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
Updated after each game that the team is involved in - this is usually sent within 10 minutes of the game ending	See Tier 13	Post-match	n/a	Once per match or at the end of the given match day	n/a	n/a	n/a	n/a

Season Expected Goals (TM9) Guide

USAGE	FEED
GET seasonal expected goals according to specified parameter values <i>Required:</i> Entity UUIDs and query parameters - see the table below.	/soccerdata/seasonexpectedgoals/{outletAuthKey}

If your request URL is as follows (does not contain both a contestant UUID and either a competition UUID or tournament calendar season UUID), the feed returns an error:
/soccerdata/seasonexpectedgoals/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the **/seasonexpectedgoals** feed by a specific contestant UUID and also include either a competition UUID or tournament calendar season UUID.

Legacy IDs: You can use one of the following combinations of query parameters to filter by legacy IDs - these only support one ID per parameter and do not support a comma-separated list of legacy IDs:

- **comp** + **ctst**
- **tmcl** + **ctst**

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL ({protocol}://{requestDomain}/{feedResource}), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid **{outletAuthKey}** this must be after the Outlet Authentication Key (and endpoint, if applicable). for **_rt={mode}** (operating mode) and **_fmt={dataFormat}** (response format), entity query parameter and UUID.
- Begin the query parameter string with **?** (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the **&** (ampersand) operator. Values must be separated by the correct operator, for example **&** (multiple values, 'AND'), or - if a parameter supports it - **,** (multiple values, 'OR') or **!** ('NOT').
- Use the required **_** (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces **{ }** from your calls (we include these as an example only).
- If using the JSONP format (**_fmt=jsonp**) you MUST use it in combination with the callback parameter (**_clbk**) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
comp + ctst	Get season expected goals for a specific contestant in a competition (of a competition). Pass the contestant UUID to the ctst parameter, and competition UUID to the comp parameter. GET https://api.performfeeds.com/soccerdata/seasonexpectedgoals/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&comp={competitionUuid}&ctst={contestantUuid}
tmcl + ctst	Get season expected goals only for a specific contestant in a tournament calendar (of a competition). Pass the contestant UUID to the ctst parameter, and tournament calendar UUID to the tmcl parameter. GET https://api.performfeeds.com/soccerdata/seasonexpectedgoals/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&ctst={contestantUuid}

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML - comp & ctst](#)
- [JSON - comp & ctst](#)
- [XML - tmcl & ctst](#)
- [JSON - tmcl & ctst](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

- ▶<seasonExpectedGoals> (XML only)
- ▶<competition>
- ▶<tournamentCalendar>
- ▶<contestant>
- ▶<stat>
- ▶<player>
- ▶<stat>
- ▶<match>
- ▶<event>
- ▶<qualifier>

Event Types

Events are delivered as an array (under `events` for XML or `events` for JSON). When an event occurs during a match, it is assigned a unique Event ID. For each unique Event ID, there is an associated Event Type ID (`typeId`) which classifies the general event type that has occurred. It is common for an event instance to be accompanied by a Qualifier array (under `qualifier`). Each Qualifier has an ID and a Qualifier ID (`qualifierId`) and value - these explain and add depth and further information about the event. However, it is not mandatory (some events will not have qualifiers).

Use this table to look-up an Event Type ID and its description. You should also cross-reference any related Qualifier ID values with the [Qualifier Types](#) list.

►SHOW/HIDE: [event typeId](#) | [name](#) | [description](#)

Qualifier Types

Qualifiers are linked to Event Types and provide more detailed information about the specific event that occurred. Each event can have a series of qualifiers describing it.

The Event Type ID classifies the general event type (such as a Pass event: `"typeId": 1`).

The Qualifier array provides further details (such as pitch coordinates or the type of Pass event) - it contains the following:

- `qualifierId` - this represents the specific event. For example, the type of Pass event, such as a 'Through Ball' (`"qualifierId": 4`).
- `value` - contains any related information. For example, pitch coordinates for the pass start point and pass end point.

Use this table to look-up a Qualifier ID and its description. You should also cross-reference any related Event Type ID values with the [Event Types list](#), and check the [Appendix](#) to get more information about the following: [Pitch coordinates and direction of play](#) | [Goalmouth coordinates](#) | [Pitch zones](#) | [Assist and keypass interpretation](#) | [<event> tag attributes information](#) | [How events are deleted](#) | [How events are edited/modified](#) | [Period IDs](#)

►SHOW/HIDE: [qualifierId](#) | [name](#) | [descriptions](#)

Statistic Types

Statistics are delivered as individual `stat` elements under the following parent elements (where available):

- `team` (contestant)
- `player` (in the team)

Within these elements, each statistic is shown as a `stat` and its `type` and value will appear under it, if it is available. For example, the `yellowCard` stat type would only appear if a yellow card was awarded to a contestant (team) or player (it would not appear if a yellow card was not awarded).

Click on the buttons below to see the complete lists of contestant (team) and player statistics.

►SHOW/HIDE: [stat type and value descriptions](#)

Appendix

This section helps give further context to some Events and their Qualifiers, such as pitch coordinates and other data. Click on the buttons below to view each section.

Appendix 1 - Pitch Coordinates And Direction Of Play

▶**SHOW/HIDE**

Appendix 2 - Goalmouth Coordinates

▶**SHOW/HIDE**

Appendix 3 - Pitch Zones

▶**SHOW/HIDE**

Appendix 4 - Assist And Keypass Interpretation

▶**SHOW/HIDE**

Appendix 5 - <Event> Tag Attributes Information

▶**SHOW/HIDE**

Appendix 6 - How Events Are Deleted

▶**SHOW/HIDE**

Appendix 7 - How Events Are Edited/Modified

▶**SHOW/HIDE**

Appendix 8 - Period IDs

▶**SHOW/HIDE**