

Last modified on

Sports Data Soccer API - Season Player Ratings Feed (TM10)

Get player ratings for a season, based on a combination of attacking, defending, goalkeeping, passing, possession and shooting.

Overview

The Soccer **Season Player Ratings feed** provides match-by-match and overall seasonal average ratings for a player over a specific season (tournament calendar). The scores will range from 20-100 and an "average" performance will score 60. The seasonal score will average performances and minutes played to give a score of their season overall. A further explanation of the match ratings and index can be found in the specification for the **Match Player Ratings** feed.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY			
	TIER 15	TIER 13	TIER 12+14	TIER 10
The feed is updated on stops in play within the game including the following types of events: Goal, Shot at Goal, Free Kick, Offside Given, Cards, Start Half, End Half, Corner Won, Corner Lost, Substitution	The feed should update approximately every 90 seconds and will be pushed out automatically in event of key actions as above. However, there will always be a gap of at least 30 seconds between updates unless there is a goal scored, in which case an update will be produced immediately. There may be a gap of several minutes between feeds if no key events take place.			

Season Player Ratings (TM10) Guide

USAGE	FEED
GET season player ratings by tournament calendar UUID and contestant UUID	/soccerdata/seasonplayerratings/{outletAuthKey}&{tournamentCalendarUuid}&ctst={contestantUuid}

If your request URL is as follows (does not contain a tournament calendar UUID and contestant UUID), the feed returns an error: /soccerdata/seasonplayerratings/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed makes use of the **Global query parameters** and you can use the following query parameters. You must query the **/seasonplayerratings** feed by a specific tournament calendar UUID and contestant UUID. See also: Using Query Parameters and **Global query parameters** for a guide.

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL ({protocol}://{requestDomain}/{feedResource}), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid {outletAuthKey} this must be after the Outlet Authentication Key (and endpoint, if applicable). for _rt={mode} (operating mode) and _fmt={dataFormat} (response format), entity query parameter and UUID.
- Begin the query parameter string with ? (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the & (ampersand) operator. Values must be separated by the correct operator, for example & (multiple values, 'AND'), or - if a parameter supports it - , (multiple values, 'OR') or ! ('NOT').
- Use the required _ (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces {} from your calls (we include these as an example only).
- If using the JSONP format (_fmt=jsonp) you **MUST** use it in combination with the callback parameter (_clbk) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
tmc1 + ctst	Get player ratings data for a season by the specified tournament calendar UUID and contestant UUID. Pass the tournament calendar UUID to the tmc1 parameter and contestant UUID to the ctst parameter. <pre>GET https://api.performfeeds.com/soccerdata/seasonplayerratings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmc1={tournamentCalendarUuid}&ctst={contestantUuid}</pre>

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML](#)
- [JSON](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

- ▶<seasonPlayerRatings> (XML only)
- ▶<competition>
- ▶<tournamentCalendar>
- ▶<contestant>
- ▶<player>
- ▶<indexScore>

Season Player Ratings Explained - Total Score And Subscores

SUBSCORE	DETAILS
Attacking	This component attempts to quantify how much a player is contributing to their team's offensive output. Here, volume
Defending	The defensive subscore incorporates two elements: • active - the active defensive element uses stats on defensive actions directly accumulated by the p • passive - the passive defensive element considers the attacking output of the other team as a wh
Goalkeeping	The main (though not complete) component for evaluating a goalkeeper's performance. This includes performance on
Passing	This component assesses a player's efficiency in circulating the ball within their team while in possession. Location is s
Possession	This component attempts to measure a player's affect on their team's ability to retain and solidify possession. Here thi
Shooting	Contrary to attack, this component prizes efficiency. Shot location and type is taken into account by proxy (e.g. outside,