

Last modified on

Sports Data Soccer API - Season Playtime Feed (TM17)

Get information about aggregated playtime and net-playtime for a season

Overview

The Soccer **Season Playtime** feed provides aggregated information across an entire season about playtime, net-playtime, as well as definition of "dead" periods e.g., how long is the ball out of play after a goal, before a free-kick, before a throw-in whilst there is an injury break.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Contact your Stats Perform representative for a full list of available comps.

FEED POLLING FREQUENCY
Once in 24 hours

Season Playtime (TM17) Guide

USAGE	FEED
GET season playtime list by tournament calendar UUID inline URL path	/soccerdata/seasonplaytime/{outletAuthK{tmcl=tmcl UUID}
GET season playtime list by tournament calendar UUID inline URL path	/soccerdata/seasonplaytime/{outletAuthKrt={mode}
GET season playtime list by tournament calendar UUID for a specific contestant	/soccerdata/seasonplaytime/{outletAuthKctst=ctst UUID}

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/seasonplaytime` feed by a fixture (match) UUID.

Legacy IDs: You can use the `fx` query parameter to filter by an Opta legacy ID (only one ID is supported - you cannot specify a comma-separated list of IDs).

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example `GET` requests (rather than `cURL`, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you **MUST** use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Parameter	Value and description
tmcl	GET Season Playtime list by tournament calendar UUID inline URL path GET https://api.performfeeds.com/soccerdata/seasonPlayTime/{outletAuthKey}?_fmt={format}&rt={mode}&{tmcl=tmcl UUID}
tmcl UUID	GET Season Playtime list by tournament calendar UUID inline URL path GET https://api.performfeeds.com/soccerdata/seasonPlayTime/{outletAuthKey}/{tmcl=tmcl UUID}?_fmt={format}&rt={mode}
tmcl + contestant	GET Season Playtime list by tournament calendar UUID for a specific contestant GET https://api.performfeeds.com/soccerdata/seasonplaytime/{outletAuthKey}?_fmt={format}xml&rt={mode}&{tmcl=tmcl UUID}&{ctst=ctst UUID}

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML](#)
- [JSON](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<seasonPlayTime>

▶<competition>

▶<tournamentCalendar>

▶<overallPlaytime>

▶<stat>

▶<contestant>

▶<stat>

▶<playerStats>

▶<player>

▶<stat>

List Of Stats

▶**Stats - names and descriptions**