

Last modified on

Sports Data Soccer API - Season Points Rankings Feed (PE14)

Provides rankings data for all players, teams, and games based on the OPTA point scores within a tournament calendar (season).

Overview

The Soccer **Season Points Rankings Feed** provides data with ranks for players within their games played based on the OPTA points capturing the individual game performance and cumulative performance within a season of competition (tournament calendar). You can see complete lists of match stats, team stats, and player stats in the guide.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY						
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5
Updated at Full Time in each game, with feeds delivered for the two teams involved in that match only - this is usually within 10 minutes of the game finishing	See Tier 13	Post-match	n/a	n/a			n/a

Season Points Rankings (PE14) Guide

USAGE	FEED
GET cumulative Opta Points according to specified parameter values	/soccerdata/seasonstatspoints/{outletAuthKey}?{c

If your request URL is as follows (does not contain either a specific UUID of a fixture and the corresponding supported query parameter), the feed returns an error: /soccerdata/seasonstatspoints/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the /seasonstatspoints feed by a specific UUID of a fixture.

Legacy IDs: You can combine parameters for `fx` to filter by legacy IDs (only Opta core).

How to use query parameters and make successful requests:

- In our guides, we use HTTPS syntax for our example `GET` requests (rather than `cURL`, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.
- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
 - Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
 - Use the required `_` (underscore) for any parameters listed with this prefix.
 - Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
 - If using the JSONP format (`_fmt=jsonp`) you **MUST** use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

At least one of the parameters `tmcl`, `stg` or `srs` is always required and can be combined with other parameters described below

Query parameter	Value and description
<code>tmcl</code>	Get cumulative Opta Points for a specific tournament calendar. Pass the tournament calendar UUID to the <code>tmcl</code> parameter. GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}

Query parameter	Value and description
stg	Get cumulative Opta Points for a specific stage of tournament calendar. Pass the stage UUID to the stg parameter. <pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&stg={stageUuid}</pre>
srs	Get cumulative Opta Points for a specific series. Pass the series UUID to the srs parameter. <pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&srs={seriesUuid}</pre>
tmcl + ctst	Get cumulative Opta Points for a contestant within a specified tournament calendar. <pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&ctst={contestantUuid}</pre>
tmcl + ctst + ctstpos	Get cumulative Opta Points for tournament calendar and contestant playing in the home or away position. <pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&ctst={contestantUuid}&ctstpos={home away}</pre>
tmcl + ctst + ctst2	Get cumulative Opta Points for a specific tournament calendar and contestant playing against a specified another contestant. The Opta Points are returned only for the contestant specified with ctst parameter. <pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&ctst={contestantUuid}&ctst2={contestantUuid}</pre>
tmcl + ctst + ctst2 + ctstpos	Get cumulative Opta Points for a specific tournament calendar and contestant playing against a specified another contestant with the first contestant playing in the home or away position. The Opta Points are returned only for the contestant specified with ctst parameter. <pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&ctst={contestantUuid}&ctst2={contestantUuid}&ctstpos={home away}</pre>
tmcl + week	Get cumulative Opta Points for a specific tournament calendar and game week (<i>positive integer</i>). <pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&week={weekNumber}</pre>
tmcl + plrpos	Get cumulative Opta Points for a specific tournament calendar and players that have played on a specific position. Possible values for player position are: goalkeeper defender - covers also Wing Back position midfielder - covers also defending and attacking midfielder positions striker - covers also attacker position which is for players substituted in

Query parameter	Value and description
	<pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&plrpos={goalkeeper defender midfielder striker}</pre>
tmcl + detailed	Get cumulative Opta Points for a specific tournament calendar including details of matches every player has played in. Pass a value of yes or no (default) to the detailed parameter. <pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&detailed={yes no}</pre>
tmcl + people	Get cumulative Opta Points for a specific tournament calendar including data for players (default) or for teams only. Pass a value of yes (default) or no to the people parameter. <pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&people={yes no}</pre>
tmcl + top	Get cumulative Opta Points for a specific tournament calendar only for people with the highest Opta Points value. The result will contain players with statistic rank $\leq$ top. Pass the top value (<i>positive integer</i>) to the top parameter. <pre>GET https://api.performfeeds.com/soccerdata/seasonstatspoints/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&top={topValue}</pre>

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML - basic](#)
- [JSON - basic](#)
- [XML - detailed](#)
- [JSON - detailed](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<seasonStatsPoints> (XML only)

▶<competition>

▶<tournamentCalendar>

▶<players> (XML only)

▶<player>

▶<matches> (XML only)

▶<match>

▶<matchRanks> (XML only)

▶<matchRank>

▶<teamRanks> (XML only)

▶<teamRank>

Opta Points Table

Stats	Player	Goalkeeper	Total Points
Goals (G)	10	10	14(G+SOnT)
Shot on target (SOnT)	4	4	
Shot off target (SOffT)	2	2	
Blocked shots (BS)	2	2	
Own goal (OG)	-5	-5	
Assists (A)	6	6	
Passes (P)	0.2	0.2	
Crosses (C)	0.2	0.2	
Tackles (Tk)	2	2	
Interceptions (INT)	2	2	
Fouls won (FW)	1	1	
Fouls conceded (FC)	-1	-1	
Offsides (O)	-1	-1	
Yellow cards (YC)	-2	-2	
Red cards (RC)	-5	-5	
Goals conceded (GC)	-1	-6	
Penalties won (PW)	4	4	
Saves (SAV)		5	
Pen Saved (PS)		5	10(SAV+PS)

For more details refer: [Match Points](#)