

Last modified on

Sports Data Soccer API - Season Power Rankings Feed (TM14)

Get season based Power Rankings for contestants across globe, at confederation levels and for particular tournament calendars queried for.

Overview

The Soccer **Season Power Rankings feed** provides all the traditional data such as `rank` , `points` , `contestantId` , `contestantName` , `contestantShortName` , `contestantClubName` and `contestantCode` clubbed with `currentRating` , `highestSeasonRating` , `lowestSeasonRating` , `seasonAverageRating` , `currentConfederationRating` and `currentGlobalRank` at division level.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
	Once in 24 hours							

Season Power Rankings (TM14) Guide

USAGE	FEED
GET season power ratings according to specified parameter values	<code>/soccerdata/seasonpowerrankings/{outletAuthKey}?{</code>

If your request URL is as follows (does not contain a fixture UUID), the feed returns an error:
 /soccerdata/seasonpowerrankings/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/seasonPowerRankings` feed using the below parameters.

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example `GET` requests (rather than `cURL`, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` (Outlet Authentication Key), query parameters for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you **MUST** use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
<code>confed</code>	GET Season Power Rankings by confederation <pre>GET https://api.performfeeds.com/soccerdata/seasonpowerrankings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&confed=yes</pre>
<code>confed + rank</code>	GET Season Power Rankings by confederation and rank <pre>GET https://api.performfeeds.com/soccerdata/seasonpowerrankings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&confed=yes&rank={1TON}</pre>
<code>tmcl + rank</code>	GET Season Power Rankings by tournament calendar and rank <pre>GET https://api.performfeeds.com/soccerdata/seasonpowerrankings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&rank={1TON}</pre>

Query parameter	Value and description
tmcl	GET Season Power Rankings by tournament calendar <pre>GET https://api.performfeeds.com/soccerdata/seasonpowerrankings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}</pre> Note: Calling by tmcl only will pull data from today's date, so active tmcl must be used. To use an inactive tmcl, a date parameter must also be used and that date should be during the tmcl specified.
rankDt	GET Season Power Rankings by rankDt <pre>GET https://api.performfeeds.com/soccerdata/seasonpowerrankings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&rankDt={YYYY-MM-DD}</pre>
rank	GET Season Power Rankings by global rank <pre>GET https://api.performfeeds.com/soccerdata/seasonpowerrankings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&rank={1TON}</pre>
tmcl + rank + confed	GET Season Power Rankings by tournament calendar, confederation and rank <pre>GET https://api.performfeeds.com/soccerdata/seasonpowerrankings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&rank={1TON}&confed=yes</pre>
tmcl + rank + rankDt	GET Season Power Rankings by tournament calendar, confederation, rank and date range <pre>GET https://api.performfeeds.com/soccerdata/seasonpowerrankings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}&rank={1TON}&confed=yes&_rt=b&rankDt={Date}</pre>
type	GET Season Power Rankings by type <pre>GET https://api.performfeeds.com/soccerdata/seasonpowerrankings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&type={men women}</pre> Default feed requests (without type query param) and type=men should serve men power rankings. Women power rankings should be served with type=women Note: Either only the type query parameter or the combination of the following can be given in the API. - confed - confed + rank - rank - rankDt The type query parameter cannot be supplied with the tmcl (the combination of tmcl + type is restricted).

Sample Feeds

These sample feeds will let you see different examples of the feeds that can be obtained using the different parameters - click the links below to view them (each link opens in a new window).

- XML - confed only

- JSON - confed only
- XML - tmcl only
- JSON - tmcl only
- XML - tmcl + rank + confed
- JSON - tmcl + rank + confed
- XML - type (Women)
- XML - confed + type
- XML - rankDt + type

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<seasonPowerRankings> (XML only)

▶<competition>

▶<tournamentCalendar>

▶<division>

▶<ranking>