

Last modified on

Sports Data Soccer API - Squads Feed (TM3)

Get squad and individual personal information for either a specific contestant or all contestants playing in a tournament calendar.

Overview

The Soccer **Squads feed** provides squad details (personnel information) of teams:

- Current squad of a specified team
- Squads of teams playing in a specified tournament calendar

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 3	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+4
Updated on any change to competition, area, player, season, team or venue information	Once every hour	Once every hour	Once every hour	Once every hour	Once every hour	Once every hour	Once every 24 hours	Once every 24 hours

Squads (TM3) Guide

USAGE	FEED
GET squads data according to specified parameter values	/soccerdata/squads/{outletAuthKey}?{queryParameters}

If your request URL is as follows (does not contain this query criteria), the feed returns an error:
/soccerdata/squads/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/squads` feed by a specific tournament calendar UUID or contestant UUID, and you can combine additional query parameters in a request.

Legacy IDs: You can use parameters for `tmcl`, `ctst`, or `tmcl` and `ctst` in combination to filter by legacy IDs.

How to use query parameters and make successful requests:

- In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL ({protocol}://{requestDomain}/{feedResource}), in the **main guide** and **API Overview and Authorisation guide**.
- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid {outletAuthKey} this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
 - Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or `-` (multiple values, 'OR') or `!` ('NOT').
 - Use the required `_` (underscore) for any parameters listed with this prefix.
 - Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
 - If using the JSONP format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
tmcl	GET squads information only for the specified tournament calendar. Pass the tournament calendar UUID to the <code>tmcl</code> parameter. • The feed will return information about all players (active or not) in the specified season. If a player is signed before the start or after the end date of the season, then the player will only appear in that squad for the next season of the competition. • You can find the start dates and end dates for each tournament calendar within a competition in the Tournament Calendars (OT2) feed. GET https://api.performfeeds.com/soccerdata/squads/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}

Query parameter	Value and description
tmc1 + ctst	GET squads information only for a specific contestant in a tournament calendar (of a competition). Pass the contestant UUID to the ctst parameter, and tournament calendar UUID to the tmc1 parameter. - The feed will return information about all players from the specified team and season, that are either active or not (active=yes no). If a player is signed before the start or after the end date of the season, then the player will only appear in that squad for the next season of the competition. - You can find the start dates and end dates for each tournament calendar within a competition in the Tournament Calendars (OT2) feed. <pre>GET https://api.performfeeds.com/soccerdata/squads/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmc1={tournamentCalendarUuid}&ctst={contestantUuid}</pre>
ctst	GET squads information only for a specific contestant. Pass the contestant UUID to the ctst parameter. - The feed will return information about all players from the specified team that are active (active=yes). This is the full list of currently assigned players to this team without looking into any season data/connections. - This query is best used when players are signed outside of the conventional season start/end dates. <pre>GET https://api.performfeeds.com/soccerdata/squads/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}</pre>
detailed	GET an extended list of (detailed) personal attributes about each person in a team. Pass a value of yes or no (default) to the detailed parameter. <pre>GET https://api.performfeeds.com/soccerdata/squads/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&detailed={yes no}</pre>
_lcl=en-op	GET assets with the Opta namings, in English, in the response (instead of Opta Core namings). When the call does not include the _lcl=en-op parameter-value, the feeds will continue to work as they do currently - for example, the response will be in the default language of English unless the call contains the _lcl parameter and a locale code value to request a different locale/language. Note: You can use this parameter in combination with other valid parameters and values in the request. However, you cannot use it in combination with a locale/language code and _lcl parameter. <pre>GET https://api.performfeeds.com/soccerdata/squads/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&lcl=en-op&{queryParameters}</pre>
_pgNm + _pgSz	GET data only in the specified page size and/or page number. All results are returned in pages and these parameters help limit the page size in order to optimise the efficiency of the SDAPI. _pgNm - Specify the {pageNumber} to return - indexed from 1 . If this value is not provided, then page 1 is returned by default. _pgSz - Specify the size of the page to return - the number of match definitions in a page. Valid {pageSize} values depend on the operating mode of an outlet. For B2B requests, the maximum value is 1000 (default is 20). For B2C requests, the maximum value is 50 (default is 20).

Query parameter	Value and description
	GET https://api.performfeeds.com/soccerdata/squads/{outletAuthKey}?tmcl=bnni2f2e6ii20b1wmzcsbpj2o&_pgSz={pageSize}&_pgNm={pageNumber}&_fmt={dataFormat}&_rt={mode}

Do not supply both the `_lcl` (with a locale/language code value) and `_lcl=en-op` in the same call - this is not supported; otherwise, the feed will return an error and code 10203 (Ambiguous/Invalid request parameters) in the response due to a duplicated `_lcl` parameter.

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML - tmcl \(basic\)](#)
- [JSON - tmcl \(basic\)](#)
- [XML - tmcl & detailed=yes](#)
- [JSON - tmcl & detailed=yes](#)
- [XML - tmcl & ctst \(basic\)](#)
- [XML - tmcl & ctst & detailed=yes](#)
- [JSON sample - ctst \(basic\)](#)
- [JSON - ctst & detailed=yes](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<teamSquads> (XML only)

▶<squad>

▶<person>

▶<teamKits>

▶<kit>