

Last modified on

Sports Data Soccer API - TV Listing Feed (MA31)

Get information on TV broadcaster, channel and language information for Soccer matches.

Overview

The Soccer **Broadcasting feed** provides all the traditional data such as match information, competition information and details of the team that are part of this match, clubbed with new broadcasting information like `tvlisting`, `country`, `broadcaster`, `tvchannel` and `languages`.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you do not exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

POLLING FREQUENCY
Twice in a day to find updated information.

TV Listing (MA31) Guide

USAGE	FEED
GET Match Broadcasting information by <code>fixture</code>	<code>/soccerdata/matchtvlisting/{out:}</code>
GET Match Broadcasting information by <code>fixture inline path URL</code>	<code>/soccerdata/matchtvlisting/{out:}</code>
GET Match Broadcasting information by <code>fixture Opta ID</code>	<code>/soccerdata/matchtvlisting/{out:}</code>
GET Match Broadcasting information by <code>fixture Opta Core ID</code>	<code>/soccerdata/matchtvlisting/{out:}</code>

USAGE	FEED
GET Match Broadcasting information by contestant	<code>/soccerdata/matchtvlisting/{outletAuthKey}&_rt=b;</code>
GET Match Broadcasting information by contestant & week	<code>/soccerdata/matchtvlisting/{outletAuthKey}&week={week number}?_fmt=xml&_rt=</code>
GET Match Broadcasting information by contestant & week & country	<code>/soccerdata/matchtvlisting/{outletAuthKey}&week={week number}&ctry={country UUID}&_fmt=xml&_rt=b;</code>
GET Match Broadcasting information by contestant & week & tmcl & country	<code>/soccerdata/matchtvlisting/{outletAuthKey}&week={week number}&ctry={country UUID}&tmcl={tmcl}&_fmt=xml&_rt=b;</code>
GET Match Broadcasting information by contestant & week & tmcl & country & matchDate	<code>/soccerdata/matchtvlisting/{outletAuthKey}&week={week number}&ctry={country UUID}&tmcl={tmcl}&mt.mDt={match date range}&_fmt=xml&_rt=b;</code>

How can I get fixture and other entity UUIDs?

Use the **Tournament Calendar (OT2)** or **Fixtures and Results (MA1)** feeds to get fixture metadata, including UUIDs for each fixture and its linked contestants, competition, tournament calendar and other entities.

Legacy IDs: You can use the `fx` query parameter to filter by legacy IDs (only one ID is supported - you cannot specify a comma-separated list of IDs).

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format). If required, it should also include an entity UUID (such as a fixture/match UUID).
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).

- If using the JSONP format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
<code>fx</code>	GET TV Listing and information about one fixture or multiple fixtures. - To return one fixture: Pass a fixture UUID or legacy Opta match ID to the <code>fx</code> parameter. - To return multiple fixtures: Pass the fixture UUIDs in a comma-separated list to the <code>fx</code> parameter. For the B2B outlet request type (<code>_rt=b</code>) you can pass up to 50 UUIDs, while a B2C request (<code>_rt=c</code>) allows up to 20 UUIDs. Multiple legacy Opta and Opta Core match IDs are not supported. <pre>GET https://api.performfeeds.com/soccerdata/matchtvlisting/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&fx={fixtureUuid}</pre>
<code>fixture/match UUID</code>	GET TV Listing and information about one fixture by passing the fixture/match UUID as a path parameter (the asset/resource) in the URL. <pre>GET https://api.performfeeds.com/soccerdata/matchtvlisting/{outletAuthKey}/{fixtureUuid}?_rt={mode}&_fmt={dataFormat}</pre>
<code>_pgNm</code> + <code>_pgSz</code>	GET data only in the specified page size and/or page number. All results are returned in pages and these parameters help limit the page size in order to optimise the efficiency of the SDAPI. <code>_pgNm</code> - Specify the <code>{pageNumber}</code> to return - indexed from <code>1</code> . If this value is not provided, then page 1 is returned by default. <code>_pgSz</code> - Specify the size of the page to return - the number of match definitions in a page. Valid <code>{pageSize}</code> values depend on the operating mode of an outlet. For B2B requests, the maximum value is <code>1000</code> (default is 50). For B2C requests, the maximum value is <code>50</code> (default is 20). <pre>GET https://api.performfeeds.com/soccerdata/matchtvlisting/{outletAuthKey}{fixtureUuid}?_rt={mode}&_fmt={dataFormat}&_pgSz={pageSize}&_pgNm={pageNumber}&{queryParameters}</pre>
<code>fx(legacy stats id)</code>	GET TV Listing by legacy stats ID. <pre>GET https://api.performfeeds.com/soccerdata/matchtvlisting/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&fx=urn:perform:stats:fixture:{fixture statsId}</pre>
<code>stats competition id</code>	GET TV Listing by legacy competition stats ID. <pre>GET https://api.performfeeds.com/soccerdata/matchtvlisting/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&comp=urn:perform:stats:competition:{competition statsId}</pre>
<code>stats contestant id</code>	GET TV Listing by legacy contestant stats ID. <pre>GET https://api.performfeeds.com/soccerdata/matchtvlisting/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&ctst=urn:perform:stats:contestant:{contestant statsId}</pre>

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML](#)
- [JSON](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<match> (XML only)

▶<matchInfo>

▶<description>

▶<sport>

▶<ruleset>

▶<competition>

▶<country>

▶<tournamentCalendar>

▶<stage>

▶<contestants>

▶<contestant>

▶<country>

▶<venue>

▶<tvListing>

▶<country>

▶<broadcasters>

▶<broadcaster>

▶<tvChannels>

▶<tvChannel>

▶<languages>

▶<language>

