

Last modified on

Sports Data Soccer API - Team Player Predictions Feed (TM15)

Get team player prediction on statistics like yellow cards, red cards, shots, goals, passes and more.

Overview

The Soccer **Team Player Predictions feed** provides

- Prediction on all key events (Goals, Cards, Pens).
- Predicted totals on team-statistics like shots, saves, red cards, yellow cards and corners.
- Statistics and Predictions for individual players in the line-up.

The data feed also provides information on season averages for each of the mentioned statistic at the team and player level. Predictions are available on team and fixture bases for the entire season and are recalculated once per day. Player related Predictions are available for the next upcoming match of the team. Predictions are recalculated once per minute after the kick-off and while a match is being played.

Note: This feed will launch with limited availability. Please ask your Account Manager for information about competition availability and about commercial legalities around this feed.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY	
	TIER 15	TIER 13
	Once per day up until fixture start date/ time, and then once every minute upon kick-off thereafter.	

Team Player Predictions (TM15) Guide

USAGE	FEED
GET team player predictions by fixture UUID	<code>/soccerdata/teamplayerpredictions/ {outletAuthKey}?fx={fixtureUUID}& {queryParameters}</code>

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/teamplayerpredictions` feed by a fixture (match) UUID.

How To use query parameters and make successful requests:
In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{}` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
<code>fixtureUuid</code>	Get the team player prediction for a specific fixture UUID (path parameter method) . GET <code>https://api.performfeeds.com/soccerdata/teamplayerpredictions/{outletAuthKey}/{fixtureUUID}?_rt={mode}&_fmt={dataFormat}</code>
<code>fx</code>	Get the team player prediction for the specified fixture UUID (query parameter method) . Pass the fixture UUID to the <code>fx</code> parameter.

Query parameter	Value and description
	<pre>GET https://api.performfeeds.com/soccerdata/teamplayerpredictions/{outletAuthKey}?fx={fixtureUUID}&_rt={mode}&_fmt={dataFormat}</pre>
detailed	Get the detailed team player prediction for the specified fixture UUID. <pre>GET https://api.performfeeds.com/soccerdata/teamplayerpredictions/{outletAuthKey}?fx={fixtureUUID}&detailed={yes no}&_rt={mode}&_fmt={dataFormat}</pre>
min	Get predictive values of a team player at a certain point in time of the game. When used with &min=[mm], the response will contain prediction values that were valid at minute [mm] of the game. When a range is specified e.g &min=[mm],[mm], the response will contain all prediction values, grouped by minutes within the range of the request. &min=-1 will deliver all available data for the match. <pre>GET https://api.performfeeds.com/soccerdata/teamplayerpredictions/{outletAuthKey}?fx={fixtureUUID}&min={mm}&_rt={mode}&_fmt={dataFormat}</pre>
stat	Get the team player prediction by the dedicated statistic or an array of statistics. This parameter is used to limit the response to either a dedicated statistic or an array of statics. Pass one or an array of the following values: yellow_cards fouls saves red_cards assists minutes shots goals passes . <pre>GET https://api.performfeeds.com/soccerdata/teamplayerpredictions/{outletAuthKey}?fx={fixtureUUID}&min={mm}&stat={statvalue}&_rt={mode}&_fmt={dataFormat}</pre>

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML](#)
- [JSON](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<match>

▶<matchInfo>

▶<description>

▶<sport>

▶<ruleset>

▶<competition>

▶<country>

▶<tournamentCalendar>

▶<stage>

▶<contestants>

▶<contestant>

▶<country>

▶<venue>

▶<liveData>

▶<matchDetails>

▶<periods>

▶<period>

▶<scores>

▶<ht>

▶<ft>

▶<total>

▶<goal>

▶<card>

▶<substitute>

▶<VAR>

▶<lineUp>

▶<teamOfficial>

▶<preMatchPredictions>

▶<players>

▶<player>

▶<team>

▶<stat>

▶<livePredictions>

▶<livePrediction>

▶<players>

- ▶<player>
- ▶<stat>
- ▶<team>
- ▶<stat>
- ▶<matchDetailsExtra>
- ▶<attendance>
- ▶<matchOfficials>
- ▶<matchOfficial>