

Last modified on

Sports Data Soccer API - Team Standings Feed (TM2)

Get data to create a league table - position, points, matches won/lost/drawn, goals scored and conceded, and goal difference.

Overview

The Soccer **Team Standings feed** contains all of the data needed to create a league table. The feed contains league position, points, matches (played, win, lose, draw), goals scored, goals conceded and goal difference. It also contains different divisions/splits/types of league table, such as a league table that shows only home matches. To get a feed that shows the team standings split by a specific type of division (returned under the **division** element in the response/feed output), pass the associated value to the **type** query parameter. For a full explanation of the different types that may be available, see [Query parameters and values](#) and [Team Standings - available division types](#).

Note: Standings feeds are updated once a game ends. Where games in a particular competition are staggered throughout a single day, customers should expect an updated file once each game ends. For competitions where scores are recorded live an 'As-It-Stands' live table will be available.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our [FAQs](#). We also recommend that you take a look at our [API Overview and Authentication Guide](#). You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY					
	TIER 15	TIER 12+14	TIER 11+13	TIER 8+9+10	TIER 5+6+7	TIER 1+2+3
Updated on any change to the season, competition, area, round, group, match, status, venue, round or other information Note: Only the TM2 feed will trigger on 'live' status	No more frequently than one URL poll every 30 seconds for range: <KO + 0h; KO + 3h> Up to 1-hour interval for range: <KO + 3h; KO + 8h> Poll twice daily outside of above timings	No more frequently than one URL poll every 10 minutes for range: <KO + 2h; KO + 14h> Poll twice daily outside of above timings	No more frequently than one URL poll every 30 seconds for range: <KO + 0h; KO + 3h> Up to 1-hour interval for range: <KO + 3h; KO + 8h> Poll twice daily outside of above timings	No more frequently than one URL poll every 30 seconds for range: <KO + 0h; KO + 4h> Up to 1-hour interval for range: <KO + 4h; KO + 8h> Poll twice daily outside of above timings	No more frequently than one URL poll every 30 seconds for range: <KO + 0h; KO + 3h> Up to 1-hour interval for range: <KO + 3h; KO + 8h> Poll twice daily outside of above timings	No more frequently than one URL poll every 10 minutes for range: <KO + 2h; KO + 14h> Poll twice daily outside of above timings

Team Standings (TM2) Guide

USAGE	FEED
GET team standings data according to specified parameter values	/soccerdata/standings/{outletAuthKey}?{queryParams}

How can I get tournament calendar and other entity UUIDs?

Use the **Tournament Calendar (OT2)** or **Tournament Schedule (MA0)** feeds to get competition, tournament calendar, and fixture metadata, including UUIDs for each fixture and its linked contestants, competition, tournament calendar and other entities.

If your request URL is as follows (does not contain a tournament calendar UUID), the feed returns an error:
/soccerdata/standings/{outletAuthKey}

Query Parameters And Example Request Parameters

You must query the `/standings` feed by a tournament calendar UUID. This feed makes use of the **Global query parameters** and you can use the following query parameters. You can only pass one ID to each parameter - it does not support a comma-separated list of IDs. See also: **Using Query Parameters** and **Global query parameters** for a guide.

Legacy IDs: You can use the `tmc1` parameter and a combination of `tmc1` and `stg` parameters to filter by legacy IDs.

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format). If required, it should also include an entity UUID (such as a fixture/match UUID).
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
<code>tmc1</code>	GET team standings information only for the specified tournament calendar. Pass the tournament calendar UUID to the <code>tmc1</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/standings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmc1={tournamentCalendarUuid}</pre>
<code>tmc1</code> + <code>stg</code>	GET team standings information only for a specific stage of a specified tournament calendar. Pass the <code>{stageUuid}</code> to the <code>stg</code> parameter, and tournament calendar UUID to the <code>tmc1</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/standings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmc1={tournamentCalendarUuid}&stg={stageUuid}</pre>
<code>tmc1</code> + <code>live</code>	GET only live team standings data by passing live parameter with <code>tmc1</code>. The available values for the <code>live</code> parameter are: <code>no</code> (default) and <code>yes</code>. In the team standings feed, you must use the <code>live</code> parameter in combination with the <code>tmc1</code> parameter and UUID. <pre>GET https://api.performfeeds.com/soccerdata/standings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmc1=bnni2f2e6ii20b1wmzcsbpj2o&live={yes no}</pre>
<code>tmc1</code> + <code>type</code>	GET only a certain type of division of team standings information. In the team standings feed, you must use the <code>type</code> parameter in combination with the <code>tmc1</code> parameter and UUID. Data is returned in the <code><division/></code> element. The available values for the <code>type</code> parameter are: • <code>total</code> (all types, default when <code>type</code> parameter is not specified) • <code>home</code> • <code>away</code> • <code>form-total</code> • <code>form-home</code> • <code>form-away</code> • <code>half-time-total</code> • <code>half-time-home</code>

Query parameter	Value and description
	- half-time-away - attendance - over-under - relegation - championship <pre>GET https://api.performfeeds.com/soccerdata/standings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmc1=bnni2f2e6ii20b1wmzcsbpj2o&type={divisionType}</pre>
<code>_lcl=en-op</code>	Add this parameter-value to return assets with the Opta namings, in English, in the response (instead of Opta Core namings). When the call does not include the <code>_lcl=en-op</code> parameter-value, the feeds will continue to work as they do currently; one example is that the response will be in the default language of English unless the call contains the <code>_lcl</code> parameter and a locale code value to request the response in a different locale/language. Note: You can use this parameter in combination with other valid parameters and values in the request. However, you cannot use it in combination with a locale/language code and <code>_lcl</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/standings/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&_lcl=en-op&{queryParameters}</pre>

Do not supply both the `_lcl` (with a locale/language code value) and `_lcl=en-op` in the same call - this is not supported; otherwise, the feed will return an error and code 10203 (Ambiguous/Invalid request parameters) in the response due to a duplicated `_lcl` parameter.

Team Standings - Available Division Types

The ranking order per division/split is according to the type. For example, for 'total' the rank order is according to all matches played and goal difference, 'form-total' is according to the form over the last six matches (home and away), and 'attendance' is ranked by highest to lowest attendance.

PARAMETER VALUE (type)	DESCRIPTION	ASSOCIATED ATTRIBUTE IN FEED OUTPUT (division)
<code>total</code>	Returns rankings data according to both home and away matches ('total'). Note: This is the <i>default</i> behaviour of the feed when the <code>type</code> parameter is not specified in the API call	<code>total</code>
<code>home</code>	Returns rankings data according to all home matches ONLY	<code>home</code>
<code>away</code>	Returns rankings data according to all away matches ONLY	<code>away</code>
<code>form-total</code>	Returns rankings data according to form over the last six matches - home and away . This constitutes a total of six (6) matches, comprising the last three (3) matches played at home and the last three (3) matches played away (and the feed will show <code>played="6"</code>). Note: During this time, if either of the teams has	<code>form-total</code>

PARAMETER VALUE (type)	DESCRIPTION	ASSOCIATED ATTRIBUTE IN FEED OUTPUT (division)
	played more of one type of match in the last six (that is, more than three home matches/more than three away matches in the last six), then the sixth match would not be included in the feed as it would be the fourth match played home/away, and therefore it would not obey the logic of the feed.	
form-home	Returns rankings data according to form over the last three away matches	form-home
form-away	Returns rankings data according to form over the last three away matches	form-away
half-time-total	Returns rankings data according to the goals scored by half time - for home and away matches ('total')	half-time-total
half-time-home	Returns rankings data according to the goals scored by half time - for home matches	half-time-home
half-time-away	Returns rankings data according to the goals scored by half time - for away matches	half-time-away
attendance	Returns rankings data according to match attendance	attendance
over-under	Returns rankings data according to Over/Under (total goals)	over-under
relegation	Returns rankings data according to relegation average index of the teams cumulated over past few seasons	relegation
championship	Returns rankings data according to the championship	championship

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- **XML** - specifies a tournament calendar (tmcl) and no types (all types returned by default)
- **JSON** - specifies a tournament calendar (tmcl) and no types (all types returned by default)
- **XML** - specifies a tournament calendar (tmcl) and 'home form' (type)
- **JSON** - specifies a tournament calendar (tmcl) and 'total' (type)
- **JSON** - specifies a tournament calendar (tmcl) and a stage (stg)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

- The root element can be **teamStandings** (XML) or **sport** (JSON) - see the table below.

- In the scenario where the match has not yet been played (for example, it is a scheduled fixture to be played in the future), not all attributes listed here will be present and we may provide placeholder values for some attributes. For example, previous result(s), contestant name and ID may not be known. However, the feed will be updated with this information once it is available.

▶<teamStandings> (XML only)

▶<sport>

▶<ruleset>

▶<competition>

▶<tournamentCalendar>

▶<stages> (XML only)

▶<stage>

▶<divisions> (XML only)

▶<division>

▶<ranking>

▶<relegation>

▶<seasons> (XML only)

▶<season>

▶<corrections> (XML only)

▶<correction>