

Last modified on

Sports Data Soccer API - Teams Feed (TM1)

Get team details of all contestants within a specified tournament calendar or details for a single contestant.

Overview

The Soccer **Teams feed** contains basic team information on the teams in a tournament calendar or a single team.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
Updated on any change/update to a team's basic data (eg name, type, officialName, shortName, and so on) and connection with a specific tournament calendar (season), stage, or series	Once every 24 hours by tmcl. Once every month by ctst.	Once every 24 hours by tmcl. Once every month by ctst.	Once every 24 hours by tmcl. Once every month by ctst.	Once every 24 hours by tmcl. Once every month by ctst.	Once every 24 hours by tmcl. Once every month by ctst.	Once every 24 hours by tmcl. Once every month by ctst.	Once every 24 hours by tmcl. Once every month by ctst.	Once every 24 hours by tmcl. Once every month by ctst.

Teams (TM1) Guide

USAGE	FEED
GET team data according to specified parameter values	/soccerdata/team/{outletAuthKey}?{queryParameters}

If your request URL is as follows (does not contain this query criteria), the feed returns an error:
/soccerdata/team/{outletAuthKey}

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the **/team** feed by a specific tournament calendar UUID or contestant UUID, and you can combine additional query parameters in a request.

How to use query parameters and make successful requests:

- In our guides, we use HTTPS syntax for our example **GET** requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.
- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
 - Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
 - Use the required `_` (underscore) for any parameters listed with this prefix.
 - Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
 - If using the JSONP format (`_fmt=jsonp`) you **MUST** use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
ctry	Get team information only for a specific country. Pass the contestant UUID to the ctst parameter. <pre>GET https://api.performfeeds.com/soccerdata/team/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&ctry={countryUuid}</pre>
ctst	Get team information only for a specific contestant. Pass the contestant UUID to the ctst parameter. <pre>GET https://api.performfeeds.com/soccerdata/team/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}</pre>
tmcl	Get team information only for the specified tournament calendar. Pass the tournament calendar UUID to the tmcl parameter.

Query parameter	Value and description
	GET <code>https://api.performfeeds.com/soccerdata/team/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}</code>
stg	Get team information only for a specific stage . Pass the stage UUID to the stg parameter. GET <code>https://api.performfeeds.com/soccerdata/team/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&stg={stageUuid}</code>
srs	Get team information only for a specific series . Pass the series UUID to the ctst parameter. GET <code>https://api.performfeeds.com/soccerdata/team/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&srs={seriesUuid}</code>

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- **XML** - **ctst** (basic)
- **JSON** - **ctst** (basic)
- **XML** - **ctst** & **detailed=yes**
- **JSON** - **ctst** & **detailed=yes**
- **XML** - **ctry** & **detailed=yes**
- **XML** - **stg** & **detailed=yes**
- **XML** - **srs** & **detailed=yes**
- **XML** - **tmcl** & **detailed=yes**

Example Calls And Responses

In this example, the query is to return data about a specific tournament calendar ID - click on the button below to see a complete example of a response from the feed.

► **SHOW/HIDE: XML (basic) example - tmcl (by tournament calendar UUID)**

► **SHOW/HIDE: JSON (basic) example - tmcl (by tournament calendar UUID)**

► **SHOW/HIDE: XML (basic) example - ctst (by contestant UUID)**

► **SHOW/HIDE: JSON (basic) example - ctst (by contestant UUID)**

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

► **<contestants>** (XML only)

► **<contestant>**

