

Last modified on

Sports Data Soccer API - Top Performers Feed (PE6)

Get basic data ranking data all players and games in a range of statistical categories within a season.

Overview

The Soccer **Top Performers feed** contains information for each team on its top performers and can be queried on a team, season or competition basis.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
Updated after each match on a given matchday								

Top Performers (PE6) Guide

USAGE	FEED
GET information about Top Performers associated with a specific Tournament Calendar UUID <i>Required:</i> Tournament Calendar UUID, either passed as a path parameter in the URL or passed to the <code>tmc1</code> query parameter.	/soccer-top-performers/{tmc1} /soccer-top-performers/{tmc1}

If your request URL is as follows (does not contain a tournament calendar UUID and query criteria), the feed returns an error: `/soccerdata/topperformers/{outletAuthKey}`

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/topperformers` feed by an entity such as a specific tournament calendar UUID, and you can combine query parameters in your requests.

Legacy IDs: You can use the `tmc1` parameter to filter by legacy ID.

How to use query parameters and make successful requests:

- In our guides, we use HTTPS syntax for our example `GET` requests (rather than `cURL`, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.
- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
 - Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or `-` if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
 - Use the required `_` (underscore) for any parameters listed with this prefix.
 - Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
 - If using the JSONP format (`_fmt=jsonp`) you **MUST** use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
<code>tmc1</code>	GET ranking information only from the specified tournament calendar. Pass the tournament calendar UUID to the <code>tmc1</code> parameter. GET https://api.performfeeds.com/soccerdata/topperformers/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmc1={tournamentCalendarUuid}
<code>{tournamentCalendarUuid}</code> Tournament Calendar UUID	GET ranking information only for the specified tournament calendar. Pass the tournament calendar UUID in the request URL directly as the <code>{assetId}</code> (asset/resource ID). GET https://api.performfeeds.com/soccerdata/topperformers/{outletAuthKey}/{tournamentCalendarUuid}?_rt={mode}&_fmt={dataFormat}

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- **XML** - `tmc1`
- **XML** - `{tournamentCalendarUuid}`
- **JSON** - `tmc1`

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<seasonTopPerformers> (XML only)

▶<competition>

▶<tournamentCalendar>

▶<playerTopPerformers>

▶<ranking>

▶<player>

▶<teamTopPerformers>

▶<ranking>

▶<team>

Ranking Types

Ranking information for the given season/tournament calendar are split into the following elements (where available):

- `playerTopPerformers` - contains a `ranking` element for each ranking type that contains data for each player in the given season/tournament calendar
- `teamTopPerformers` - contains a `ranking` element for each ranking type that contains data for each team/contestant in the given season/tournament calendar

Click on the SHOW/HIDE buttons below to see the complete lists of player and team (contestant) ranking types/stats.

Ranking - Player

▶SHOW/HIDE

Ranking - Team/Contestant

▶SHOW/HIDE

