

Last modified on

Sports Data Soccer API - Tournament Calendar Reference Feed (TMR)

Get a list of Tournament calendar from your requested feed that have been updated since a date/time specified by you.

Overview

The Soccer **Tournament Calendar Reference feed** provides a way for you to find which tournament calendars have been updated since a certain point in time. This allows you to limit and refine the number of calls you need to make to your data feed, which will also improve performance.

Currently, this is available only for the following feeds:

- Team Standings Feed (TM2)
- Squads Feed (TM3)
- Seasonal Stats Feed (TM4)
- Season Expected Goals Feed (TM9)
- Season Player Ratings Feed (TM10)
- Season Playtime Feed (TM17)

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

POLLING FREQUENCY

Every 30-60 seconds. The feed only accepts a maximum value range from the current time of your request (currentTime) - 36 hours

Tournament Calendar Reference (TMR) Guide

USAGE

GET **tournament calendar reference data** for updated tournament calendars for the specified feed by a specified reference delta date/time

If your request URL is as follows (does not contain mandatory query parameters and criteria), the feed returns an error: `/soccerdata/tournamentcalendarreference/{outletAuthKey}`

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/tournamentcalendarreference` feed using the below parameters.

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
<code>_rdlt</code> + <code>type</code>	Get a tournament calendar reference list for tournament calendars updated since a particular date/time (where data has changed) for the specified type of feed. • <code>type</code> - pass the feed code to the parameter. Values: <code>tm2</code>, <code>tm2_live</code>, <code>tm3_basic</code>, <code>tm4_basic</code>, <code>tm4</code>, <code>tm9</code>, <code>tm10</code> or <code>tm17</code> • <code>_rdlt</code> - pass the date/time to the parameter. Values: Use <code>{xsd:dateTime}</code> (with timezone) or <code>{milliseconds}</code> (since the epoch) to specify the date and time. The format of the date/time for XSD UTC/GMT is: <code>YYYY-MM-DDThh:mm:ssZ</code>

Query parameter	Value and description
	Important: The parameter (and feed) only accepts a maximum value range from the current time of your request (currentTime) - 36 hours. If the value exceeds maximum value, error code 10213 is returned (and HTTP 400). GET http://api.performfeeds.com/soccerdata/tournamentcalendarreference/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&_rdlt={dateTime}&type={feedCode}&{queryParameters}
_pgNm + _pgSz	Get a tournament calendar reference list for tournament calendars by specifying pagination parameters _pgNm - Specify the {pageNumber} to return - indexed from 1 . If this value is not provided, then page 1 is returned by default. _pgSz - Specify the size of the page to return - the number of match definitions in a page. Valid {pageSize} values depend on the operating mode of an outlet. .The maximum value is 50 (default is 50). GET http://api.performfeeds.com/soccerdata/tournamentcalendarreference/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&_pgNm={pageNumber}&_pgSz={pageSize}&{queryParameters}

Sample Calls

These sample calls let you see an example of how to format the URL - click on the links below (opens in a new window).

Note: You will receive error code **10213** in the feed response because these sample URLs contain a **_rdlt** date/time value that exceeds the maximum specification of the feed (currentTime - 36 hours). Click on the buttons below to see examples of the feed response when the call is successful (date/time value is within specification).

- XML** - TM4 feed
- JSON** - TM4 feed

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

```
<tournamentCalendarReference>(XML) or type (JSON)

<tournamentCalendar>
```