

Last modified on

Sports Data Soccer API - Tournament Calendars Feed (OT2)

Get basic information about the tournament calendars - the individual seasons/editions of a competition.

Overview

The Soccer **Tournament Calendars feed** provides basic information about the tournament calendars - the individual seasons/editions of a competition.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview And Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
Updated on any update to seasons, teams, rounds, groups, areas or other information	Once every 24 hours							

Tournament Calendars (OT2) Guide

USAGE	FEED
GET a <i>list</i> of Tournament Calendars	/soccerdata/tournamentcalendar/{outletA

USAGE	FEED
GET Tournament Calendar information according to specified parameter values	/soccerdata/tournamentcalendar/{outletAuthKey}/{queryParams}
ENDPOINTS	
GET all authorized Tournament Calendars (those your outlet has access to)	/soccerdata/tournamentcalendar/{outletAuthKey}/authorized
GET all active Tournament Calendars (usually the current/most recent)	/soccerdata/tournamentcalendar/{outletAuthKey}/active
GET all Tournament Calendars that are both only authorized and active	/soccerdata/tournamentcalendar/{outletAuthKey}/active/authorized

Query Parameters And Example Request Parameters

This feed also makes use of the **Global Query Parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other), as well as the `/active` and `/authorised` endpoints. You must query the `/tournamentcalendar` feed by a specific tournament calendar UUID or contestant UUID - you can combine additional query parameters in a request.

Legacy IDs: You can use parameters for `comp` and `ctst` to filter by legacy IDs.

How to use query parameters and make successful requests:

- In our guides, we use HTTPS syntax for our example `GET` requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You **MUST** format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.
- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` (Outlet Authentication Key), query parameters for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
 - Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
 - Use the required `_` (underscore) for any parameters listed with this prefix.
 - Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
 - If using the JSONP format (`_fmt=jsonp`) you **must** use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-

generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
comp	Get tournament calendar information only for the specified competition. Pass the competition UUID to the comp parameter. <pre>GET https://api.performfeeds.com/soccerdata/tournamentcalendar/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&comp={competitionUuid}</pre>
ctst	GET tournament calendar information only for the specified contestant (the opposition in a fixture, such as a sports team). Pass the contestant UUID to the ctst parameter. <pre>GET https://api.performfeeds.com/soccerdata/tournamentcalendar/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}</pre>
stages	GET or exclude the following stages, series, and standings information of a tournament calendar: - All stages including the Opta Core ID, stage UUID and name (such as, Group Stage, Play-Offs, Final), stage start and end date, and a lastUpdated timestamp. - All series information including the Opta Core ID, series UUID and name (such as, Group A, Group B), and a lastUpdated timestamp. - Standings information on the stage element. Pass a value of yes or no to the stages parameter. <pre>https://api.performfeeds.com/soccerdata/tournamentcalendar/{outletAuthKey}/active/authorized?_rt={mode}&_fmt={dataFormat}&stages=yes</pre>
coverage	GET coverage information for tournament calendars that will have Live Text Commentary (LTC) or Opta facts (pre/live/post) and the available languages: Pass a value of yes or no to the coverage parameter. <pre>https://api.performfeeds.com/soccerdata/tournamentcalendar/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&coverage=yes</pre>
_pgNm + _pgSz	GET data only in the specified page size and/or page number. All results are returned in pages and these parameters help limit the page size in order to optimise the efficiency of the SDAPI. Note: You cannot use this parameter without passing the data_type in the call. _pgNm - Specify the {pageNumber} to return - indexed from 1 . If this value is not provided, then page 1 is returned by default. _pgSz - Specify the size of the page to return - the number of match definitions in a page. Valid {pageSize} values depend on the operating mode of an outlet. For B2B requests, the maximum value is 1000 (default is 400). For B2C requests, the maximum value is 400 (the default is 400). <pre>GET https://api.performfeeds.com/soccerdata/tournamentcalendar/{outletAuthKey}?_pgSz={pageSize}&_pgNm={pageNumber}&{queryParameters}</pre>

Endpoints

You can also use the following criteria in the OT2 feed, and combine it with the **comp** and **ctst** query parameters.

Endpoint + Query parameter	Value and description
/active + comp	GET the active (usually the current/most recent) tournament calendars only for the specified competition UUID . GET <code>https://api.performfeeds.com/soccerdata/tournamentcalendar/{outletAuthKey}/active?comp={competitionUuid}&{restOfString}</code>
/active + ctst	GET the active (usually the current/most recent) tournament calendars only for the specified contestant UUID . GET <code>https://api.performfeeds.com/soccerdata/tournamentcalendar/{outletAuthKey}/active?ctst={contestantUuid}&{restOfString}</code>
/authorized + comp	GET the authorized tournament calendars only for the specified competition UUID . Pass the competition UUID to the comp parameter. GET <code>https://api.performfeeds.com/soccerdata/tournamentcalendar/{outletAuthKey}/authorized?comp={competitionUuid}&{restOfString}</code>
/authorized + ctst	GET Tournament Calendar information for the specified contestant only (the opposition in a fixture, such as a sports team). Pass the contestant UUID to the ctst parameter. GET <code>https://api.performfeeds.com/soccerdata/tournamentcalendar/{outletAuthKey}/authorized?ctst={contestantUuid}&{restOfString}</code>
/authorized + ctst + comp	GET Tournament Calendar information for the specified contestant UUID (the opposition in a fixture, such as a sports team) and competition UUID . . Pass the contestant UUID to the ctst parameter and pass the competition UUID to the comp parameter. GET <code>https://api.performfeeds.com/soccerdata/tournamentcalendar/{outletAuthKey}/authorized?ctst={contestantUuid}&comp={compUuid}</code>

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- **XML**
- **JSON**
- **XML - active**
- **XML - comp**
- **JSON - active & comp**
- **JSON sample - active, authorized & comp**
- **XML - comp & coverage**
- **XML - stages (yes) & coverage**

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<tournamentCalendars> (XML only)

▶<competition>

▶<tournamentCalendar>

▶<coverage>

▶<level>

▶<stage>

▶<series>

▶<coverage>

▶<level>