

Last modified on

Sports Data Soccer API - Tournament Schedule Feed (MA0)

Get schedule information for a tournament, including individual matches split by day, including the coverage level for a match.

Overview

The Soccer **Tournament Schedule feed** provides basic match information with the games split by day, as well as the coverage level for the match.

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
Updated on any update to the match time, date, teams, round, season, competition or other information	Once every 24 hours							

Tournament Schedule (MA0) Guide

USAGE	FEED
GET basic information about tournament schedules including matches associated with a tournament calendar UUID <i>Required:</i> Tournament Calendar UUID, either passed as a path parameter in the URL or passed to the <code>tmc1</code> query parameter.	<code>/soccerdata/tournamentschedule/{tournamentCalendarUUID}</code> <code>{tournamentCalendarUUID}</code> <code>/soccerdata/tournamentschedule/tmc1={tournamentCalendarUUID}</code>

If your request URL is as follows (does not contain a tournament calendar UUID and query criteria), the feed returns an error: `/soccerdata/tournamentschedule/{outletAuthKey}`

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other. However, you must query the `/tournamentschedule` feed by a specific tournament calendar UUID.

Legacy IDs: You can use the `tmc1` parameter to filter by legacy ID.

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` (Outlet Authentication Key), query parameters for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or `-` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you **must** use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly generated function names. You must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
<code>tmc1</code>	Get match information only for the specified tournament calendar. Pass the tournament calendar UUID to the <code>tmc1</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/tournamentschedule/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmc1={tournamentCalendarUuid}&{queryParameters}</pre>
<code>{tournamentCalendarUuid}</code> Tournament Calendar UUID	Get match information only for the specified tournament calendar. Pass the tournament calendar UUID in the request URL directly as the <code>{assetId}</code> (asset/resource ID). <pre>GET http://api.performfeeds.com/soccerdata/tournamentschedule/{outletAuthKey}/{tournamentCalendarUuid}?_rt={mode}&_fmt={dataFormat}&{queryParameters}</pre>
<code>cvlv</code>	Get fixtures for only the specified coverage level/s (subject to other query parameters/criteria). This will filter out (hide) all matches that are not from requested coverage level/s. Pass one value (or multiple values in a comma-separated list) to the parameter: <code>1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15</code> - this is a number that represents the coverage level tier, in the range <code>1 - 15</code> - for example: <code>cvlv=9</code> Note: - In the <code>matchDate</code> element, the <code>numberOfGames</code> attribute-value will be recalculated to reflect the current number of matches from that tier. - If we do not have any matches on a specified date, the <code>matchDate</code> element will be hidden. - If we do not have any matches from the requested tier for a specified tournament calendar, only the <code>competition</code> and <code>tournamentCalendar</code> elements will be shown (the <code>matchDate</code> element will not be shown). - If no matches are available for the specified tier and query criteria, the standard error code is returned to reflect that no data is available. - In the absence of this parameter, the default behavior of the feed is to retrieve fixtures from all tiers, taking into account other query criteria. <pre>GET https://api.performfeeds.com/soccerdata/tournamentschedule/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&cvlv={coverageLevel}</pre>
<code>_lcl=en-op</code>	Add this parameter-value to return assets with the Opta namings, in english, in the response (instead of Opta Core namings). When the call does not include the <code>_lcl=en-op</code> parameter-value, the feeds will continue to work as they do currently; one example is that the response will be in the default language of english unless the call contains the <code>_lcl</code> parameter and a locale code value to request the response in a different locale/language. Note: You can use this parameter in combination with other valid parameters and values in the request. However, you cannot use it in combination with a locale/language code and <code>_lcl</code> parameter. <pre>GET https://api.performfeeds.com/soccerdata/tournamentschedule/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&_lcl=en-op&{queryParameters}</pre>

Do not supply both the `_lcl` (with a locale/language code value) and `_lcl=en-op` in the same call - this is not supported; otherwise, the feed will return an error and code `10203` (Ambiguous/Invalid request parameters) in the response due to a duplicated `_lcl` parameter.

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (opens in a new window).

- [XML](#)
- [JSON](#)

Example Call And Response - By Tournament Calendar UUID

In this example, the query is to return data about a specific tournament calendar ID - click on the buttons below to see complete examples of a response from the feed.

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

▶<tournamentSchedule>(XML only)

▶<competition>

▶<tournamentCalendar>

▶<matchDate>

▶<match>