

Last modified on

Sports Data Soccer API - Transfers Feed (TM7)

Get information about players transferred between clubs, including transfer type, date, currency and transfer value.

Note: This feed will only include entries related to transfers where a player is switching from one club to another.

Overview

The Soccer **Transfers feed** will return a list of players transferred between clubs with information such as transfer type, date, currency and transfer value (where available).

Required Compliance:

To comply with our API security and best practice logic for your API calls please refer to our **FAQs**. We also recommend that you take a look at our **API Overview and Authentication Guide**. You will learn the basics of how our API works and key concepts to get started.

How Often Should I Poll The Feed?

We have provided some guidelines to help ensure that you call the feed only as often as you need to. Make sure that you don't exceed the rate confirmed with us - this can vary depending on whether you make requests as a B2B or B2C outlet - if you need more information on this, contact your Stats Perform representative.

UPDATED	POLLING FREQUENCY							
	TIER 15	TIER 12+14	TIER 4	TIER 11+13	TIER 8+9+10	TIER 6+7	TIER 5	TIER 1+2+3
Updated on any change to player, team, area, season, transfer, competition or other data	The feed can be polled every 24 hours							

Transfers (TM7) Guide

USAGE	FEED
GET transfers information according to specified parameter values	<code>/soccerdata/transfers/{outletAuthKey}?{queryParams}</code>

If your request URL is as follows (does not contain this query criteria), the feed returns an error:
`/soccerdata/transfers/{outletAuthKey}`

Query Parameters And Example Request Parameters

This feed also makes use of the **Global query parameters**, and you can combine them with the following query parameters (some of which can be used in conjunction with each other). However, you must query the `/transfers` feed by a specific UUID of a person or contestant (team), and you can combine additional query parameters in a request.

Legacy IDs: You can use parameters for `prsn` and `ctst` (and combine them with each other or with the `comp` parameter) to filter by legacy IDs.

Caution - use of the comp parameter:

- We do not recommend calling the feed using only the `comp` query parameter, this is because the feed will return all player transfers for the specified competition from all tournament calendars (seasons/years) - this could return thousands of results, in some cases more than 10,000 results.
- The most efficient way to query the feed by competition UUID is to do so within a specific date range - you can do this using the `strtDt` (start date) and `endDt` (end date) query parameters, as given in the table and sample calls.

How to use query parameters and make successful requests:

In our guides, we use HTTPS syntax for our example GET requests (rather than cURL, for example). All URLs are case-sensitive - this means that URL strings must contain the correct case and operators. You MUST format your requests correctly and include certain information; otherwise, an error will be returned. You can find information about the API, including the base URL (`{protocol}://{requestDomain}/{feedResource}`), in the **main guide** and **API Overview and Authorisation guide**.

- Include the following information in the URL or header and make sure it is correct for your outlet: your unique and valid `{outletAuthKey}` this must be after the Outlet Authentication Key (and endpoint, if applicable). for `_rt={mode}` (operating mode) and `_fmt={dataFormat}` (response format), entity query parameter and UUID.
- Begin the query parameter string with `?` (question mark) - this must be after the Outlet Authentication Key (and endpoint, if applicable). To build up a query string, make sure that each query parameter is separated by the `&` (ampersand) operator. Values must be separated by the correct operator, for example `&` (multiple values, 'AND'), or - if a parameter supports it - `,` (multiple values, 'OR') or `!` ('NOT').
- Use the required `_` (underscore) for any parameters listed with this prefix.
- Remove any placeholder value curly braces `{ }` from your calls (we include these as an example only).
- If using the JSONP format (`_fmt=jsonp`) you MUST use it in combination with the callback parameter (`_clbk`) and a fixed value (or where you use a different value in a different instance, you must do this as little as possible). Be aware that common JavaScript frameworks, such as jQuery, can default to use randomly-generated function names - you must make sure that these are overridden and define a fixed function name instead.

Query parameter	Value and description
prsn	GET transfers data for a specific person (a player). Pass the person UUID to the prsn parameter. GET https://api.performfeeds.com/soccerdata/transfers/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&prsn={personUuid}
ctst	GET all player transfers for the specified contestant - the feed returns transfers for all players that have/had membership at the contestant. Pass the contestant UUID to the ctst parameter. GET https://api.performfeeds.com/soccerdata/transfers/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&ctst={contestantUuid}
comp + strtDt + endDt	GET all player transfers in the specified date range and competition. Pass the competition UUID to the comp parameter, and date values to the strtDt and endDt parameters (in the format YYYY-MM-DD). GET https://api.performfeeds.com/soccerdata/transfers/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&comp={competitionUuid}&strtDt={YYYY-MM-DD}&endDt={YYYY-MM-DD}
tmcl	GET all player memberships for the specified tournament calendar. Pass the tournament calendar UUID to the tmcl parameter. GET https://api.performfeeds.com/soccerdata/transfers/{outletAuthKey}?_rt={mode}&_fmt={dataFormat}&tmcl={tournamentCalendarUuid}

Sample Calls

These sample calls let you see an example URL and the response - click on the links below (hyperlinks open in a new window).

- [XML - prsn](#)
- [JSON - ctst](#)
- [XML - comp + strtDt + endDt](#)
- [XML - tmcl](#)

Feed Output

Here, you can find an explanation of all possible response fields and data. This is XML but fields in the feed response are similar for JSON.

- ▶<transfers> (XML only)
- ▶<person>
- ▶<membership>
- ▶<transfer>