

LATENCY AND HDR/ARC SUPPORT UP TO 230FT

SKU: BG-EXHKVM-70C MSRP: \$199.00 STATUS: IN STOCK

ADD TO CART →





COMPLIMENTARY DESIGN SERVICES AND ENGINEERING SUPPORT



3 YEAR WARRANTY =



Configure the Perfect Solution GET STARTED









TECH SPECIFICATIONS

Model No.	BG-EXHKVM-70C	
Technical	Transmitter	Receiver
Input	HDMI IN x1, DC2.1 x1, USB-A x1	DC2.1 x1, RJ45 x1, USB-A x2
Output	HDMI OUT x1, RJ45 x1	HDMI OUT x1, S/PDIF OUT x1
HDMI compliance	HDMI2.0, compatible HDMI1.4	
HDCP compliance	HDCP2.2, compatible HDCP1.4	
Transmission meduim	CAT6/CAT6A/CAT7	
Transmission distance	≤70 meters	
Video bandwidth	18Gbps	
Video support	1280x960, 1280x800, 1280x768, 1680x1050, 1360x768, 1366x768, 1600x900, 1024x768, 800x600, 480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/80Hz, 1080p@50/60Hz, 3840x2160@24/25/30/50/60Hz, 4096x2160@24/25Hz	
Audio formats	LPCM/DTS-HD/DTS-Audio/Dollby Digital 5.1CH	
HDR10 (YUV4:4:4)	Supported	
HDMI Loop-out	Supported	
S/PDIF out	Supported	
EDID through	Supported	
KVM function	Supported	
Input TMDS signal	0.7~1.2Vp-p	
Input DDC signal	5Vp-p	
HDMI connector	Type A 19 Pins, Female	
Network cable standard	CAT6/CAT6A/CAT7, follow IEEE-5688 standard	
Mechanical	Transmitter	Receiver


Net weight	0.57lbs [260g]	0.57lbs [260g]
Power supply	5V/2A	5V/2A
Power consumption	4W	4W
Material	Aluminium alloy material+crystal panel	
Dimensions (LxWxH)	5.9 x 4.2 x 1.1in [150.0 x 107.0 x 28.4mm]	
Operation temperaure	-4~140°F/-20~60°C	
Storage temperature	-22 ~ 158°F /-30 ~ 70°C	
Relative humidity	0 ~ 90% (no condensation)	

RECOMMENDED PRODUCTS











8K UHD HDMI 2.1 Extender - ... \$999.00

Online