

A BRIEF REPORT ON PERMANENT MAGNET ASSISTED SYNCHRONOUS RELUCTANCE MOTORS

Petr Zakopal

XP14DES



Structure of the report:

- Introduction,
- Design,
- Control,
- Comparison to other machines,
- Recent research interest.



PMSynRelM

actively used in automotive and traction applications

control strategies based on known principles

may use relatively simple mathematical model for control



PMSynRelM

actively used in automotive and traction applications

control strategies based on known principles

may use relatively simple mathematical model for control



PMSynRelM

actively used in automotive and traction applications

control strategies based on known principles

may use relatively simple mathematical model for control



PMSynRelM

actively used in automotive and traction applications

control strategies based on known principles


may use relatively simple mathematical model for control



Stator




- **Delta** winding
- **Star** winding
- **Star-Delta** hybrid winding



Rotor




- internal/external
- power factor/wide power range \Rightarrow saliency ratio (L_d/L_q)
- shape/placement/number of flux barriers
- magnets - rare earth (with neodymium/dysprosium), non-rare earth (ferrites)



BONTHU, Sai Sudheer Reddy; CHOI, Seungdeog; GORGANI, Aida; JANG, Kibong. Design of permanent magnet assisted synchronous reluctance motor with external rotor architecture. In: 2015 IEEE International Electric Machines & Drives Conference (IEMDC). Coeur d'Alene, ID: IEEE, 05/2015, pp. 220–226. ISBN 978-1-4799-7941-7. Available from DOI: 10.1109/IEMDC.2015.7409063.


- embedded along the flux barriers, facing the q -axis (a)
- crossing the flux barriers, facing the d -axis (b)




NGO; HSIEH. Performance Analysis of Synchronous Reluctance Motor with Limited Amount of Permanent Magnet. Energies. 09/2019, roč. 12, č. 18, p. 3504. ISSN 1996-1073. Available from DOI: 10.3390/en12183504.

Control







$$T = \frac{3}{2}p_p |\underline{\psi}_{dq} \times \underline{i}_{dq}| = \frac{3}{2}p_p (\psi_d i_q - \psi_q i_d). \quad (1)$$

$$T = \frac{3}{2}p_p (L_d i_d i_q - (L_q i_q - \psi_{PM}) i_d) = \frac{3}{2}p_p (L_d i_d i_q - L_q i_q i_d + \psi_{PM} i_d). \quad (2)$$



Recent improvement was achieved:

- by using non-rare earth materials such as ferrites,
- by using novel hybrid stator winding structures,
- by analyzing rotor structure types and motor parameters based on the permanent magnet position and perfecting the design for the specific application,
- improving control strategies,
- variable flux motor (strategy).



Thank you for your attention.

