



Azure App Configuration audit logs.

Table attributes

 Expand table

Attribute	Value
Resource types	microsoft.appconfiguration/configurationstores
Categories	Audit
Solutions	LogManagement
Basic log	No
Ingestion-time transformation	Yes
Sample Queries	Yes

Columns

 Expand table

Column	Type	Description
_BilledSize	real	The record size in bytes
CallerIdentity	dynamic	Caller identity of this event.
CallerIPAddress	string	IP Address of the caller that triggered this audit event.
Category	string	The log category of the event.
CorrelationId	string	GUID for correlated logs.
ETag	string	An identifier for a specific version of the resource.
EventCategory	string	Audit category of this event.
_IsBillable	string	Specifies whether ingesting the data is billable. When _IsBillable is <code>false</code> ingestion isn't billed to your Azure account
OperationName	string	Name of the audited operation.


Column	Type	Description
RequestId	string	Unique request ID generated by server.
_ResourceId	string	A unique identifier for the resource that the record is associated with
ResultType	string	The result of the operation being audited.
SourceSystem	string	The type of agent the event was collected by. For example, <code>OpsManager</code> for Windows agent, either direct connect or Operations Manager, <code>Linux</code> for all Linux agents, or <code>Azure</code> for Azure Diagnostics
Status	string	Status of this audit event.
_SubscriptionId	string	A unique identifier for the subscription that the record is associated with
TargetResource	dynamic	Target resource that apply to the operation being audited.
TenantId	string	The Log Analytics workspace ID
TimeGenerated	datetime	Timestamp (UTC) when log was generated.
Type	string	The name of the table

AACHttpRequest

Article • 04/14/2025


Incoming requests to Azure App Configuration. The records in this table are aggregated. The 'HitCount' field describes the number of requests that each record accounts for.

Table attributes

 Expand table

Attribute	Value
Resource types	microsoft.appconfiguration/configurationstores
Categories	Azure Resources
Solutions	LogManagement
Basic log	No
Ingestion-time transformation	Yes
Sample Queries	Yes

Columns

 Expand table

Column	Type	Description
_BilledSize	real	The record size in bytes
BytesReceived	int	The total number of bytes received by the server across all requests included in this aggregated entry.
BytesSent	int	The total number of bytes sent by the server across all requests included in this aggregated entry.
Category	string	The log category of the event.
ClientIpAddress	string	IP Address of the client that sent the requests.
ClientRequestId	string	Request ID provided by client.
CorrelationId	string	GUID for correlated logs.


Column	Type	Description
DurationMs	int	The average duration of the operation, in milliseconds, of all the requests included in this aggregated entry.
HitCount	int	Count of requests that are included in this aggregated HTTP request log entry.
_IsBillable	string	Specifies whether ingesting the data is billable. When _IsBillable is <code>false</code> ingestion isn't billed to your Azure account
Method	string	HTTP Method.
RequestId	string	Unique request ID generated by server.
RequestURI	string	URI of the requests.
_ResourceId	string	A unique identifier for the resource that the record is associated with
SourceSystem	string	The type of agent the event was collected by. For example, <code>OpsManager</code> for Windows agent, either direct connect or Operations Manager, <code>Linux</code> for all Linux agents, or <code>Azure</code> for Azure Diagnostics
StatusCode	int	HTTP Status Code of the requests.
_SubscriptionId	string	A unique identifier for the subscription that the record is associated with
TenantId	string	The Log Analytics workspace ID
TimeGenerated	datetime	Timestamp (UTC) marking the start of the aggregation period.
Type	string	The name of the table
UserAgent	string	User Agent provided by the client.

AADB2CRequestLogs

Article • 04/14/2025


Logs generated by AAD gateway for displaying B2C tenant's web requests and its throttle info.

Table attributes

 Expand table

Attribute	Value
Resource types	microsoft.aadiam/tenants
Categories	Audit, Security
Solutions	LogManagement
Basic log	No
Ingestion-time transformation	No
Sample Queries	-

Columns

 Expand table

Column	Type	Description
AADTenantId	string	The AAD tenant ID of associated request.
_BilledSize	real	The record size in bytes
CallerIpAddress	string	Hashed format of caller IP address. Can be used to identify if a single IP address is using a large portion of traffic.
CorrelationId	string	The ID for correlated log analytics events. Can be used to identify correlated events between multiple tables.
_IsBillable	string	Specifies whether ingesting the data is billable. When _IsBillable is <code>false</code> ingestion isn't billed to your Azure account
OperationName	string	Name of the operation.
_ResourceId	string	A unique identifier for the resource that the record is associated with
ResultSignature	string	The HTTP status code of the corresponding REST call.

Column	Type	Description
ResultType	string	Indicates whether the request is throttled or not.
SourceSystem	string	The type of agent the event was collected by. For example, <code>OpsManager</code> for Windows agent, either direct connect or Operations Manager, <code>Linux</code> for all Linux agents, or <code>Azure</code> for Azure Diagnostics
_SubscriptionId	string	A unique identifier for the subscription that the record is associated with
TenantId	string	The Log Analytics workspace ID
TimeGenerated	datetime	The date and time of the request received at the AAD gateway in UTC.
Type	string	The name of the table