

1.4 RGB

Andre Monteiro

Term 3, 2025

Algorithm

Reduce the problem to an ordinary shortest path instance by first filter the graph so that it only contains edges that join vertices of different colours.

Then a plain BFS gives the required path.

- (a) Build a new graph $G' = (V, E')$ with

$$E' = \{\{x, y\} \in E : \text{colour}(x) \neq \text{colour}(y)\}.$$

Checking each original edge once costs $O(|E|)$.

Justification (validity of G')

- Every colour-alternating path in the original graph consists only of edges connecting vertices of different colours, so these edges are preserved in G' . Conversely, any path in G' uses only edges joining different colours, so any path found in G' is a valid colour-alternating path in G .

- (b) Run a standard BFS from u to v on G' and output the path it finds.

Time complexity of BFS: $O(|V| + |E'|)$

Justification (Choice of BFS)

- BFS finds a path with the minimum number of edges in an unweighted graph. Since G' preserves all legal alternating edges from G , this path is a shortest colour-alternating path.

Complexity

Total time is

$$O(|E|) + O(|V| + |E'|) = O(|V| + |E| + |E'|).$$

Since $E' \subseteq E$, we have $|E'| \leq |E|$, so

$$O(|V| + |E| + |E'|) = O(|V| + 2|E|) = O(|V| + |E|).$$

Correctness Proof

Forward direction (forward correctness)

- We need to prove that when BFS is applied to the filtered graph G' , the shortest path it finds does not use edges with both vertices of the same colour.
 - By construction, $G' = (V, E')$ where

$$E' = \{\{x, y\} \in E : \text{colour}(x) \neq \text{colour}(y)\}.$$

- BFS only traverses edges in G' .
- Therefore, every edge in any path returned by BFS connects vertices of different colours.
- Consequently, any path found by BFS is a valid colour-alternating path in the original graph G .

Backward direction (backward completeness)

- We need to prove that BFS on G' will consider every path that does not use edges with vertices of the same colour.
 - Let p be any colour-alternating path in the original graph G .
 - By definition, all edges of p connect vertices of different colours.
 - Since G' contains all edges connecting vertices of different colours, p exists as a path in G' .
 - BFS explores all paths in G' , so every colour-alternating path in G is considered by the algorithm.

Conclusion

By reducing the graph first and then calling BFS, the shortest colour-alternating path is found in:

$$\boxed{O(|V| + |E|)}$$